
ARCHITECTURAL

RECORD



JUNE 1946

SMALL THEATERS

0 N

RG

100

35

CORD

oth

FECissue - was pubntire

have ound form

these rints e deoated.

Y.

.....

R. 5-46

RECORD



SPECIFY 'INCOR' FOR EARLIER OCCUPANCY AT LESS COST



Time was never so expensive as it is today—and time-saving with 'Incor' 24-Hour Cement was never so important. On this 6-story apartment, built in 1937, 'Incor' saved 7 working days, with 40% less forms—a net cash saving, at 1937 costs, of \$1.45 per cu. yd. of concrete. At today's costs, this net saving would be \$2.81 a cu. yd. on 2270 cu. yds. concrete. Nearly 20 years' experience shows that 'Incor' time and form savings often run to double these figures, on all types of structures—concrete-frame, steel-frame and wall-bearing. Specify 'Incor'* 24-Hour Cement: save 40-60% on form material and make-up, cut time and overhead, get earlier completion at less cost. Write for "Cutting Concrete Costs"—packed with time- and money-saving suggestions.

LONE STAR CEMENT CORPORATION



LONE STAR CEMENT, WITH ITS SUBSIDIARIES, IS ONE OF THE WORLD'S LARGEST CEMENT PRODUCERS: 15 MODERN MILLS, 25,300,000 BARRELS ANNUAL CAPACITY ... OFFICES: ALBANY . BIRMINGHAM . BOSTON . CHICAGO . DALLAS HOUSTON . INDIANAPOLIS . JACKSON, MISS. . KANSAS CITY, MO. . NEW ORLEANS. NEW YORK.NORFOLK.PHILADELPHIA.ST. LOUIS.WASHINGTON, D. C.

19 Years' Outstanding Performance . . . 'INCOR' . . . America's FIRST High Early Strength Portland Coment


JUNE 1946

EM the ings of rom uces

MS vide ED.

NN.

litorial an









STAIRS



DECORATIVE GRILLES



ENTRANCE DOORWAY



SPANDRELS



DIRECTORY

for small homes, too,

ARCHITECTURAL METALS

add the mark of distinction!

Maybe you've always thought of Architectural Metals in terms of commercial, monumental or institutional buildings. If so, it's time to enlarge your thinking.

Architectural metals, because of their extreme versatility and because they combine beauty with utility, can be used in practically every type of building—including small houses.

For instance, items such as smartly designed handrails can do much to improve the whole exterior appearance of a home or add distinctive beauty to its interior. The use of aluminum windows and prefabricated lightweight steel stair units for residences are other instances where metal work can serve you and your clients to good advantage.

As you design tomorrow's buildings—whether they be residential or commercial, large or small—use architectural metals—for extra strength, extra protection in stairs, railings, door frames, windows and in hundreds of other building items. Use them, too, in the entrance, for store fronts, marquees, grilles, and all types of exterior and interior decorations.

The manufacturers and fabricators of architectural metals are anxious to work with you, to offer helpful suggestions and to be of assistance in any way they can. Consult them whenever you plan new buildings.

Architects interested in obtaining a copy of the new Handbook on Stairs and Railings published by the Association are invited to contact any of the members. For a Directory containing names and addresses of Leading Fabricators write to Dept. AR-6.

NATIONAL ASSOCIATION OF

ORNAMENTAL METAL MANUFACTURERS

209 CEDAR AVENUE, TAKOMA PARK, WASHINGTON 12, D.C.



NON-FERROUS WINDOWS



FLAGPOLE BASE



STORE FRONTS AND MARQUEES




FIXTURES



HAND RAILINGS

ECORD



In almost all large buildings, the selection of piping for the boiler room is a phase of the planning job. The final specification plays a big part in determining the life and satisfaction of the installation, and so merits unusually careful attention.

In the boiler room of the United States Naval Air Station at Corpus Christi, Texas, the designers gave both performance and appearance proper weight. The efficiency suggested by the attractive arrangement is confirmed by the careful selection of material. As an example . . . in suction lines, discharge lines, boiler connections, condensate returns, and hot water lines, where corrosion threatens useful life, Byers Wrought Iron was installed.

Wrought iron is particularly well fitted to withstand the corrosive conditions encountered in all these services, as engineering records can testify. One engineer reported not long ago that wrought iron pipe was installed in his boiler

room 24 years ago. Only recently were there any signs that replacements were necessary. Conditions vary so widely that what would be excellent life in one locality might be short life in another, but engineering experience indicates that under any given set of conditions, wrought iron can generally be expected to last longer, and to show a lower cost-per-year.

Most piping replacements are not made necessary by complete failure of the pipe, but by holes that start from severe pitting. The unique structure and composition of Byers Wrought Iron help to prevent such failures. Tiny fibers of glass-like silicate slag are threaded

through the main body of highpurity iron. These fibers act like baffles, to halt and disperse corrosive attack uniformly over the entire surface. The initial protective scale is anchored by these fibers, and so serves as a shield for the underlying metal.

When you are concerned with the selection of pipe for any building services, you may find some helpful information in our bulletin, "Wrought Iron for Piping Systems." May we send you a copy?

A. M. Byers Co., Pittsburgh, Pa. Established 1864. Boston, New York, Philadelphia, Washington, Atlanta, Chicago, St. Louis, Houston, Seattle, San Francisco.

CORROSION COSTS YOU MORE THAN WROUGHT IRON

BYERS

GENUINE WROUGHT IRON
TUBULAR AND HOT ROLLED PRODUCTS

ELECTRIC FURNACE ALLOY STEELS · OPEN HEARTH ALLOY STEELS CARBON STEEL TUBULAR PRODUCTS

ARCHITECTURAL

RECORD



Copyright 1946 with all rights reserved F. W. DODGE CORPORATION • Vice-President in charge of Magazine Division, H. Judd Payne • EDITORS: Editor-In-Chief, Kenneth Kingsley Stowell, A.I.A.; Managing Editor, Emerson Goble: Associate Editors, Douglas Haskell, Charles Mattlage, John W. Ragsdale; Associate in South America, Edmund J. Whiting, A.I.A.; News Editor, Florence A. van Wyck • ART DEPART-

MENT: Gail Twichell; Peter Piening, Consultant • CONSULTANTS: Industry Relations Consultant, Thomas S. Holden; Statistical Consultant, Clyde Shute; Building Economics Consultant, Norbert Brown; Field Research Consultant, Clifford Dunnells, Jr.

Architectural Record (combined with American Architect and Architectural is published monthly by F. W. Dodge Corporation, 10 Ferry St., Concord, N. H., with Editorial and Executive Offices at 119 West & Street, New York, N. Y. Thomas S. Holden, Pres., Howard J. Beringer, Vice-Pres., Chan-Tress., Irving W. Hadself, Vice-Pres., Chanco, L. Williams, Vice-Pres., Sanford D. Stockton, Jr., Secy.; Walter F. De Solx, Ast. Treas., Edwin H. Freed, Ast. Trea

VOL. 99 • NO. 6	Jun	e 1	946
WHAT ARE ESSENTIAL BUILDINGS?	e e		71
Part I. Plans of Various Hospital Units by Hospital Facilities Section, U Health Service	. S. Pi	 ublic	72
SIX VETERANS ADOPT A BASIC PLAN	• •		91
CO-OP SCHEME CUTS HOUSE COSTS	lls Proj	ject,	92
FOUR HOUSES IN GROUP EFFORT			94
Cooperation Pays in Small Project for Four M.I.T. Professors. David J. and Associates, Architects	Abrah	ams	
BUILDING TYPES STUDY NO. 114 THE SMALL			
(400-SEAT) MOTION PICTURE THEATER Prepared under direction of Ben Schlanger, Architect, In collaboration Stow Reisner, Architect, Max O. Urbahn, Consultant, William A. Hoffbneer, Daniel W. B. Warner, Architect, Edward Content, Acoustical Engineer E. Sutton, Mechanical Engineer	erg, E	ngi-	99
BUDGET AND SITE FACTORS			101
THE AUDITORIUM			103
AUDIENCE ACCESS AND CONVENIENCES			108
"EXPLOITATION" FOR THE SHOW			111
INTERIOR MATERIALS			112
ARCHITECTURAL ENGINEERING Technical News and Research	:h		113
STRUCTURAL ECONOMY		× .	113
PROJECTION IN THE SMALL THEATER	, , ,		115
SMALL-THEATER ACOUSTICS			116
HEATING, VENTILATING AND AIR CONDITIONING			117
ACOUSTICS OF MODERN AUDITORIUMS			119
PRODUCTS For Better Building			124
MANUFACTURERS' LITERATURE			126
TIME-SAVER STANDARDS Motion Picture Theater Data ,			129
THE RECORD REPORTS News from the Field			7
REQUIRED READING			26
INDEX TO ADVERTISEMENTS			198
SEMI-ANNUAL INDEX			200
COVER: Cartoon figures from "Make Mine Music," courtesy of Walt Disne	v Stud	ios	

like orroe enctive bers,

with ouildsome letin, ems."

New gton, Hous-

RON

LS



of the many Watrous Points of Superiority


Water Saver Adjustment
Self-Cleansing By-Pass
Single-Step Servicing
Self-Tightening Handle
Packing
Screenless Silent-Action
Sturdy Brass and Bronze
Construction

A small feature . . . Watrous Self-Tightening Handle Packing . . . yet just one more of the many features that go to make a great flush valve!

It requires no periodic tightening . . . eliminating maintenance . . . because its spring-loaded packed stem automatically maintains proper tension on the packing at all times . . . provides real protection against leakage. Note the illustration.

When you specify Watrous Flush Valves you get Self-Tightening Handle Packing on every valve. It is one of the reasons why the selection of Watrous Flush Valves is a constant source of satisfaction over the years to everyone concerned.

THE IMPERIAL BRASS MFG. CO., 1240 W. Harrison Street, Chicago 7, III.





Watrous Flush Valves

THE RECORD REPORTS

Lumber Situation Still Not Happy • Housing Program Is Under Way • Rental Housing Encouraged • VA Future Construction Destined for Private Architects and Engineers

As the rare days of June beamed on the nation's capital, officials professed to see the sun peep through — here and there — the dark clouds hanging over housing.

Nobody expects the clouds to clear away altogether, but optimism begins to show in some official faces. Analysts point notably to lumber. During April, May and June production is expected to total nearly eight billion feet or 30 per cent more than in the first three months of the year. Gradual alleviation of the tight lumber situation is anticipated by officials during the rest of the year.

ınce

roper

ainst

ening

ction

r the

7, 111.

Production Still Lagging

Only recently, however, Richard A. Colgan, Jr., executive vice president of the National Lumber Manufacturers Association, told the Senate Banking and Currency Committee that lumber production cannot possibly reach the government's goal unless OPA is ordered by Congress to change some of its methods of fixing prices, and charged that "inadequate price ceilings alone are responsible for most of our decreased production today."

"I cannot predict this year's total," Mr. Colgan said, "but it obviously will not approach the goal needed for the housing program — 36 billion board feet. That was our record production of recent years, reached in 1942. We could produce that much and more — the capacity is available. But the present rate is only at a little more than 24 billion feet, or two-thirds of what we need. It may rise somewhat, but under present conditions we cannot possibly attain the production goal set for us — and the housing program will inevitably fail by that much."

'47 Outlook Tight

It is pertinent here to note that in 1947 a lumber demand of about 42 billion board feet is expected as compared to an anticipated 1946 output of 32 billion board feet. How to replenish war-depleted stocks in the face of constantly growing requirements remains an unanswered problem.

Wild scrambles for lumber brought widespread black market charges, in the wake of which OPA and the Department of Justice set machinery to work for criminal prosecutions. Buyers and sellers are held equally responsible under the

As one means of boosting production,

Representative Thom of Ohio introduced in Congress a bill, H. R. 5973, authorizing a yearly appropriation of \$1 million for the Secretary of Agriculture to provide technical assistance to smalland medium-size lumber mills in increasing their output.

Housing Program Moves

The beginning of summer saw Wilson Wyatt's emergency housing program starting forward from coast to coast. Intended chiefly to aid veterans, it is expected, despite "stop" orders on much proposed construction, also to bring about increased necessary nonresidential activity. Wyatt himself warns against absolute reduction of construction competing with homes. As he puts it, people need other things besides housing.

Materials and manpower will be available to essential projects such as schools, hospitals, highways, streets, sewers and other utilities as well as industrial plants producing needed materials. In fact, the Housing Expediter says, there will be more, not less employment, building and investment in the heavy-construction nonresidential fields. Civilian Production Administration regional offices will screen out non-essentials (thousands of stop orders were issued before the end of April) and take care of applications for industrial and commercial construction.

CPA Takes Action

With a revised Priorities Regulation 33, CPA now lets FHA pass on housing construction of all kinds, including maintenance, repairs and alterations. It extends to the Department of Agriculture authority to pass on farm building applications other than dwellings. It adds items to the critical list on which priorities assistance is given, including asphalt and tarred roofing products, building board, gypsum board and lath and asbestos-cement siding shingles.


Washington is keeping in mind preference for veterans in allowing new store construction in the new housing developments. Where chain stores are given entry, it is assumed, they will hire veteran managers, clerks, salesmen, etc. Favor is expected for erection of stores in new communities rather than in sections already served.

Rental Housing Wanted

Wyatt advises that, with rental housing needs heavy, all possible encouragement is being given to apartment building projects, large and small. Expansion of Title VI of the National Housing Act, under the Patman Bill, he adds, would virtually insure private builders against loss in large rental housing units — 90 per cent loans on current costs rather than normal values.

The swelling demand for building materials caused by the veterans housing program, estimates the Housing Chief, will reach a total nearing \$15 billion. Besides lumber requirements, indicated earlier, he points out that demand for brick this year will run two-and-a-half times last year and three times as much

(Continued on page 10)



- Drawn for the RECORD by Alan Dunn



Whether remodeling a loft building or glazing an office hallway, Blue Ridge Decorative Glass achieves new, sparkling beauty—and "borrows" light for added brightness.


The floor-to-ceiling office partitions shown above utilize Satinol Louvrex glass, while the hallway partitions feature Satinol Flutex. Many other attractive patterns are manufactured by the Blue Ridge Glass Corporation of Kingsport, Tenn., and sold through leading glass distributors by Libbey Owens Ford. Architects, designers and contractors may specify plain or Satinol finish, semitransparency or complete obscurity. And these glasses may be Securitized (heat tempered) for greater resistance to thermal and physical shock. Most patterns are also available in modified bends. For further information, write the Blue Ridge Sales Division, Libbey Owens Ford Glass Company, 8966 Nicholas Building, Toledo 3, Ohio.




Smart hallway in a Chicago publishing office. Architect: James F. Eppenstein.


"Design it with one of the 5 EX's" LINEX FLUTEX STYLEX






LOUVREX









DOUBLEX



BLUE RIDGE Decorative GLASS

FOR SOFT, DIFFUSED LIGHT . SMART DECORATION . COMPLETE PRIVACY





WHEN YOU'RE "LOOKING AROUND" FOR SAVINGS — DON'T FORGET TO LOOK

UP

Wherever processing operations create humid atmospheres, there's generally roof trouble . . . from corrosion, spalling or decay . . . so when you're plugging maintenance leaks that drain away profits, don't overlook the roof.

Koppers pressure-treated lumber has helped a lot of plants solve this problem. It doesn't corrode: there is no reduction of strength or section in aggressive atmospheres. It doesn't spall. And it is dependably protected against decay. Special treatments are available to meet special conditions: "Asidbar"*, a plastic-impregnated wood, for unusually corrosive atmospheres, and a salts treatment that imparts a high degree of fire-retardance. You will find some helpful information on the many jobs pressure-treated wood is doing for industry in our illustrated bulletin, "Economical and Permanent Construction with Pressure-Treated Wood." May we send you a complimentary copy? Wood Preserving Division, Koppers Company, Inc., Pittsburgh 19, Pa.

* Trade Mark

hicago

hitect:

RECORD



as in 1947. Clay sewer pipe and gypsum board and lath needs will run double 1945. For cast iron radiation, the 1946 need will be more than four times, and 1947 almost five times, 1945 production.

CPA figures show that the two groups representing most of the building materials — stone, clay and glass products and lumber products — plan capital outlays of over \$800 million for the first year following the close of hostilities as against expenditures for such purposes of less than \$100 million in 1939.

Non-Housing Authorized

More than \$96,000,000 worth of nonhousing construction has been authorized since enactment of the Veterans Housing Program Order, the CPA reported late in April.

From March 26, when the order went into effect, to April 11, the field construction offices the CPA maintains in 71 cities had received 6,037 applications for construction authority out of which 1,431 applications with a value of \$96,971,313.99 were approved and 167 applications with a valuation of \$5,515,950.47 were denied. Of the total number received, 557 applications were withdrawn, 3,879 are still pending, and 40, with an individual valuation of more than \$1 million each and a total valuation of \$151,227,726, were sent to the Washington office for disposition.

More Prices Rise

OPA's Paul Porter continues upping price ceilings, with many products released from controls altogether. Stimulation of production, he cites as one reason for the actions. Among building materials the range varies. Lumber items recently allowed boosts are Northeast, Appalachian and Southern hardwood lumber, red cypress, Western pine, Douglas fir and hemlock.

Increases also affect white cedar shingles, Douglas fir doors and screen doors using wire meshes as well as glazed sash, window and garage doors. Other items upped include fireclay and silica refractory brick, warm air furnaces, water heater tanks, domestic fuel oil storage tanks, water storage tanks and solar tanks.

Atom Branches Out

Among major items on the legislative program prior to adjournment of the current session of Congress is the bill to set up controls over atomic energy. The plan is to establish a special commission with a subsidiary general advisory committee and military liaison committee, and to continue research.

Although ultimately far-reaching effects on the nation's economy are acceded, immediate ramifications of atomic energy are such that it will be long before building activity will be reshaped in any sense. However, the pending legislation makes provision for the Atomic Energy Commission not only to acquire materials and property but also to erect buildings and acquire and sell real estate. This includes requisitioning powers and powers of eminent domain. Presumably any such activity, at least for the present, will be for the housing, health, safety, welfare and recreation of personnel employed by the Commission. Ownership of production facilities is prohibited to private interests.

CD Funds Increased

Due to the incorporation in the Commerce Department of certain carry-over wartime activities, its annual appropriations by Congress show a sizable increase over last year. Included, presumably in blanket fashion and without specific mention, are certain activities of the new Construction Division, which absorbed statistical work of the old War Production Board.

High Court Backs N.Y.C.

Of interest is the recent decision of the Supreme Court upholding an amendment to New York's Multiple Dwelling Law. This 1944 amendment required that lodging houses "of non-fireproof construction existing prior to the enactment of this subdivision" comply with certain new requirements, including the installation of an automatic wet-pipe sprinkler system. The Queenside Hills Realty Co. instituted suit for a declaratory judgment holding these provisions unconstitutional, but the high tribunal upheld the city.

Save that Neighborhood!

In a discussion of "neighborhood conservation" as part of its series on urban planning, the Federal Home Loan Bank points out that cities lose to the suburban fringe new construction that goes there because of the shabbiness of the older city neighborhoods.

While the present dearth of building lots, it says, will probably put some new construction in these neighborhoods, more might be attracted if steps were being taken to keep them sound and attractive.

It calls attention to the need for a thorough study of the costs and methods (Continued on page 12)

DODGE SURVEY UNCOVERS CONSTRUCTION BOTTLENECKS

The construction industry's goal of full production has been stymied by inadequate price ceilings, strikes directly and indirectly affecting production in plants and factories, inadequate manpower, inadequate raw materials, and inadequate supplies other than raw materials. This is the conclusion reached by F. W. Dodge Corp. following a survey conducted among top executives of the nation's leading building materials and equipment producers.

Government regulations, particularly administration of the Price Control Act, are cited as the chief bottleneck of production by producers of such materials and equipment as masonry products, wood, metal products, glass, roofing and siding, heat insulation, wallboard, floor and wall materials, paints and finishes, doors, windows, hardware, sanitary equipment, water supply and drainage,

electrical distribution, air conditioning and heating.

Some producers have already discontinued nonprofitable lines, among them roofing, siding, heat insulation materials and hardwood. The Wyatt program restricting nonresidential construction has been of deep concern to many manufacturers, particularly in the heating and hardware fields and among manufacturers of building stone and cement.

Paint manufacturers, the only important group not faced with the problems of strikes, inadequate or inefficient manpower, are being hit hard by price controls, inadequate supplies of flaxseed, linseed, drying oils and pigments, metal containers and even paper for printing labels.

Strikes in their own plants or in the plants of their suppliers have affected production in masonry materials, metal products, glass, roofing and siding, waterproofing, doors, windows, hardware, sanitary equipment, water supply and drainage, air conditioning, heating and lighting equipment. Inadequate manpower was reported as a bottleneck in all the lines above, with the exception of metal products, waterproofing, and lighting. Inefficient manpower was reported as a problem among producers of masonry materials, metal products, glass, roofing and siding, heat insulation, wall-board, floor and wall materials, hardware, air conditioning and heating.

Inadequate raw materials were reported as a problem among producers of wood products, metal products, roofing and siding, wallboard, paints and varnishes, doors, windows, hardware, sanitary equipment, water supply and drainage, air conditioning, heating and lighting. Inadequate supplies other than raw materials are affecting production of wood products, paints and varnishes, hardware, water supply and drainage, air conditioning, heating and lighting.

e Comry-over approsizable d, previthout tivities , which ld War

Y.C. sion of amendwelling equired reproof enacty with ing the et-pipe e Hills leclara-

ood!
od conn urban
n Bank
he subnat goes
of the

ribunal

ouilding me new orhoods, ps were nd and

d for a nethods page 12)

ardware, ply and ing and ise manick in all ption of nd lightreported of mass, glass, on, walls, harding.

were reroducers ets, roofints and ardware, oply and ting and her than oduction arnishes, lrainage, ghting.

ECORD

Charm and Beauty



For low-cost concrete homes


Could be, that available concrete and lightweight aggregate block will play a big part in small home construction. And certainly this type of construction finished with Medusa Portland Cement Paint makes a charming small home.

Medusa Paint has Portland Cement as a base—the same material used in the block itself. That's why it bonds perfectly, making a permanent decorative and weatherproofed cement-like finish. Medusa Paint's low first-cost and easy application—helps you keep the total price within the budget. It mixes with water—is sprayed or brushed on damp or dry, inside or outside on

concrete, stucco, or masonry surfaces. Your choice of eight distinctive colors, black and white. Here's paint that saves time because it can be used on new damp construction and can be applied on damp days.

For all the facts on Medusa Portland Cement Paint, write today for the descriptive illustrated book "How to Paint Concrete, Stucco, and Masonry" —26 years of experience are packed into this volume.

"OVER 53 YEARS OF CONCRETE PROGRESS"





THE architect who specifies Penetrating Seal-O-San for hospital floors wins the gratitude of everyone charged with efficient hospital management. For Seal-O-San not only keeps the surface clean, it makes certain that every wood cell below the surface remains clean.

A Seal-O-San finish becomes part of the wood. Penetrating deep, the liquid fills the empty cells, eliminating the hidden sources of dirt. Sealing the cells, it forms a protective finish that actually reinforces surface fibres. Thus, a Seal-O-San finished floor is covered with a wear-resisting seal that locks out dirt or moisture. As a result, stains and dust are easily removed. Costly scrubbing is seldom necessary.

Moreover, the tougher Seal-O-San finish keeps dirt from piercing the surface and getting a foothold. It puts an end to cracks and crevices that harbor germs or dirt. That's why a Seal-O-San floor stays clean longer... why maintenance becomes simple and inexpensive.

Unlike hard, brittle, surface finishes, Seal-O-San will not chip, crack, or peel. Consequently, Seal-O-San has convinced hundreds of hospital administrators that it will not break down where traffic is heaviest.

Seal-O-San leaves a beautiful, softlustre, natural finish—as smooth and polished as a fine piece of furniture. And the ease of application—with a lambswool mop—brings worthwhile labor savings.

Your insistence on beauty, cleanliness and simple maintenance for hospital floors will inevitably lead you to Seal-O-San. Why not write for specifications and details—today!

HUNTINGTON LABORATORIES INC

P-E-N-E-T-R-A-T-I-N-G
SICAL-O-SAN
PERFECT SEAL AND FINISH FOR WOOD FLOORS

THE RECORD REPORTS

(Continued from page 10)

of house maintenance and repair and for new methods of financing repairs and improvements.

Home Costs Surveyed

NHA reports the results of a late March survey on price increases for homes and building lots from spring, 1940, to February, 1946 as follows:

Lower-priced homes up 65 per cent; medium-priced, 57 per cent; lots, 61.8 per cent. Regionally, home prices rose most in the Pacific area, least in the Middle Atlantic area.

Last September to February this year: up 17.7 per cent, 14.8 per cent, 23.3 per cent respectively; "H-2" houses over WPB ceilings (lifted last fall), 30.5 per cent.

Federal Steps Vary

Recent federal developments touch a wide variety of topics of immediate interest to architects, building contractors and others in the construction industry. Here is summary mention of a few:

1. CPA hopes increased output of building materials will permit relaxation, if not complete lifting, of its Veterans Housing Program Order 1 by next January.

The Census Bureau is making a check of building codes and will publish its compilations.

3. Housing experts are seeking now to correct only the "worst" faults in local building codes; analysis of about 600 codes is under way. Efforts at correction will be made through local chambers of commerce, and specific trade and realty groups.

4. In many parts of the country, Labor Department officials say, increased availability of materials would not help much since contractors could not get sufficient workers.

5. NHA wants to stimulate expansion of local utilities and traction companies into the suburbs to service new housing developments.

6. The Stabilization Director is pressing to check sharp increases in commercial rents, particularly in the interests of new ventures, with emphasis on veterans' projects.

7. The Reconversion Office has under way a survey of guaranteed annual wage plans and includes construction among the industries to be studied. When completed, the plan is to circulate the findings among employers and trade unions rather than to seek legislation.

8. Rear Admiral Kirby Smith as General Deputy Expediter for the veterans' emergency housing program is putting first emphasis on problems of supply and

(Continued on page 14)

page 10) air and irs and

d a late ses for spring, follows: er cent; ts, 61.8 es rose in the

is year: 3.3 per es over), 30.5

touch a mediate g contruction ntion of

tput of relaxaof its ler 1 by

aking a publish

ing now in local out 600 rrection nbers of d realty

country. say, ins would rs could

cpansion mpanies housing


is pressin comhe interhasis on

ual wage among nen comthe finde unions

as under

as Genveterans' putting pply and page 14)

ECORD




They also have higher flexible strength with less air friction

and cleaner operation. Hydraulic expansion of tubes into wide collared fins, another exclusive McQuay feature, provides a permanent mechanical bond with greater contact surface between fins and tubes. Copper headers are used in all McQuay coils, because inherent flexibility of copper enables it to meet the unequal contraction and expansion. This results in the strongest possible construction.


McQuay coils are available in a wide variety of styles and sizes, both standard and special coils for steam, hot water, cold water, brine, direct expansion and other applications. For complete information write McQuey, Inc., 1605 Broadway Street N. E., Minneapolis 13, Minnesota. Representatives in all principal cities.





To the inherent characteristics of steel floor plate (such as durability, ability to stand tough traffic, oil, heat, fire and crackproof and no maintenance cost) add, for A. W. Super-Diamond these three distinctive advantages well worth knowing about for safer floors. Notice the shape of the elevations and the pattern? 30% minimum contact area with the shoe. Sloping sides that maintain "sharpness" of contact, resist dirt collection, make for easier cleaning, better draining. And a pattern that matches more easily with less scrap! These are reasons why alert architects, builders, product engineers, and purchasing agents are insisting on AW Super-Diamond Floor Plates.

Write For 16 page Booklet L-33 Giving Helpful Information on Weight Per Square Foot and Maximum Sizes. Alan Wood Steel Company, Conshohocken, Pa.



THE RECORD REPORTS

(Continued from page 12)

production. He previously developed and supervised a \$4.5 billion building program for the Navy Department.

9. No matter what may be done taxwise in the last minute by the present Congress, signs on Capitol Hill point to a general tax revision in 1947.

VA Changes Policy

The A.I.A. has announced that with the exception of some few jobs already long since on the boards, the entire construction program of the Veterans Administration will be given out to architects and engineers in private practice. The program will be in progress for a number of years and will include several hundred million dollars worth of construction.

With the collaboration of the A.I.A., the VA has set up a board of consultant architects. These consultant architects are assisting the Administration to develop the various criteria and standards for the guidance of those architects and engineers engaged in the program.



WYATT, VETERANS MEET

Early last month national officers of the American Legion, the American Veterans Committee, the Veterans of Foreign Wars and the American Veterans of World War II met with Housing Expediter Wilson W. Wyatt in the first session of NHA's new Veterans Advisory Council. Officers of the Disabled American Veterans, also invited, could not attend. The Council will meet regularly with Mr. Wyatt for the dual purpose of keeping him informed of veterans' views, criticisms and suggestions and keeping the veterans up to date on the problems and progress of the emergency housing program.

Several interesting proposals came out of the first session:

1. Stimulation of the building trades apprenticeship programs by calling for Joint Management-Labor Apprenticeship Committees where they do not already exist and by interesting the veterans in the long-term advantages of learning construction crafts.

2. Permission to build homes "slightly" over the \$10,000 ceiling for veterans with very large families where sufficient space cannot be obtained otherwise in areas of especially high construction costs.

3. Permission for home owners, in cases where a state might have to exercise eminent domain and remove houses in the way of essential highways or other public construction, to move and rehabilitate their homes, even though such home owners be non-veterans.

(Continued on page 140)

age 12) eloped ilding nt. ne taxresent

oint to

t with dready re conns Adarchiactice. s for a several th of

A.I.A., sultant hitects ion to standchitects gram.

icers of nerican rans of eterans g Expesession y Counmerican attend. with Mr. keeping s, critiing the roblems housing

s came

g trades lling for renticedo not the vettages of

slightly" ans with nt space areas of ts.

ners, in to exere houses or other and reugh such

page 140)

ECORD

For huge multitier bookstacks or shelving for small libraries Call on SNEAD & COMPANY

Typical SNEAD Library Installations U. of Alabama U. of California Cal. State Library Leland Stanford U. Library of Congress **Army War College** U. of Notre Dame U. of Colorado Loyola U. Dartmouth College Ohla State U. U. of Philippines U. of Puerto Rico Library of Hawaii Vatican Library Nat'l Museum Nat. Hist., Paris **Joint Universities** Skeleton steel bookstack structure, Yale University Library

JAMES GAMBLE ROGERS, ARCHITECT

For many generations Snead & Company has been the leader and pioneer in the design and construction of library equipment. Whether you are planning a large multitier bookstack or a library of modest size, it will pay you to contact us for a free consultation.

We will gladly assist in the preparation of plans and specifications, and submit a quotation. Since proper planning takes time, we suggest that you let us start without delay.

Write for the Snead bookstack catalog containing engineering and library planning data.

Maria Mitchell Library, Nantucket, Mass., built completely by Snead & Company, including book ranges and other equipment.

Since 1849, the Snead symbol of lasting beauty, quality and progress in metal con-



SNEAD & Company FOUNDED 1849

Designers, manufacturers and erectors of library bookstacks and steel partitions

Sales Office: 96 Pine Street, JERSEY CITY 4, N. J.

Main Office and Plant: ORANGE, VA.

PREFABRICATORS ANNOUNCE PLANS



Shelter Industries' two-bedroom house

PREFABS FOR VETERANS

Falling in with Housing Expediter Wyatt's emergency housing program, a number of prefabricators have announced mass production plans of small, quickly erected, low-cost units. Among them:

Shelter Industrie:


Already being manufactured for sale to veterans at a factory price of \$4,685, with first deliveries anticipated by the end of this month, is Shelter Industries Inc.'s two-bedroom house. Of permanent construction designed to meet all FHA space and structural requirements, this house is a basic unit consisting of living room, two bedrooms, bath and dinettekitchen; it is easily expandable by the addition of a third bedroom and a dining alcove.

Floor, exterior and interior walls and roof are all factory-fabricated, stressed-skin plywood panels, insulated with a two-ply aluminum foil insulation providing three separate air spaces between the panels. Equipment includes a choice of gas or oil circulating warm air furnace, gas or electric hot water heater, all plumbing, tub-shower bath combination with all other bathroom fixtures, and complete kitchen equipment including sink, cabinets, electric refrigerator and gas or electric range. All of these are designed and built into the house in one

Floorplan of the Shelter Industries house

compact central core — Borg-Warner Corp.'s Ingersoll Utility Unit (see AR, April, '46, p. 162).

Design of the house is based on eight years of study and research by the staff of Donald Deskey Associates. Ralph Gulley, director of Shelter Industries, was chief architect. Features are a 3-ft. overhanging eave on the terrace side of the house, equipped with pipe fittings for the addition of an awning; a large picture window in the living room, overlooking the terrace; cross ventilation in every room; five good-sized clothes closets, a linen closet, a kitchen-storageutility closet and 27 sq. ft. of kitchen shelf space. Over-all size of the house is 28 ft. 8 in. by 20 ft. 8 in.



The Blaski house features air-flow curves

Blaski Aluminum

The Streamlined Aluminum Home recently introduced by the Blaski Mfg. Co. was created especially for returning veterans. Mass Production is already under way.

Done in the natural finish of aluminum, and precision fabricated in airflow curves, the Blaski house is Quonsetshaped, 16 ft. 6 in. by 22 ft. 3 ¾ in. in size. The combination living-bedroom is 15 ft. 11 in. by 12 ft. 10 in.; the kitchen accommodates a full-sized electric refrigerator, a four-burner gas stove, a sink and electric washer, a combination work and dining table, and two chairs.


The 24 S.T. Alclad Aluminum, Blaski reports, will last a lifetime without any painting or other maintenance whatever. Its high reflectivity insulates out the heat of the summer sun, and helps to keep in the heat from the gas or electric heater in the winter.

Wingfoot Homes

Mass production of 48,900 two-bedroom homes annually, if necessary materials and equipment are readily forthcoming, has been promised by P. W. Litchfield, chairman of the board of the Goodyear Tire and Rubber Co. Using idle war plants, the completely assembled homes will be built at the rate of 157 per day by Wingfoot Homes, Inc., a



Wingfoot's two-bedroom prefab has telescopic wings to permit delivery by truck



Goodyear subsidiary. They would sell at the factory for under \$2,500, would be delivered complete with bathroom and kitchen fixtures, built-in beds, bureaus, closets, mirrors and cabinets.

First developed in 1942, the Wingfoot Homes have been produced on a limited scale during the past year in a pilot assembly plant at Litchfield Park, Ariz. The house is 26 ft. long and 8 ft. wide, which permits easy delivery by truck. At the site, telescoped wings are pushed out to convert the structure into a T-shaped unit 26 by 15 ft. in size. A front porch and a roof are attached as the house is moved onto its foundation ready for sewage, water, gas and electric connections.



B.I.S.F. model, designed for urban areas

British Prefabs

Large-scale production is under way in England of two new types of prefab: the B.I.S.F., of steel construction, designed by the British Iron and Steel Federation, and suitable for urban areas in groups of 50 or more; and the Airey, of precast concrete construction, suitable for rural areas.

OTHER BUILDING NOTES

New Offices

An entire facade of aluminum, with the exception of the window areas, will be the feature of a 20-story office build-(Continued on page 18)

A Simplified Framework of Uniform Quality . . .


STRAN

Cut to accurate lengths and supplied with all structural and joining members necessary for each building or development, Stran-Steel framing simplifies construction and provides greater permanence for homes.

Studs, joists and channel plates are easy to handle, and make possible speedy construction. A patented nailing groove in framing members permits nailing wall or other collateral materials directly to the steel framework. Stran-Steel accessories to connect framing members are supplied in correct quantities, and make construction easy and practical with ordinary hand tools.

For simplicity and reliability—for the strength and uniformity of steel, made practical for varied framing requirements—build with Stran-Steel. For further details, see Sweet's File, Architectural, Sweet's File for Builders, or the January issue of Building Supply News.

GREAT LAKES STEEL CORPORATION
Stran-Steel Division - Penobscot Building - Detroit 26, Michigan
UNIT OF NATIONAL STEEL CORPORATION





has tele-

y truck

uld sell

, would

n beds,

abinets.

Vingfoot

limited a pilot

rk, Ariz. ft. wide,

y truck. e pushed

into a size. A attached

foundagas and

an areas

f prefab: atruction, and Steel ban areas he Airey, ion, suit-


um, with areas, will face buildon page 18)

RECORD

JUNE 1946

17

When conditions are



USE WOLMANIZED LUMBER*

Why? Because this lumber, impregnated with Wolman Salts* preservative by pressure treatment, will give you more years of service in places where rot-producing moisture is present.

It is recommended for use in structures exposed to:

- 1 Moisture in artificially humidified buildings.
- 2 Steam and vapor from industrial processes.
- 3 Condensed water vapor in walls, floors and ceilings of refrigerated buildings.
- 4 Soil moisture and rainwater, held in joints, etc., of outdoor structures.
- 5 Moisture condensed by concrete or masonry.

When you buy treated lumber, remember to specify pressure-treated . . . it's the only dependable kind!



1679 McCORMICK BUILDING, CHICAGO 4, ILLINOIS

BUILDING NOTES

(Continued from page 16)




Proposed aluminum-faced office building

ing to be erected by the Aluminum Company of America at Park Avenue and 58th Street, New York.

Employing a new type of construction embodying an aluminum-faced curtain wall, the proposed structure has been designed as a "dramatic demonstration of all the proven architectural applications of aluminum." Harrison, Abramovitz and Wiggins are the architects.

Designed to have something of an irregular U-shape, the building will permit maximum utilization of office space exposed to daylight. There will be a large display area on the ground floor with an aluminum-faced escalator at the rear leading to a second-floor lounge and open terrace. Garage facilities for building occupants will be located in the basement.



Power house for Sherwin-Williams plant

Power Plant

Construction is under way on a new power house at the Chicago plant of the Sherwin-Williams Company, paint manufacturers. Approximately 125 ft. sq., equal to seven stories in height, the building will have a tile exterior, red colored floors of concrete on the first (Continued on page 138)

n page 16)



Carpet By The Mile

Our looms are weaving contract carpet at top speed . . . weaving it by the mile in stunning new colors and eye-catching designs. But even MILES of carpet isn't enough to fill the demand. So continue to be patient, please. It shouldn't be TOO LONG before you can again specify "Alexander Smith" and have your order filled without delay. Alexander Smith & Sons Carpet Company, 295 Fifth Avenue, New York 16, N. Y.

Weavers of "Crestwood"... America's No. 1 contract carpet



ALEXANDER SMITH CONTRACT CARPET

luminum

struction d curtain has been nstration applica-Abramotects. ng of an

ding will of office here will e ground escalator cond-floor age facilibe located



ams plant

on a new plant of ny, paint 125 ft. eight, the erior, red the first page 138)

RECORD



You're Way Ahead If You Have the RIGHT E for the Job!

Aerofin's Dependable Engineering is Your GUARANTEE

FLEXITUBE AEROFIN FOR STEAM HEATING

Each tube built to expand and contract independently, thus relieving headers, tubes and tube joints of strains due to temperature changes. Crowned orifice insures equal steam distribution to each tube and prevents freezing due to clogging of tubes by scale and other foreign matter.

NON-FREEZE AEROFIN COIL

embodies all of the features of Aerofin Flexitube, plus non-stratifying and non-freeze features for any entering air conditions.

UNIVERSAL AND HIGH PRESSURE AEROFIN

for steam heating where a heavy coil of rugged construction is required.

CONTINUOUS TUBE WATER COIL

for cooling or heating with water, brine or other non-volatile refrigerants.

REMOVABLE HEADER WATER COIL

for same duties as Continuous Tube Coil, with added feature of removable header for complete cleaning and draining of each tube.

DIRECT EXPANSION COOLING COIL

for cooling with volatile refrigerant. Patented distributing headers insure perfect distribution for all loads.

SPECIAL COILS FOR SPECIAL APPLICATIONS

For long, trouble-free, low-cost service select the right type, design, size and material. Aerofin units are insurance against costly changes and repairs:

Metallic bond of fin and tube is not injured by expansion or contraction. Rigid material specifications and inspections assure quality that maintains Aerofin's dependable ratings.

Special coatings or non-corroding metals can be furnished to prevent chemical damage.

For highest practical heat exchange, over 100,000,000 feet of Aerofin have been

CALL IN AN EXPERIENCED AEROFIN FIELD ENGINEER FOR THE WHOLE STORY ON HEAT EXCHANGE.

AEROFIN CORPORATION

CHICAGO · DETROIT · CLEVELAND · NEW YORK · PHILADELPHIA · DALLAS · TORONTO

410 South Geddes St., Syracuse 4, N. Y.

BRIXMENT MORTAR

Has Better Water-Retention



Here's the way to test for high water-retention. Slap a small dab of any two mortars onto a brick. Wait a minute, then feel each dab. The



one that stays plastic longest will be the one having the highest water-retention. Try this with Brixment mortar!

-AND HIGH WATER-RETENTION IS ESSENTIAL TO WELL-BONDED, WATERTIGHT MASONRY

Water-retaining capacity is the ability of a mortar to retain its moisture, and hence its plasticity, when spread out on porous brick.

High water-retaining capacity is of extreme importance in mortar. If the mortar does not have high water-retaining capacity, it is too quickly sucked dry by the brick; the mortar stiffens too soon, the brick cannot be properly bedded, and a good bond cannot be obtained.

Brixment mortar has extremely high water-retaining capacity. It strongly resists the sucking action of the brick. Brixment mortar therefore stays smooth and plastic longer, when spread out on the wall. This permits a more thorough bedding of the brick, and a more complete contact between the brick and the mortar. The result is a better bond, and hence a stronger and more water-tight wall.

LOUISVILLE CEMENT CO., Incorporated, LOUISVILLE 2, KENTUCKY
CEMENT MANUFACTURERS SINCE 1830

JUNE 1946

21

TEE

ving

and other

ying

atile

n is

e of

ders

e and s: action. ntains

revent been

N. Y.

RONTO

RECORD



of America's homeowners, Lumite* Window Screen is here to stay!

This amazing plastic screen that can't rust, corrode or stain... that can't dent or bulge . . . is enjoying a "boom" that will last our lifetime and yours.

So ... to meet this insistent, increasing demand for LUMITE, we have built a plant that is not only modern in every respect today . . . but is also planned to cope with the inevitable production-expansion which many years of tomorrows will bring.

All plant equipment is up-tothe-minute...our looms the most modern to be had. Our craftsmen know their jobs from A to Z... REG. U. S. PAT. OFF.

and our Research and Testing Laboratory staff experiments endlessly to produce new uses for better merchandise.

This is the only plant in America built for the sole purpose of manufacturing plastic screen and fabric. On 300 acres of rolling Georgia countryside, this new plant will fill the ever-growing demand for LUMITE, giving you speedy and efficient service.

Write today for full information and samples of LUMITE Plastic

WOVEN OF SARAN A DOW CHEMICAL CO. PRODUCT

WHY LUMITE IS A BEST-SELLER:

- RUSTPROOF
- WON'T BULGE
- · CAN'T STAIN
- NO PAINTING
- · CLEANS EASILY
- EASY TO HANDLE
- · EASY TO FRAME
- NON-INFLAMMABLE
- TESTED COLOR
- LASTS LONGER
- AND STRONGER-Lumite is woven of heavy plastic filament (0.015" diameter)



CHICOPEE MANUFACTURING CORPORATION 47 Worth Street, New York 13, N. Y. World's largest maker of Plastic Screen Cloth CHITECTS

ER:

mite is

filament

L RECORD

HARET TO THE TOTAL PROPERTY OF THE PARTY OF

Reliability

CHARTING a course or transferring ideas into workable plans calls for reliable instruments which one can trust. Among these is the drawing pencil—great in productive capacity when it measures up to precision standards.

VENUS Drawing Pencils are engineered to give you drafting perfection without failure: accurately graded to assure uniformity in all 17 degrees . . . strong in performance . . . smooth and clean in action.

Put VENUS to the test on your drawing board. Send us a postcard or a note for two free samples. Specify degrees wanted.


VENUS

DRAWING PENCILS

AMERICAN LEAD PENCIL COMPANY, HOBOKEN, NEW JERSEY

HERE'S YOUR CATALOG OF TRUSCON

Steel Building Products



Truscon is the world's largest manufacturer of steel building

products. From no other single source can you secure such a wide range of essential, heavy-duty structural units-each one a scientifically designed, well-made product that has been proved by many years of service in industrial structures.

At the present time these building products are not immediately available. However, our production plans are

finally being molded into shape, and we are bending every effort to Made height lastina railros

MEC

neeting

Rubber

reach maximum output with the least possible delay. In the meantime, design Truscon Steel Building Products into the industrial structures you now are planning.

Concentrate on Truscon as the major source of your steel building products-for dependability, for responsibility, and for designing, engineering and delivery service, no matter where you or your job may be.

OPEN TRUSS STEEL JOISTS



Truscon developed the open truss steel joists to meet the demand for economical, light weight, fire-resistant floors in schools, hospitals, apartments and other light-occupancy buildings. They are easy to install. Completely shop fabricated, they reach the job ready for placing.

CLEARSPAN JOISTS




Truscon "Clearspan" Joists meet all clear span requirements up to 64 feet. They eliminate undesirable columns and provide greater unobstructed floor areas.

FERROBORD STEEL DECK ROOFS



Truscon Ferrobord provides a fire-resistant, economical roof deck for all new construction or replacements. Covered with insulation and water-proofing, it weighs approximately 5 pounds per square foot.

DOUBLEMESH HERRINGBONE LATH



A plaster saving lath, designed for a perfect mechanical bond. Sheets are unusually rigid, allowing wider spacing of supports. A complete line of corner beads and other accessories will also be available.

HOLLOW PARTITION STUDS

Truscon hollow partition studs assure permanence, rigidity and economy. They are fire-resistant, provide excellent heat insulation, and sound resis-tance, are rodent and termite proof. They will not swell or warp and will resist impact, vibra-tion or plaster cracking.



CURB BARS



Protect exposed corners of concrete curbs, walls steps, etc. Designed to give positive anchorage into the concrete. Plate surrounds and protect the corner without splitting concrete into two portions.

CONCRETE BARS



A special rolled section of high grade steel, with a series of longitudinal and diagonal ribs, so designed to provide the maximum bond with the enclosing concrete.

PRESSED STEEL




Truscon Slotted Inserts are attached to the forms and are completely imbedded in the concrete. Bolt can be moved along slot to any location, allowing wide variation in position. Used in ceilings, slabs, beams or columns.

WELDED STEEL FABRIC

Truscon Welded Steel Fabric is made in various sizes for concrete reinforcing in all types of structures, and highways. Each joint is electrically welded for permanence.

FLOODLIGHT TOWERS

Made in a wide selection of heights, they offer a firm, longlasting floodlight tower for railroad sidings, airports, factory yards, etc.




PIPE LINE SUPPORTS

Weltrus Pole sections provide ideal pipe line supports. Correct as to engineering, neat in appearance, economical, permanent and efficient in operation.



PIVOTED WINDOWS

Adaptable to all types of industrial and commercial buildings. Easy to open and close. Come in a wide range of sizes.



nto shape, ry effort to le delay. In g Products planning. ce of your

r responsi-

d delivery

b may be.



COMMERCIAL PROJECTED WINDOWS

Used widely in buildings where appearance, shading and screening convenience and low cost are required.

Lever Arm or Rack and Pinion Types for operating long

runs of Pivoted or

Projected Windows



DOUBLE-HUNG WINDOWS

Electro-Galvanized steel, bonderized and finished with baked-on priming coat of paint, guaranteed spring balances, factory installed weatherstripping, and attractive hardware. Shipped completely assem-bled ready for installation.



CONTINUOUS WINDOWS

Continuous windows provide large glass areas for admitting daylight and controlled ventilation. Used with properly designed mechanical operators, it is possible to open and close all the windows in each bay or several adjacent bays through one control.



a fire-resistant, eco-new construction or insulation and water-nately 5 pounds per



ARS





concrete curbs, walls, positive anchorage ting concrete into



MECHANICAL OPERATORS

TWO SECTION TURNOVER DOOR

CRANE DOORS

Frequently the cost of this type door can be saved in a single season due to increased efficiency of workmen and fuel savings. Door leaf can be completely filled with sash to permit maximum transmission of daylight. Doors open and close quickly. Usual electric operating speed is 45 feet per minute.

Designed for rapid operation, they are effective barriers to infiltration of cold air and resultant heat loss in industrial buildings of all types. An important advantage of this type door is the reduced clearance required inside the building for opening and closing these doors.



Truscon swing and slide doors are adaptable for use in basements, rear entrances, boiler rooms, fire exits and similar places in residences, hotels, apartments, schools, churches, shops, warehouses, factories, filling stations and stores. They are durably made for heavy usage,

SWING AND SLIDE DOORS



Truscon Welded Bank Vault Reinforcing consists of welded steel units placed



parallel to each
other with their chord members forming a barrier of steel near the inner and outer faces of the walls, floor and ceiling slabs. The web members of the welded units provide reinforcement through the thickness of the concrete.

TRUSCON STEEL COMPANY

YOUNGSTOWN 1, OHIO . Subsidiary of Republic Steel Corporation

Manufacturers of a Complete Line of Steel Windows and Mechanical Operators . . . Steel Joists . . . Metal Lath . . . Steeldeck Roofs . . . Reinforcing Steel . . . Industrial and Hangar Steel Doors . . . Bank Vault Reinforcing . . . Floodlight Towers...Bridge Floors.

L FABRIC

ic is made in various g in all types of struc-h joint is electrically

HOUSES TO BUILD

New Homes for Today. By Paul R. Williams, A.I.A. Hollywood, Calif., Murray & Gee, Inc., 1946. 8½ by 11 in. illus. \$2.00.

This new book by Paul Williams has all the popular appeal of his earlier "The Small Home of Tomorrow." Predominantly a book of plans, it has an introductory chapter discussing the problems that every family faces as it sets out to build its own house. Here, in concise form, are a consideration of the pros and cons of the one-story home as against the two-story, the current trends in planning, the technical matters such as heating and air conditioning, the possibilities of remodeling, the principles of furnishing and decorating, the problem of site selection - all topped off with a practical list of Do's and Don'ts in building.

The plans Mr. Williams has assembled here are varied enough to suit every taste. Some are as distinctly modern as others are distinctly traditional, but most are small, and all show a shrewd sense of good space usage. It is a nicely balanced, attractive collection of which any architect could well be proud.

AND MORE HOUSES

If You Want to Build a House. By Elizabeth B. Mock. Illustrated by Robert C. Osborn. New York (1230 Sixth Ave.), Simon and Schuster, Inc., 1946, for the Museum of Modern Art. 7½ by 10 in. 96 pp. illus. \$2.00.

Very different in character is this second book on the art of home building. It is an out and out appeal for the socalled modern style. "Only in modern architecture," Mrs. Mock writes, "is any serious attention given to the peculiar problems of the small house." She isn't advocating, however, that boxlike, hospital-clean, impersonal functionalism which all too often passes for modern. Take what she says of the kitchen, for example: "A kitchen is more than the sum of its gadgets. . . . Hard, smoothsurfaced materials are, of course, easy to clean, but that doesn't mean that the entire kitchen must look like the inside of an ice-box. Can't we achieve, in contemporary terms, something of the rich and warmly human dignity which still seems to characterize peasant kitchens all over the world?"

Mrs. Mock has chosen well from among the best examples of modern small-house architecture. Frank Lloyd Wright, Harwell Hamilton Harris, Richard J. Neutra, Marcel Breuer, Wurster and Bernardi, Pietro Belluschi — these are some of the architects represented. Examples of their work are used to illustrate Mrs. Mock's various chapters on space for living, plenty of light, mak-

ing small houses seem large, and so on. Even though this quite obviously is intended as a book of ideas rather than as a workbook, it is curious that not a single floor plan has been included.

VIVIFYING COMMUNITIES

Rebuilding Our Communities. By Walter Gropius. A lecture given at the Institute of Design, Chicago. Chicago. 2 (5 N. Wabash Ave.), Paul Theobald, 1945. 8½ by 11 in. 62 pp. illus.

In common with the majority of city planners, Walter Gropius stresses as a necessary first step in city rehabilitation the reawakening of community interest and spirit. Every citizen must be permitted to participate actively in the community life, he says. "To attain this, our administrative framework must be humanized. It should be based on self-contained neighborhood units, small enough to serve as organisms for reactivating normal social intercourse."

"Such a self-contained neighborhood unit," he explains, "would have from five to six thousand inhabitants, the minimum number needed for an efficient elementary school. The next larger administrative unit would be a precinct in the city, or a county in the country, each comprising a cluster of from six to 10 neighborhood units — say 30 to 50 thousand people. Finally, the largest unit is the entire city or metropolis itself."

Daily commuting time should not exceed 30 or 40 minutes, Mr. Gropius says, and the size of neighborhood units should be limited by walking distances. Legal instruments should be developed that could channel any housing development, private as well as public, into a controlled and balanced communal organization. Land ownership and use should be regulated by legislation.

Two less familiar ideas are advanced by Mr. Gropius. First, that cities could be relieved from congestion by the siphoning out of "those people who cannot be permanently employed in the city," and the resettling of them, together with some smaller industries, in neighborhood units to be built in the country. And second — a new proposal well worth serious consideration — the building by each state of at least one model neighborhood community as a memorial to the dead of World War II.

A TOWN SURVEYED

A Comprehensive Municipal Plan for Lancaster, Pennsylvania. Prepared by Michael Baker, Jr. Rochester, Pa., The Baker Engineers, 1945. 8½ by 11 in. illus.

When Michael Baker sets out to do a planning survey, he does a thorough job of it. As in his study of Beaver County,

Pa., published almost two years ago (see AR, Oct., 1944, p. 26), this survey of Lancaster covers every possible facet of development and need. The city's history is sketched from the beginning to the present day, with full attention paid to the background of the early settlers. Present-day standards of living, land use, occupations, industries, commerce and agriculture are analyzed in detail. Population characteristics and trends are studied. The physical development of the community is examined almost with a microscope. And with all of this careful analysis as a background, specific recommendations are made and a program for future action is presented.

DRAWING TEXTBOOK

Simplified Architectural Drawing. By Truman C. Buss, Jr. Chicago 37 (Drexel Ave. at 58th St.), American Technical Society, 1946. 8¼ by 11 in. 258 pp. illus. \$4.75.

Here is a basic textbook, complete with examples and graded problems, for the use of architectural students. Its author, a registered architect, is the head of the department of architectural drawing at the Pullman Free School of Manual Training in Chicago — a happy background for a book of this kind.

Divided into sections on technique, working drawings and construction, and display drawing, the book is easy to work with. It does not skimp anywhere along the line either on explanation or on illustration. Nor does it presuppose any previous training in the field. With its generous number of problems, its reading list and its index, it is the sort of textbook that both instructors and students should welcome.

PLASTICS BIBLE

Modern Plastics Encyclopedia: 1946, New York 17 (122 E. 42nd St.), Plastics Catalogue Corp., 1946. 8¼ by 11¼ in. 1390 pp. illus. \$6.00 (\$7.00 outside the United States).

Year after year the Plastics Catalog gets bigger and better, more attractive, and easier to work with. And year after year it faithfully reports the latest developments in the plastics field. It is really appalling the way the thing grows: the 1945 edition was almost 200 pages longer than the 1944, and the 1946 edition adds still another 212 pages!

The most noticeable and welcome change from previous editions is the peacetime aspect of the new volume. For several years the catalog has fairly bristled with things military; it is both pleasant and somehow reassuring to find in this volume pleasure boats instead of PTs, dresser sets instead of mess kits, civilian rather than military models and needs. No longer is the introductory section of the volume concerned with wartime developments and applications; instead there is a "Plastics

(Continued on page 28)

ars ago survey le facet ty's hisning to ion paid settlers. g, land mmerce ı detail. trends lopment almost l of this specific l a pro-

By Truel Ave. at ety, 1946. complete lems, for ents. Its , is the itectural ichool of

ted.

a happy cind. chnique, cion, and easy to nywhere ion or on pose any With its its reade sort of

and stu-


946. New tics Cata-1390 pp. ed States). Catalog ttractive, rear after atest deeld. It is ng grows: 200 pages the 1946 pages!

as is the dume. For as fairly it is both suring to boats ininstead of a military err is the lume connents and "Plastics"

n page 28

RECORD

welcome



Copper was chosen of course for durability, and Anaconda Through-Wall Flashing because: (1) Die-stamped dam and corrugations provide positive drainage; (2) Flat selvage permits sharp bends for counter-flashing, or for locking to adjacent metal; (3) Dam designed so as to permit placing edge within ½ inch of face of wall, and still allow for pointing of mortar; (4) Thoroughly water-tight joints are formed when flashing is locked endwise by nesting

For detailed description and suggested specifications, write for Publication C-28, or refer to Sweet's Architectural Catalog.

one or two corrugations.



THE AMERICAN BRASS COMPANY

General Offices: Waterbury 88, Connecticut
Subsidiary of Anaconda Copper Mining Company
In Canada: Anaconda American Brass Ltd.,
New Toronto, Ont.





Health Center Building, Royal Oak, Michigan

No damp and grimy areas deface the exterior of this structure. It has been treated to a protective coat of portland-cement paint—made with Atlas White Cement.

When applied to concrete, concrete masonry, brick, stone or hollow tile, this sturdy finish penetrates the pores to form a permanent bond. It resists moisture . . . combats dirt and dust. Saves money, too . . . because frequent repaintings are unnecessary.

Atlas White Cement is used by manufacturers of portlandcement paint as a base for natural white and for a wide variety of colors—to bring out clearly, permanently, the full color values of the pigments used. Conveniently packaged, portlandcement paint is ready for mixing with ordinary tap water on the job.

For full details, write to Atlas White Bureau, Universal Atlas Cement Company (United States Steel Corporation Subsidiary), Chrysler Building, New York 17, N. Y.

FACTORY-PREPARED PAINT IS PREFERABLE SEE YOUR LOCAL PAINT DEALER



U. S. STEEL RADIO SHOW — Sunday Evenings — Consult your local newspaper for time and station.

REQUIRED READING

(Continued from page 28)

Panorama" telling what plastics are, what methods and machines are used in forming them, what they are used for.

How the plastics industry is growing is indicated in a chapter on facts and figures. The technical data section includes a detailed bibliography, a series of charts and tables, and complete specifications. The exhaustive materials section has been thoroughly brought up to date. The excellent group of charts which has formed an important part of previous volumes has been augmented with two additions - the SPI classification of plastic molding materials, and an adhesives chart - and has been issued separately in an envelope (extra copies may be had at \$3.75 the set of 10) rather than bound in the volume as has been done heretofore; whether or not this separation will prove an advantage is a moot question. The appendix includes a bibliography, a glossary, the index, and a directory of manufacturers.

FOR BETTER CODES

Your Building Code, By Miles L. Colean. New York 18 (512 Fifth Ave.), National Committee on Housing, Inc., 1946. 6 by 9 in. 30 pp. 35 cents.

Emphasized again and again in the drawing up of postwar building programs has been the necessity of building code revision. Thousands of words have been written on what the problem is and what should be done about it. And now comes this pamphlet written by Miles Colean for the National Committee on Housing, summing it all up in a few short pages.

Mr. Colean finds six main building code problems: (1) what the code should cover; (2) scientific standards; (3) non-uniformity; (4) multiple jurisdiction; (5) legal rigidity; (6) adequate inspection and fair enforcement. He analyzes each of these, and sketches out a possible solution.

MORE ABOUT CODES

Building Code Modernization (A Series of Reference Bulletins). New York 1 (350 Fifth Ave.), American Iron and Steel Institute, 1946. 6 by 9 in. 70 pp.

A handy companion to Miles Colean's analysis of the building code problem is this series of eight papers on both general and specific code considerations. The bulletins include facts related to the purpose and legal limitations of building codes, contents and arrangement, building classification, fire hazards, fire protection and exit regulations, structural standards, etc. They are based on a study of building practices through out the United States, started in 1938 and carried out by the Institute's Committee on Building Codes.

page 28)

tics are, e used in ed for. rowing is cts and ction ina series lete sperials secht up to f charts t part of gmented classifiials, and been is-

be (extra

olume as ier or not dvantage endix in-

sary, the facturers.

L. Colean.

National

6. 6 by 9

in in the ling prof building ords have em is and And now by Miles mittee on few short

building
de should
(3) nonisdiction;
te inspecanalyzes
a possible

Series of (350 Fifth Institute,

Colean's

ES

problem on both derations related to ations of arrangefire hazgulations, are based s throughd in 1938 tte's Com-


RECORD

Almost any roof looks good when it is new. The real test comes after it has been exposed to tough conditions . . . to water lying in low spots . . . to breaks caused by vibration . . . to years, years,

That is why roofs are like beauty that is skin deep.

If a roof fails for any reason, the client is apt to think you are to blame. That is why it is safest to specify the kind of roofing materials that long years of experience have proved will last...roofing whose "beauty" goes clear through to the deck. Your safest bet is coal tar pitch roofing. With all the improvements that have been made in other things, no one has been able to find any better built-up roofing than this old true-and-tried material. For your own sake, as well as for the sake of your client, specify coal tar pitch.—Koppers Company, Inc., Tar & Chemical Division, Koppers Building, Pittsburgh 19, Pa.

Why are roofs



a KOPPERS Product


DESIGN POSSIBILITIES FOR RESIDENCES

. . with



The modern home combines beauty, utility, and efficiency. That's why wainscots or walls of Carrara Structural Glass are so frequently specified in architect's kitchen and bathroom designs. Carrara is permanent, easy to clean, unsurpassed in beauty. It is available in ten attractive colors and in a wide range of thicknesses. Architect: Stiles Clements.

The trend toward more and larger window areas calls for the use of quality glass for glazing. Pennvernon Window Glass is widely used for general glazing because it has an unusually high degree of clarity, good looks, and freedom from distortion. For glazing larger areas, lustrous Pittsburgh Plate Glass is recommended.



Striking effects can be obtained by using Pittsburgh Mirrors. Small rooms can be made to seem larger, narrow rooms wider, dark rooms lighter. Available for your designs are mirrors of blue, flesh tinted, green, or regular Plate Glass and gold, silver, or gunmetal backings. Interior by Mabel Cooper Bigelow and E. Chas. Werner. Architect—Rollin Pierson.





urgh Mirnarrow for your green, or gunmetal

RECORD

More and more, the outdoors is being brought into the home by the use of large picture windows and panels of glass. Such generously-proportioned glass areas, without cross-sash of any kind to interfere with vision, enable the architect to take full advantage of attractive surroundings in designing gracious

homes. Pittsburgh Polished Plate Glass is the practical choice for applications like this. It is brilliantly reflective of surface, enhancing substantially the exterior appearance of the home. And it affords clear, undistorted vision through it from any angle. Architect-A. S. Alschuler.

We believe you will find much to interest you in our illustrated booklet of ideas for the use of Pittsburgh Glass in architectural design. Send the coupon for your free copy.

* Design it better with

Pittsburgh Plate Glass Company 2191-6 Grant Building, Pittsburgh 19, Pa. Please send me, without obligation, your book-let entitled: "Ideas for the Use of Pittsburgh Glass in Building Design."

PLATE GLASS COMPANY

Here's a POWERFUL'story FOR City Planners



· Any architect, engineer, contractor, utility dire commissioner interested in efficient power distribution we find this case history extremely helpful. It shows how, by adding steam sales, the Piqua Municipal Power system was able to plan a long range expansion program on a sound basis able to plan a long range expansion program on a sound basis—at the same time bringing to the community all the benefits of "Central Heating"—smoke and soot abatement, reduction of fire hazards, fuel and manpower savings resulting from elimination of individual heating plants and of private coal delivery and ash removal. It also shows the important part Ric-wiL played by providing a modern steam distribution system.

Write for your copy today.

RIC-WIL INSULATED PIPE CONDUIT SYSTEMS THE RIC-WIL COMPANY . CLEVELAND, OHIO



STARTING with buried service entrance cable, jacketed and insulated with GEON, all the wire used in this modern house is insulated with this modern material.

That's because wire insulated with GEON offers so many advantages-excellent electrical properties, to name one of the most important. Insulation made from GEON is flame resistant; increases safety, reduces fire hazard. Because of its outstanding electrical properties

insulation made from GEON may be used in thin coatings which means more conductors per conduit. It's smooth, too, easy to handle and install; quickly identified because the entire NEMA color range is available. And, of course, it's Underwriters' approved.

As soon as the house is completed, more wire insulated with GEON will make its appearance. It may be in the form of appliance, lamp, and telephone wire. Or it may be the hookup wire now being used in modern radio sets and other electrical devices.

All of GEON's advantages are available to users in domestic, industrial or utilities wiring. The next time

> you order wire or cable from your supplier be sure to specify insulation made from GEON. Or for help with specific applications please write Dept. A-6, B. F. Goodrich Chemical Company, Rose Building, Cleveland 15, Ohio.



B. F. Goodrich Chemical Company THE B. F. GOODRICH COMPANY

RECORD



ONCE YOU HAVE THESE JOHNS-MANVILLE WALLS—CEILINGS—FLOORS, YOU CAN KEEP CHANGING THE WHOLE BUILDING INTERIOR AS REQUIRED

MOVABLE WALLS—The keystone of flexibility in Unit Construction is the J-M Transite Wall. Can be disassembled and relocated as needs require. One-unit rooms, for instance, can be speedily converted into two-unit rooms, or vice versa. Made of fireproof asbestos and cement, practically indestructible materials, the movable panels form rigid, double-faced partitions, 4" thick. Can also be used as interior finish of the outside walls. Removable Transite panels permit ready access to wiring, etc.



ACOUSTICAL CEILINGS—Important factor in helping to overcome the handicap of distracting noise, Johns-Manville Acoustical Ceilings are beneficial both to teacher and student alike. They give the desired degree of quiet for effective teaching, and are proved aids to concentration. An exclusive Johns-Manville patented construction system permits interchangeability of flush-type fluorescent lighting and acoustical units, which are readily demountable.



-exp

Johns



COLORFUL, RESILIENT FLOORS—J-M Asphalt Tile Flooring completes the Unit Construction System. Made of asbestos and asphalt, the units withstand hard wear, yet are comfortable and quiet underfoot. Individual units permit easy alterations or extension of patterns. Made in a wide variety of plain and marbleized colors.

A lecture room now, it may be a laboratory tomorrow—expanded or rearranged to meet a new need! That's the structural flexibility made possible by the Johns-Manville Unit Construction System.



"Structurally " flexible"

Yes! This attractive university lecture room can be enlarged, subdivided, or even relocated!

Johns-Manville Unit Construction provides the complete interior for schools and colleges... offers many new advantages

HERE IS CONSTRUCTION that sets new standards of architectural beauty and at the same time meets the long-existing need of schools and colleges for *complete structural flexibility*.

Whenever educational needs present new requirements, you can expand, convert, or subdivide interiors built with Johns-Manville Walls, Ceilings, and Floors.

You can vary the size or arrangement of rooms and corridors... make endless revisions of space-use... and do it economically, quickly, without waste of material!

Also, this proved method of construction makes the whole interior—walls, ceilings, floors—available under *one* specification, *one* manufacturer's responsibility. Each material contributes individual advantages:

- 1. Movable Walls...readily assembled...are interchangeable... 100% salvageable. Made of sound-resistant, asbestos-cement Transite panels...hard to mar, easily cleaned by a simple washing—advantages that make a big difference in the maintenance budget.
- Acoustical Ceilings . . . attractive . . . demountable . . . reduce distracting noise. Units can be taken down and relocated as desired.
- Colorful, Resilient Floors . . . quiet underfoot. Small units permit easy extension of floor pattern.

All these constituent parts are durably built to last as an *integral* part of the building. Write for further information and details on this significant development in the construction of educational buildings. Address Johns-Manville, Department AR-6, P. O. Box 290, New York 16, N. Y.

Johns-Manville Unit Construction

ASPHALT TILE FLOORS . MOVABLE TRANSITE WALLS . ACOUSTICAL CEILINGS

HOSPITAL ARCHITECTS:


"BUILT-IN" FACILITIES

FOR MODERN HOSPITALS




Properly coordinating installations of recessed and built-in hospital equipment not only calls for the experience of specialists, but also requires the benefits of knowledge that can be acquired only through extensive contacts with hospital management personnel.

More than 40 years of such contacts and of experience in designing and manufacturing major equipment such as sterilizers, surgical lights, and instrument and supply cabinets, have qualified the Technical Sales Service Department of the Scanlan-Morris Division to supply valuable data and assistance to architects in planning hospital construction. Call on us, without obligation, for information and assistance on the types of products illustrated below.



Scanlan-Morris Built-In Sterilizers include models to meet every requirement of the modern hospital — individual sterilizers and batteries, for any type of heat. Also exposed types. Complete catalog includes both pressure and non-pressure sterilizers, cylindrical and rectangular autoclaves, and extensive planning and installation drawings and data.



Scanlan-Morris Recessed Instrument and Supply Cabinets are made of 20-gauge furniture steel, in a wide variety of styles and sizes; built from plans and specifications covering the individual requirements of the hospital.

Hospital architects are invited to send for literature and planning data on Surgical Lighting, Sterilizers and Recessed Cabinets, and for suggested layouts of equipment based on floor plans.

THE OHIO CHEMICAL & MFG. CO.
General Offices:
60 East 42nd Street, New York, N. Y.

Heidbrink Division, Minneapolis. Medical Gas Division, Cleveland. Hospital Supply and Watters Laboratories Division, New York. Scanlan-Morris Division, Madison, Wis. Represented in Canada by Oxygen Company of Canada Limited, and internationally by Airco Export Corporation.

Ohio Chemical

Manufacturers of Medical Apparatus, Gases, and Supplies for the Profession, Hospitals and Research Laboratories

BRANCH OFFICES IN PRINCIPAL CITIES



The NEW and REVOLUTIONARY
PLASTEEL AIR CONTROL

Canoes revolution ary

Canoes revolution are

Canoes revolution ar

A really improved <u>RIDGE-TYPE</u> <u>VENTILATOR</u> for Industrial Buildings

Out of the experience of years—and the technical and practical knowledge acquired in solving thousands of industrial building atmosperic problems comes the new PLASTEEL AIR CONTROL.

Not just another ventilator . . . but a positive "control." It gets heat, smoke and fumes out of buildings rapidly and efficiently when you want it to . . . controls the volume of exhaust to suit temperature and climatic conditions.

It eliminates structural disadvantages of past designs.

It provides heretofore unobtainable advan-

tages of freer air flow . . . maximum efficiency . . . and greater economy in the finished installation.

When furnished in Plasteel . . . that permanent material . . . it resists corrosive conditions, weather and other destructive elements . . . never needs painting or maintenance during the life of your building.

Obtainable in throat sizes 6 inches to 6 feet in any length to meet any building structural condition and exhaust requirement.

Specifying "Plasteel Air Control" will assure you of permanent lifetime satisfaction.

Write, wire or phone for complete data



PROTECTED STEEL PRODUCTS

Standard Life Bldg., Pittsburgh, Pa. - Plant: Washington, Pa.

JUNE 1946

37

data.

and dels.

ypes. and

and inets, have s Service an-Morris data and planning us, withtion and products

G. CO.

cal Gas ad Waticanianesented Canada Export

, and Supplies h Laboratories

RECORD



In every school, hospital, theatre, or other building where people gather, there are danger zones... corridors, stairways, fire towers and exits. Passageways to safety, when plunged into sudden darkness may become areas of extreme danger.

Normal supply of electric current may fail anywhere and at any time, for despite all precautions of utility companies, storms, floods, fires, collisions and other accidents beyond their control may strike without warning and become a serious menace to electric power lines. You can safeguard the buildings you plan against light failure. An Exide Emergency Lighting Unit supplies safe, sure, modern protection. Batteries are always fully charged and are ready to respond *instantly* and *automatically* when needed. Write for full particulars.



THE ELECTRIC STORAGE BATTERY COMPANY, Philadelphia 32 • Exide Batteries of Canada, Limited, Toronto



Proven performance through the years won for Red Lead its wide acceptance by industry as the standard paint for protecting metal.

But it remained for modern research to show the reasons why Red Lead is such an effective guardian against rust. One of the most important of these is Red Lead's ability to keep iron and steel in a "passive" state, in which rusting activity is reduced to a mini-

As is well known, bare, unprotected steel exposed to moisture rapidly rusts.

However, the same steel protected by Red Lead remains in a "passivated" or rustinhibited condition.

This non-corroding state of Red-Leaded steel, as compared with unprotected steel, can be measured electrically. See accompanying graph.

It is worth noting that, even after five years' exposure, the "passivating" power of Red Lead is still retained. No wonder, then, that Red Lead is considered the foremost paint for making metal last.

Specify RED LEAD for All Metal Protective Paints

The value of Red Lead as a rust preventive is most fully realized in a paint where it is the only pigment used. However, its rustresistant properties are so pronounced that it also improves any multiple pigment paint. No matter what price you pay, you'll get a better metal paint if it contains Red Lead.

Write for New Booklet-"Red Lead in Corrosion Resistant Paints" is an up-to-date, authoritative guide for those responsible for specifying and fermulating paint for structural iron and steel.



Scientific Proof of Red Load's Protective Effect

Scientific Proof of Real Load's Protective Effect
In this test, a piece of unpainted steel was immersed in water. Iron, going into solution, reacted with oxygen in the water to form rust. This unrestrained corroding state is indicated by a rapidly developed and maintained negative potential relative to hydrogen (see above graph). However, when steel panels painted with Red Lead were immersed under the same conditions, iron and lead salts formed directly next to the metal. This action at once stifled corrosion by preventing the iron from going into solution, thus keeping the steel surface passive. The result is shown in the graph curves above, where a quickly rising positive potential remains constant throughout the test. out the test.

It describes in detail the scientific reasons why Red Lead gives superior protection. It also includes typical specification formulas . . . ranging from Red Lead-Linseed Oil paints to Red Lead-Mixed Pigment-Varnish types. If you haven't received your copy, address nearest branch listed below.

The benefit of our extensive experience with Red Lead paints for both underwater and atmospheric use is available through our technical staff.

NATIONAL LEAD COMPANY: New York 6; Buffalo 3; Chicago 80; Cincinnati 3; Cleveland 13; St. Louis 1; San Francisco 10; Boston 6, (National Lead Co. of Mass.); Philadelphia 7, (John T. Lewis & Bros. Co.); Pittsburgh 30, (National Lead Co. of Pa.); Charleston 25, W. Va. (Evans Lead Division).





ou

ide

ife,

are

to

nen

When you plan a playroom ...

When the guests have gathered and the games are on, nobody likes to hike upstairs to answer the telephone or make a call. Naturally, the alert architect realizes this and plans for a telephone outlet in the playroom as well as in other convenient locations.

Built-in conduit to carry telephone wires within the walls, with telephone

outlets at all handy locations, are a mark of good planning and sensible construction. Prospects will expect these features — in small homes as well as large ones. The cost is small for the extra convenience and room beauty.


Your Bell Telephone Company will be glad to help you plan for them. Just call your Telephone Business Office.



Room planned by George Daub, Philadelphia, Architect

BELL TELEPHONE SYSTEM





"Portrait" of a Star Shoe Salesman

"He's" a diligent worker, this super salesman . . . "he" brings in more customers . . . gives them comfortable satisfaction every minute they're in the store . . . encourages them to stay longer and buy more . . . leaves them with pleasant memories and a desire to return. Architects know him well—in fact, "he" frequently gets his star selling jobs through architects' recommendations. They know "him" as the Chrysler Airtemp "Packaged" Air Conditioner.

This simplified form of air conditioning, pioneered by Chrysler Airtemp, is ideal for stores of all types. "Packaged" Air Conditioners, with the famous sealed compressor, are engineered for long, dependable life. They are compact and

easily moved, an advantage when remodeling or changing locations. Operating and upkeep costs are exceptionally low.

"Packaged" Air Conditioners gently circulate cool, filtered and dehumidified air quietly and efficiently. Add a heating coil, and you have year 'round air conditioning.

Also of first importance to architects is the small amount of floor space occupied by "Packaged" Air Conditioners and the fact that, singly or in multiple, they are easy to install. For full particulars, write Airtemp Division of Chrysler Corporation, Dayton 1, Ohio; or, in Canada, Therm-O-Rite Products, Ltd., Toronto, Ontario.

CHRYSLER CAIRTEMP

HEATING • COOLING • REFRIGERATION

ons, are a d sensible rill expect mes as well hall for the beauty.

Inpany will them. Just office.



New building? Or addition or alteration to an old one? Bethlehem can supply the structural steel. Whether it's big stuff or small. No mill rolls a greater variety of sections—ranging from 36-inch wide-flange shapes down to the smallest used in steel construction. And none offers today's builders more dependable service. Bethlehem structural steels are backed by nearly half a century of experience in this field, and again stand ready to play their part in American construction in the busy days ahead.





FORMICA MEANS SUBSTANTIAL SAVINGS PER SQUARE FOOT



AFTER having used Formica decorative plastic sheets on furniture, bulkheads, doors, and other surfaces in ships and having observed the results for several years the office of George Sharp, well-known naval architect, declares that each square foot of surface covered with Formica in a ship will save many dollars in the course of twenty years.

This saving is made up of many factors. The surfaces never need to be re-painted or refinished. That saves labor, and also makes it unnecessary for the space to be withdrawn from use while the work is done. Formica is much easier to keep clean than many surfaces and there are important savings in cleaning time.

While other users of Formica may not have analyzed the situation as closely as the ship builders there is reason to believe that similar savings are possible wherever Formica is used—in hotels, bars, soda fountains, railway, bus, and train terminals, hospitals, public buildings, office buildings and stores.

And of course, in addition to economy, Formica offers eceptional beauty of color and surface, characteristic inlays, Realwood surfaces—it is a thoroughly modern and strikingly attractive surfacing material.






THE FORMICA INSULATION COMPANY

4651 Spring Grove Avenue

Cincinnati 32, Ohio

BURDINE'S built with

MIAMI, FLORIDA



• FLOORS because...

Q-Floors gave E. L. Robertson, Miami and John R. Weber, New York, architects, freedom from all floor plan beadaches.

You have no worry about change of floor plans, even in a building where frequent change is essential to the business, if you are working with Q-Floors.

Burdine's department store, for example, rolled back the rug display one night, tapped the Q-Floors for electrical outlets and set up the demonstration of sewing machines, pictured on the right, with each machine having an outlet.

An outlet takes literally only a few minutes to install on Q-Floors. A Q-Floor is steel cells crossed over by raceways in such a manner that any six inch area can be tapped for power. An electrician merely drills through a thin concrete fill. No trenches with their mess and muss. Think what this means in terms of flexible floor layout.

Over-all electrical availability protects any building you design from electrical obsolescence no matter what the future hatches out of electronics. From a purely professional point of view, you can save yourself a whale of a lot of grief by specifying Q-Floors. Your client can locate partitions and electrical fixtures after he moves in.







And for Rodney Miller, Miami contractor, Q-Floors formed a dry, clean, noncombustible platform for all trades

Faster construction with Q-Floors is easily translated into money saved by your client. Q-Floors reach the job cut to fit. Two men can lay 32 sq. ft. in 30 seconds. The floors go in as fast as frame goes up. No forms or shoring; no wet materials cause delay. This speeds all other trades along so that construction time is reduced

20 to 30%. Robertson has proved this on thousands of installations. Q-Floors construction advantages and the over-the-years electrical advantage would justify premium costs. But—costs are right in line. You don't have to hedge one bit for cost. For com-

plete information call a Robertson representative or write to

H. H. ROBERTSON COMPANY 24

2404 Farmers Bank Building Pittsburgh 22, Pennsylvania



Offices in 50 Principal Cities World-Wide Building Service



RECORD



THAT'S RIGHT—other than ordinary washing and cleaning, there's no maintenance required with an Adlake Aluminum Window!

Because Adlake is built to last and last! An exclusive combination of nonmetallic weather stripping and serrated guides gives finger-tip control, eliminates excessive air infiltration, allows no warping or sticking, cuts maintenance problems to the bone! What's more, Adlake is beautifully designed for lasting architectural appeal.

Before specifying or detailing any window, why not get full information about Adlake Windows? We believe you'll find it well worth while.

THE ADAMS & WESTLAKE COMPANY

Furnishers of Windows to the Transportation Industry for Over 30 Years

ESTABLISHED 1857

ELKHART, INDIANA

NEW YORK . CHICAGO



SHUTLBRAK SWITCHBOARDS



® DESIGNED for FLEXIBILITY...® one-piece switchboard units can be conveniently arranged—singly or grouped. Removable end walls permit adding sections to either side.

® SECTIONALIZED for EASE and ECONOMY of INSTALLATION... ® assembled and shipped ready for connection of main and branch circuit cables...reducing installation costs. Sections readily fit together... with built-in junction boxes at top plus removable covers.

TAILORED TO MEET YOUR EXACTING REQUIREMENTS... Number and capacity of M Shutlbrak Switches provided as specified by you.



Switchboards like everything else must keep pace. They should be planned with an eye to the future.


Shutlbrak Switchboards make it easy not only to provide adequately for present day needs, but for future expansion as well.

Each unit of these modern, safety-type, heavy duty switchboards is self-contained, with all switch units connected to the bus bars of that section. Each has a junction box built into the top of the panel so that any number of units can easily and quickly be joined side by side or otherwise arranged to fit available space.

The Shutlbrak Switch, the outstanding characteristic of this switchboard, embodies the latest design and construction for a high quality heavy duty industrial switch with quick make and break connections held under compression by a tempered steel spring in the shuttle enclosure and with Kamklamp fuseholders. All copper surfaces are silver plated for good and lasting service. All steel parts are either made of galvanized steel, or cadmium plated. Switches are of interlocking type.

If it is high quality heavy duty switching that you need, insist on Shutlbrak Switchboards—the switchboard for today and tomorrow!





Designed and Engineered


FOR EVERY KIND OF JOB!

IN the American-Standard line of quality heating and plumbing products, you'll find equipment and fixtures styled, designed and engineered to fit the widest variety of applications.


American-Standard makes radiator heating, warm air and winter air conditioning equipment for coal (hand fired or stoker), gas, or oil. And American-Standard plumbing fixtures give you an equally wide choice for residential, commercial and institutional buildings.

Backed by many millions of dollars in research, these widely advertised American-Standard products have been Serving the Nations' Health and Comfort for more than half a century. Their smart appearance, efficient performance and proved operating economy assure lasting customer satisfaction. No products enjoy greater public acceptance. Yet, they cost no more than others and are available for modernization jobs on our FHA Time Payment Plan.

For information, contact your Heating and Plumbing Contractor. American Radiator & Standard Sanitary Corporation, P. O. Box 1226, Pittsburgh 30, Pennsylvania.



HEATING AND PLUMBING PRODUCTS for every use . . . including Boilers, Warm Air Furnaces, Winter Air Conditioners, Water Heate. " r all fuels . . . Radiators, Convectors, Enclosures . . . Gas and Oil Burners . . . Heating Accessories . . . Bathtubs, Water Closets, Lavatories, Kitchen Sinks, Laundry Trays, Brass Trim . . . and specialized products for Hospitals, Hotels, Schools, Ships and Railroads.




Ruberoid Makes Every Type

• No matter what type of roofing the job calls for—Ruberoid makes it—with complete specifications to meet any condition. Whether smooth surfaced Asbestos; or Coal Tar Pitch and Felt with gravel or slag surfacing; or Asphalt, smooth or gravel and slag surfaced—they're all available from Ruberoid!


That's why specifying Ruberoid

simplifies any roofing problem. Since Ruberoid approved roofers are not prejudiced in favor of any one type of material, they give you unbiased help—help that's solidly based on years of experience. You get all your roofing from one source, assuring centralized responsibility, smoother operation and uniform quality!

When desired, Ruberoid Built-up Roofs are bonded for 10, 15 or 20 years, depending upon specification used.







HANDY ROOF INCLINE FINDER

For Your Superintendent

This useful pendulum device instantly gives the roof incline in inches per foot. Helps determine proper type of roof. Made of transparent plastic, it can also be used as a protractor.

FREE ON REQUEST!

ill fuels

CORD



This message is addressed to thoughtful bankers and their architects. Each of you is familiar with Herring-Hall-Marvin's century of leadership in metalcraft engineering. But today we come to you with entirely new standards of bank protection — a new conception of architectural beauty — conveniences that are years ahead — with inbuilt standards of trouble-free service never previously achieved. Many of these improvements, now obtainable, are too far advanced to publicize! We'd prefer to tell you about them. Consult your local Herring-Hall-Marvin office — or write, wire, phone us direct.

HERRING-HALL-MARVIN SAFE

Manufacturers of Bank Vault Equipment - Bank Counters - Tellers' Buses and Lockers - Safe Deposit Boxes - Night Depositories - Bank and Office Safes BUILDERS OF THE UNITED STATES SILVER STORAGE VAULTS AT WEST POINT

General Offices
HAMILTON, OHIO
BRANCH OFFICES

BRANCH OFFICES
In New York, Chicago, Boston, Washington,
St. Louis, Atlanta, Houston, Philadelphia,
Los Angeles, Detroit, Pittsburgh
OTHER AGENCIES ALL OVER THE WORLD

Rolling Steel ORS

Combine Utility-Appearance in the Permanence of Steel

The advantages of the vertical action of Rolling Steel Doors are manifold, as compared with any other type of swinging or sliding door. The ultra modern design of Mahon Rolling Steel Doors and their operating mechanisms; the hot-dipped galvanized steel construction of interlocking slats and hoods; the combined utility and fine appearance—plus the permanence and fire safety of steel-warrants your careful consideration. There is a Standard Mahon Rolling Steel Door, Grille, or Shutter to meet every normal requirement. See Mahon Insert in Sweets' or consult a Mahon Engineer.

THE R. C. MAHON COMPANY Detroit 11, Michigan • Western Sales Division, Chicago 4, Illinois

Representatives in All Principal Cities

Manufacturers of Rolling Steel Doors, Shutters and Grilles, and Mahon Steel Deck for Roofs, Sidewalls, Partitions, Accoustical Ceilings,



DOORS, SHUTTERS AND GRILLES TO MEET EVERY

MAHC

JUNE 1946

51

tful u is

oday s of rchiears free hese adbout rvin

ORLD

RECORD

NOW YOU CAN PUT A
WATERFOLL
"RAINCOAT" ON YOUR BUILDINGS

before after

Have you a property investment that looks shabby?

Does it show the ravages of time and weather? You can put a "raincoat" on your building now that will restore and decorate it like new. The "raincoat" is Waterfoil . . . a scientific contribution of the Horn Laboratories to masonry protection. Waterfoil is manufactured of irreversible inorganic gels. It bonds chemically and physically to the masonry surface forming a hard dense coating. Waterfoil lets the masonry breathe, yet impedes water absorption inwards so as to prevent reinforcing bar rust and spalling. Write for the literature on Waterfoil today.

A. C. Horn Company, Inc.

Established 1897

SUBSIDIARY OF SUN CHEMICAL CORPORATION

Manufacturers of Materials for Building Maintenance and Construction . LONG ISLAND CITY 1, N. Y. . Houston, Texas . Chicago, Illinois . San Francisco, Calif.

ELDORAD

TELECONO IND

9



Typhonite Eldorado — the comfortable, trusted pencil whose purpose is to work with you! It brings out the best in every drawing and does a beautiful job on every job!

DIXON'S TYPHONITE

ELDORADO

PENCIL SALES DEPARTMENT, JOSEPH DIXON CRUCIBLE CO., JERSEY CITY 3, N. J.



TEAMWORK brings RESULTS

Anything can happen when there's a smoothly operating team! And what actually does happen when you specify Columbia window shades or Venetian blinds is that you're assuring your clients years of good service. This is because Columbia believes in teamwork between manufacturer and dealers.

Our dealers are trained to recognize your

problem and to make competent installations. Through their suggestions to us we're able to turn out merchandise tailored to meet the most rigorous demands.

When you suggest Columbia shades and blinds, you're recommending products which give satisfaction through teamwork... Sorry, all merchandise still not immediately available.

See Sweet's Architectural Catalog for more complete information on Columbia products.

Columbia WINDOW SHADES
AND VENETIAN BLINDS

THE COLUMBIA MILLS, INC. . 225 FIFTH AVENUE, NEW YORK 10, N. Y.

TITUSVIILE Compact STEEL HEATING BOILERS



WHEN the gremlins start working they will find Titusville Compact Boilers a tough nut to crack, for they are truly an "all steel boiler"

built to give many, many years of satisfactory, uninterrupted service. Even the front flue doors are pressed out of steel plate, doing away entirely with shut-downs and expensive repairs so often experienced with

other types of flue doors. Ask for your copy of the new Titusville Compact Boiler Bulletin.

HIGH GRADE STEEL 'cause steel can't

BREAK

TITUSVILLE IRON WORKS CO.

Division of STRUTHERS WELLS CORP.

Titusville, Penna.

Plants at Titusville, Pa. and Warren, Pa. Offices in Principal Cities


Dependable since 1860

EXTRA LARGE COMBUSTION CHAMBER

gives the fuel both time and space to burn

CRANE CONCENTRATES PRODUCTION

ON PLUMBING FOR TODAY'S ESSENTIAL NEEDS



PLUMBING FOR NON-RESIDENTIAL CONSTRUCTION

The non-residential field—bospitals, schools, public buildings and other construction—requires plumbing specifically designed to meet many needs. Crane is producing a complete line of equipment for these fields. Be sure to get information on Crane Plumbing for all the plans on your boards and include Crane Plumbing in your specifications.

To aid in meeting today's emergency needs, Crane Co. is concentrating production on residential plumbing equipment specifically designed for the low-cost home. Above are shown fixtures now being produced in quantities in Crane plants. Compact in size and priced to fit the needs of homes built on a limited budget, the fixtures are high in quality — truly representative of the name Crane.

Besides plumbing for the residential field, Crane Co. is producing fixtures to cover the essential needs of non-residential construction.

Whatever plans are on your boards—residential or non-residential—consult your Plumbing Contractor or Crane Branch. They will be glad to assist you in every way possible.

CRANE

CRANE CO., GENERAL OFFICES: 836 S. MICHIGAN AVE., CHICAGO 5

PLUMBING . HEATING . PUMPS VALVES . FITTINGS . PIPE

NATION-WIDE SERVICE THROUGH BRANCHES, WHOLESALERS, PLUMBING AND HEATING CONTRACTORS

ION EEDS

Co. is conment speciwn fixtures s. Compact on a limited

Co. is proresidential


or non-resine Branch.

OFFICES: HICAGO 5

· PUMPS · PIPE

NTRACTOR:

L RECORD



More House, More Heat for Less Money

thanks to Anthracite Simpli-Fire Room!

PODAY so many prospective home

I owners are caught between the

millstones of rising prices and station-

ary incomes. How can you help them?

problem with the conviction that heat

is a necessity only part of the year; that

money could be saved by scientifically

engineering both heating room and sys-

tem; that this money saved could be

The result is the Answer Home with

the Simpli-Fire Room, designed by

Chapman and Evans, one of the most

down from the kitchen, the Simpli-Fire Room eliminates all need for the costly,

old-fashioned cellar, saves construction

1. Conveniently located, a few steps

far-reaching developments in years.

used to buy more and better house.

Anthracite Institute tackled this

2. Heating costs, too, are lower, since the Simpli-Fire Room is designed for anthracite, the economy quality fuel.

3. Because of the Simpli-Fire Room, the use of anthracite becomes easier than anyone ever thought possible. The storage bin is within easy shovel reach

of the heater. Ashes feed by gravity into a light metal basket. This is removed outside the house. Thus, ash shoveling becomes a thing of the past—along with the dust and dirt!

4. Type of heating is optional . . . steam, hot water, warm air. Plenty of heat is assured with warm, healthful floors.

Answer Home No. 2 featured above is an interesting example of the modern cottage, and thanks to the Simpli-Fire Room, thousands can build it.

SIMPLI-FIRE ROOM . . . Heart of the Answer Home. Note its efficiency. See how simple it is to feed the heater . . . how ash shoveling is eliminated.

Architects are invited to write for definitive drawings of this house, together with details of co-operation.

For FREE Plans of this Answer Home—and others —mail coupon today.



ANTERACITE INSTITUTE
115016
ew York 17, N. Y.
charge handsome 16-page color
Inswer Homes Nos. 1, 2 and 3
o details of Simpli-Fire Rooms.

Firm____

7

_Zone___State__

time, reduces over-all cost. warm, healthful floors.

ANTHRACITE INSTITUTE

101 PARK AVENUE, NEW YORK 17, N. Y.

SORRY, NO PLANS AVAILABLE, BUT... Another full color ad in the new Gold Bond series now running in the Saturday Evening Post. Like previous ads, this will probably bring a flood of letters from prospective home builders inquiring, "Where can we'obtain the plans?" And the answer will be, "Consult your architect!" National Gypsum Company, Buffalo 2, N. Y.



Ask your Gold Bond lumber and building material dealer how to have a home like this. He is headquarters for new building products and ideas.

So nice to come home to!

WHEN you swing off the bus at the corner after a hard day's work, think how nice it would be to come home to a new house like this—all your own! That's what a lot of us have been looking forward to for years. Of course, it doesn't have to be this Cape Cod cottage—nice as it is. You might want a "modern" or a colonial type. Or some other traditional style. Whatever the design, it will be your dream home—and you'll love every inch of it!

Few people build more than one home in a lifetime — so it's important to know before you start what to insist on to make your investment a sound one. Take walls and ceilings for instance. It's easy—for a few months or years—to hide cheap, secondrate quality in walls and ceilings. But today, thanks to Gold Bond's years of research, it's just as easy to build walls that will last virtually forever. Firesafe. Ever so much stronger structurally at no extra cost. Walls that turn away summer heat and keep you warmer in winter. That can be decorated in the most charming colors you've ever laid eyes on with a marvelous new paint that dries in one hour.

demanding the six Gold Bond features shown below. They are part of the famous Gold Bond family of 152 better building products, produced in 23 modern plants and sold through 10,000 leading lumber and building material dealers.

There's a Gold Bond Dealer in your locality. See him first when you start thinking about new building or modernizing. He can bring you the latest in building products and ideas. He can really make that new home "so nice to come home to" in beauty and value at no more than the cost of ordinary construction. National Gypsum Company, Buffalo 2, N. Y.

Over 150 tested Gold Bond Building Products for new construction or remodeling add greater permanency, beauty and fire protection. These include wallboard, lath, plaster, lime, sheathing, wall paint, insulation, metal and sound control products.

You can get these advantages and many more by

DEMAND
THESE SIX
GOLD BOND
FEATURES
IN YOUR
NEW HOUSE

GTFEUM SHEETHING

Big, weatherproofed panels of Gold Bond Storm Sealed Gypsum Sheathing add structural strength and built-in fire protection. Cost less than old-style sheathing GOLD SOND FLOATING WALL SYSTE



A new way to build plaster interiors with "floating action" to withstand normal structural strain. Longer-lasting beauty. Greater fire protection, GOLD NONG FIRSTRADO GYPSUM LATH



Gold Bond Gypsum lath is the perfect plaster base. Can't warp, expand or contract. Available with insulating vaporseal, metal back as a barGOLD SOND PIETESOD PLASTIE AND LINE



Micron-sized Gold Bond Gypsum Plaster plus specially processed pure white Gold Bond Finish Lime build new beausy and lasting satisfaction into walls and cellings. SOLE SONE HISPEDDS



For greater year 'round comfort in new and of homes. New Extra-efficient. Waterproof. First proof. Verminproof Cuts heating costs a

GOLD BONG SUMPLEX



Dries in one hour with no objectional painty, after odor. Easier to apply. This modern decoration is now available at your dealer's in a full

EXTRA COST

for Stronger Mesker Metal Windows for Schools, Hospitals, Apartments, Office Buildings

> There is no substitute for STRENGTH...yet added strength is just one of the many "extras" making Mesker the outstanding metal window in the field. At no extra cost, you get beauty, convenience and utility PLUS the metal mass so essential for durability and long life – a total thic!:ness of 134" to the casement! No other metal window is made to such generous proportions. Deep ventilator members assure perfect alignment of vents, enhance the weathertightness of the window. Extra depth of frame bars give greater strength, more resistance to wind pressure. We've built "window satisfaction" into the slim lines of every Mesker Metal Window . . . our engineers have designed them to last as long as the building itself!

ETAL WINDO

0

DESIGN FOR AN AUTOMOBILE AGENCY—walls of light make showcase for the 1946 models. Mesker Metal Windows throughout! MAIL THIS COUPON NOW!

MESKER BROS., Dept. AR66, 428 S. Seventh St., St. Louis 2, Mo.

- Without cost or obligation, mail me the following:
- ☐ Book of Apartment Windows
- Book of School Windows
- ☐ Book of Hospital Windows
- ☐ Public Building Windows
- Office Building Windows
- Book of Industrial Windows

☐ Book of Windows for Homes

Architect. Address_

Zone. State_


eatures shown be-Gold Bond famacts, produced in gh 10,000 leading

your locality. See about new buildg you the latest in an really make that e to" in beauty and ordinary construc-

y, Buffalo 2, N. Y.

alers.

L RECORD





THE FRIENDLY FRONT actually puts the entire store on display. Its broad, unobstructed areas of clear glass breathe cordiality and invite immediate inspection of the tempting array of wares revealed within.

The new idea is to plan the front as part of the store itself and you can do this best with complete Brasco Construction. The Brasco line of unified members has been developed and engineered in keeping with the most advanced conception of exterior-interior store front design. All parts are precision machined to fit perfectly and simplify installation problems. Classic beauty of design and finish contribute unobtrusively to the entire architectural scheme.

Brasco Store Fronts are built to endure. Heavy-gauged members, in all modern metals, are steel reinforced where additional strength is required. Exclusive patented features are incorporated for adequate glass protection. Thus, Brasco not only builds beautiful fronts it safeguards that beauty for a lifetime of service.



BRASCO MANUFACTURING CO. HARVEY · (Chicago Suburb) · ILLINOIS

National Distribution Assures Effective Installation

RCA Sound System solves 16-year-old problem of CHICAGO CIVIC OPERA HOUSE

THE WACKER CORPORATION BO NORTH WACKER DRIVE CHICAGO 6

JAMES C. THOMPSON

April 22, 1946

Sound Equipment Section Engineering Products Department Radio Corporation of America 445 North Lake Shore Drive Chicago, Illinois

Our RCA Sound System has overcome a problem in the Opera House that we have had for years -- getting complete audibility in all parts of the auditorium. With the RCA installation even the softest voices reproduced in natural tone are heard clearly in all parts of the house.

From the standpoint of both audience and artist, this installation has been extremely satisfactory and has received much favorable comment. We believe it to be one of the finest installations of its kind in the country.

Hours very truly, James C. Thompson President



View of Chicago Civic Opera House, completed in 1929 with a seating capacity of 3,517. RCA Sound System speakers are strategically located for complete audience coverage.



THIS outstanding RCA Sound System installation provides twenty-one stage microphone positions, any twelve of which may be used simultaneously. Position of the control console in the auditorium balcony permits selection of best operating level for each individual stage microphone and optimum over-all volume level from the standpoint of the listening audience.

Here is another excellent example of RCA Sound System engineering . . . and another excellent reason to come to RCA for the finest in sound equipment. For full information see your local RCA Sound Distributor, or write direct to Sound Equipment Section, Dept. 10-F, Radio Corporation of America, Camden, N. J.

auditorium volume level.

control of twelve stage microphones and

SOUND SYSTEMS

RADIO CORPORATION of AMERICA ENGINEERING PRODUCTS DEPARTMENT, CAMDEN, N. J.

rated for beautiful service.

store on breathe empting

ore itself

on. The

gineered

r-interior

perfectly

sign and scheme.

nembers,

strength

CO.

lation

RECORD



"It's GAS for heat," says Doyle

"Oh no", says Brown, it's OIL"





... yet both of them agree the best for heat's G.E.



WHETHER your client is Brown or Doyle, you can go along with his heating preferences and still specify G. E.

There are G-E gas- or oil-fired units for your steam, hot water or conditioned warm air applications. Each of these is time-tested, reliable . . . worthy of the G-E reputation . . . and *yours!*

Remember, too, that a G-E unit will please your client because of its economical operation. Some G. E. owners

have reported savings up to ½ their fuel bill.

So, for the kind of home-planning clients tell their friends about, be sure to include a G-E unit in your specifications. See Sweets Catalog for details. For information on price and delivery call your nearest G-E dealer—you'll find him listed in your Classified Telephone Directory. General Electric Co., Air Conditioning Department, Section 6446, Bloomfield, N. J.

Automatic Home Heating

GENERAL ELECTRIC

OIL-FIRED



Boiler for steam or hot water heating systems



G-E Winter Air Conditione (warm air)



G-E Conversion Oil Burner



Boiler for steam or hot water heating systems



G-E Winter Air Conditioner
(warm air)

GAS-FIRED


FOR INSIDE AND OUT YOU CAN SPECIFY.

Alcoa Aluminum

One of the outstanding advantages of Alcoa Aluminum as a building material is the fact that it is not limited to either inside or outside use. You can gain by using it for both interior and exterior applications.

Where you need structural strength and light weightspecify aluminum. If you need a material with weather resistant quality-Alcoa Aluminum has it. It can't rustcan't rot-can't warp. And for decorative purposes, Alcoa Aluminum has almost limitless applications.

Yes, inside and outside, you'll build better with Alcoa Aluminum. Be sure you include this versatile building material in the plans on which you are now working. ALUMINUM COMPANY OF AMERICA, 1867 Gulf Building, Pittsburgh 19, Pennsylvania.









VERSATILE OF ALL BUILDING MATERIALS



























ALCOA ALUMINUM



Conditioner

Gase Study Louse 11 the "GI" model



WITH CASE PLUMBING FIXTURES

Planned to satisfy high standards of convenience and comfort without exceeding the limits of "GI" budgets, this house is designed with two efficient bathrooms. The Case plumbing fixtures were selected by the architect to meet both requirements in full. Their design, vitreous china construction and mechanical excellence assure lifetime satisfaction and freedom from costly maintenance. Case plumbing fixtures are distributed nationally—see your Classified Telephone Directory or write W. A. Case & Son Mfg. Co., Buffalo 3, N. Y. Founded 1853.

THE LAVATORY is the ever-popular Cosmette with concealed front overflow, anti-splash rim, chrome finish accessories and convenient shelf. Available also in wall-hung style.



THE WATER CLOSET is the 2-piece combination *DeLuxe* model, with modern styling and a silencing device that assures quietness under all pressures. Free-standing tank does not deface the wall.



Douglas Fir Plywood Again Allocated

-To Meet the Urgent Needs of the Reconversion Housing Program

TODAY'S most urgent and immediate need is for housing—and the Douglas fir plywood industry pledges complete cooperation with the Reconversion Housing Program.

The demand for housing requires that Douglas fir plywood again be put on an allocation basis. This means that a substantial proportion of the industry's production will be channelled to housing contractors, stock cabinet manufacturers, prefabricators and distributors

As a result, the present supply situation for all other industrial and construction uses will be temporarily aggravated.

May we strongly urge you to anticipate your needs far in advance—and discuss your requirements with your regular sources of supply.

Even though today the supply situation in Douglas fir plywood is critically short, for many projects such as forming concrete surfaces, for signs and display work, for boat building, and for many other industrial and commercial uses, it is almost indispensable. In these cases it is well worth waiting for, as it will save time and labor and do a better job.



Douglas Fir Plywood Association Tacoma 2, Washington

uxe model, es quietness ce the wall.

TURES

rt without

with two

eous china

atisfaction ctures are

ectory or


ded 1853.



COMMERCIAL SOLVENTS CORPORATION, penicillin plant, Terre Haute, Indiana. Diffused natural daylight floods areas where laboratory workers conduct experiments with white rabbits. Insulux has high insulating properties which reduce cost of air conditioning and heating.



SPERRY GYROSCOPE COMPANY, precision manufacturing, Long Island, New York. Insulux panels bring light to stairways and other dark corners in factories or homes. Insulux transmits and diffuses light better than ordinary windows.



Insulux Glass Block is a functional building material—not merely a decoration. It is designed to do certain things that other building materials cannot do. Investigate!

Controlled Daylight

... and more ... with Insulux

ARCHITECTS are making increased use of Insulux Glass Block because it is a functional building material with unique characteristics and because it adds to the appearance of most buildings.

Panels of Insulux transmit and diffuse natural daylight better than ordinary windows. Besides *controlling* light they seal out dirt and dust –insure privacy. High insulating value reduces the cost of heating and air conditioning.

Insulux resists vapor and fumes-painting is not required. It is easy to clean and keep clean.

In laboratories, factories, public buildings, stores, theaters, offices and homes if there is a problem in light control there is usually a spot for the advantageous use of Insulux Glass Block.

Investigate the almost unlimited architectural possibilities of this modern building material.

5 REASONS WHY

- 1 SAVE FUEL-Better insulation means less fuel loss.
- 2 SAVE UPKEEP CHARGES-Easy to clean—and to keep clean. No painting required.
- 3 SAVE MAN HOURS-Better light control insures better working conditions.
- 4 SAVE SPOILAGE LOSSES-No infiltration of dust or dirt.
- 5 SAVE REPLACEMENT COSTS-Panels of Insulux do not rot, rust or corrode.

OWENS - ILLINOIS

INSULUX

GLASS BLOCK

For technical data, specifications, and installation details, see our section in Sweet's Architectural Catalog, or write: Dept. C-6, Owens-Illinois Glass Co., Toledo 1, Ohio.

Here's how to "dress up" exposed cold lines

These pictures show the application of Armstrong's Cork Covering to a fitting where both efficient insulation and maximum attractiveness are wanted. Although covering often must be thick to help maintain low temperatures, it need not look clumsy and conspicuous. It can be streamlined, with a surface that's easy to clean.



1. Cork covering on cold line ready for final finish; valve still uninsulated.




2. Sections of Armstrong's Fitting Cover cemented together and wired on.



3. Hexagonal mesh wire stapled over fitting cover to provide key for cement.



4. Asbestos and portland cement mixture troweled on in two coats.



5. Final finish on low-temperature valve and line is 8-oz, canvas, sewed on, sized and painted with two coats of good quality oil paint in desired color. (Steps not shown here: all joints are sealed with Armstrong's Seam Filler, and interior voids are poured with Armstrong's Fitting Filler.)

COLD LINE INSULATION must always be efficient—but in many applications a smooth, clean looking appearance is a further asset. In buildings where cold lines are exposed, the application of this finish can contribute greatly to orderly and sanitary appearance.

Straight sections of covering are finished in the same manner as fitting covers, except that instead of the addition or hexagonal mesh wire and cement. rosin sized paper is wrapped around the cork covering before application of the sewed canvas and paint finish.

For further information on Armstrong's Cork Covering and other low-temperature insulations, write today to Armstrong Cork Co., Building Materials Division, 2406 Concord Street, Lancaster, Pa.

ARMSTRONG'S INDUSTRIAL INSULATION Complete Contract Service For All Temperatures To 2600° Fabrenheit

n in Sweet's ado 1, Ohio.

characterngs. etter than

and dust

ating and

It is easy

lly a spot

s of this

painting

nditions.

corrode.

GOOD WASHROOMS

one of the Big 4"in good working conditions

...say men and women workers in 400 plants



ISABEL: "You can tell how considerate a company is of its employees just by looking at the washrooms."

GRACE: "Can't you though! They must really want us to be happy here—they keep this one so clean and pleasant."

Sanitary modern washrooms mean a whole lot to women workers . . . and men workers too. An unbiased survey of men and women workers from coast to coast shows that these factors are the "Big 4" in good working conditions: good washrooms, proper lighting, safety devices and adequate ventilation.

Besides helping keep workers happy, plenty of hot water, soap and good quality individual paper towels help keep germs from spreading. By encouraging frequent and thorough washing, good washrooms help reduce the number of absences due to colds and their more serious complications.

Haven't you yourself been irritated by a poorly planned, badly equipped washroom? Then make sure your washrooms are designed to be "Health Zones," not "Germ Exchanges"—"morale-boosters," not "temper-testers."



Good Washrooms begin at the Drawing Board

Efficient, well-equipped washrooms that help keep workers healthy and happy are a result of careful thinking and planning in the blueprint stage. For practical suggestions on modern washroom layout, turn to our four pages in Sweet's catalog—or call on the Scott Washroom Advisory Service, Scott Paper Company, Chester, Pennsylvania.

SCOTTISSUE TOWELS STAY TOUGH WHEN WET



Trade Marks "ScotTissue," "Washroom Advisory Service" Reg. U.S. Pat. Off.

tions

LIGHT MODERNIZATION

at its
Finest

Littoburgh Lermaflector LIGHTING

EQUIPMENT



"Something Better Has Come to Light!"

INCANDESCENT:

Show Window Permaflectors -Recessed Ceiling Units - Indirect Permaflectors - Luminaires -Spotlights - Floodlights - Stage Lights - Accessories.

FLUORESCENT:

The Presidential Luminaires for pendant or surface mounting · Recessed Troffers · Strips · Accessories

PITTSBURGH PERMAFLECTORS are selected for this, and thousands of other outstanding installations, because they offer the right combination of lighting equipment to meet all design and use requirements for efficient and effective illumination.

Whatever your illuminating requirements—fluorescent, incandescent or a combination of both—if you are interested in efficient light utilization and in improved lighting design . . . you'll want the whole story of Pittsburgh Permaflector Lighting Equipment . . . you'll want to learn how standard units can be tailored to your individual needs.

Every lighting application involves a different set of problems. Our knowledge of lighting, our 31 years of manufacturing "Permaflectors for Every Purpose" enables us to meet all lighting equipment specifications. Consult your nearest Pittsburgh Permaflector Lighting Engineer for further information.



Pillsburgh Reflector Conspany
Oliver Building • Pittsburgh 22, PA.
Manufacturers of Permaflector Lighting Equipment
Olstriguted by Better Electrical Wholesales Everywhers
Permaflector Uphting Engineers in all Principal Cities

sty Fibre

the loard

l-equipped

t help keep

and happy

areful think-

g in the blue-

or practical nodern wash-

turn to our

weet's catan the Scott

isory Service, Company, ylvania.

JUNE 1946



NOW! Apartment Dwellers Can Enjoy Individual Comfort

BUILDING OWNERS AND MANAGERS

YOU WON'T have to wait until new apartments are built to enjoy just the comfort temperature you prefer. For Minneapolis-Honeywell has developed a "Personalized" Heating Control System that can be installed in your present apartment. With a thermostat in every suite, you can select your own temperature just as you select your decorations. P. H. C. makes available to every apartment dweller the same unlimited comfort that Moduflow* brings to singlefamily dwellings.

Now you can install a P. H. C. System in your existing building without remodeling or even redecorating! By an ingenious method developed and used exclusively by Minneapolis-Honeywell, the work can be done in a matter of hours, without inconvenience to your tenants. See below how easily and inexpensively this can be done.

During the past 18 months, Honeywell P. H. C. Systems have been installed in 232 buildings (3,099 suites) in 28 different cities. They are not only greatly increasing tenant satisfaction (which means longer leases) but they are also saving fuel at an average rate of 20 per cent.

* Moduflow is the name given to Honeywell's newest heating control system for homes. It means heat modulated to whatever temperature is required for comfort, with a uniform, continuous flow.



COMFORT UNLIMITED

Each tenant can have the comfort temperature he desires. Just set the thermostat-as simple as dialing in your favorite

CUTTING THE GROOVE

Special cutting tool, designed by Honeywell, cuts groove in wall to conceal wiring. Vacuum cleaner attachment removes plaster chips and dust.



NO "MOVING DAY"

radio station.

You won't have to face the terrors of moving day in order to enjoy the even. comfortable temperature that only apartments equipped with P. H. C. can offer.

COVERING HIS TRACKS

The flexible copper tubing is sealed in the groove with a specially prepared plastic cement. Then the groove is concealed with adhesive tape previously prepared to exactly match the wall color.



NO UNHEALTHFUL OVERHEATING

No more colds and sickness caused by overheated apartments or drafts from windows opened to get relief. And, precious fuel is saved for other useful purposes.

JOB FINISHED

Within an hour after he started, the service man has departed, leaving behind no mess or evidence of his work. Just as simple as installing a telephone.



IF YOU ARE PLANNING TO BUILD, you should get complete information about Honeywell P. H. C. Systems . . . Just mail the coupon or write to Minneapolis-Honeywell Regulator Company.

HEATING CONTROL

MINNEAPOLIS-HONEYWELL	REGULATOR	COMPANY
2600 Fourth Avenue South	Minnegnolis 8	Minnesota

Please send information about M	I-H Personalized Hea	ting Control for:
Existing Buildings	New Buildings	
Name	***************************************	******
Street Address		
City	State	
Owner Manager	Architect	Engineer

RECORD

WHAT ARE ESSENTIAL BUILDINGS?

And how can we get them built? Most kinds of buildings are considered essential by their particular protagonists, and with logical justification. But when materials and manpower are short, some types of buildings can be deferred more easily than others if the welfare of the nation is the criterion. The Wyatt program puts all emphasis on low-cost housing for veterans. The public would certainly include schools and hospitals high on the list of the essential and non-postponable buildings. We agree.

Now that the first fanfare of the ambitious publicity drive has announced the stage set, the realities of the situation are being appraised by the clear-headed, both in government and out. There is a growing awareness that homes for veterans at rents or prices within reason will be attainable only when three conditions exist:

First, when price adjustments encourage full production of scarce building materials, and competition is again a factor in building supplies.

Second, when the building of all types of dwellings (except the luxury class) is again permitted; i.e., the building of both low and moderate-cost dwellings — multifamily, row, or single family — for rent as well as for sale. The total supply must be increased. Moderate-cost dwellings and fireproof apartments will add new units that will release lower-cost units, for in the final analysis everyone lives in a "second-hand" home, veterans and civilians alike.

Third, when rental housing entrepreneurs, insurance companies and the like can be assured of a fair return on their investments, rent ceilings realistically related to production, operation and other costs.

It should go without saying that the production of materials is the prime requisite, and Wilson Wyatt has the power to speed production by making it profitable for the manufacturers to produce. Then, and only then, can housing and schools and hospitals and other essential buildings get under way in the volume necessary for the welfare of the country, as well as for the welfare of the building industry. The planning of all such buildings should continue in architects' offices at an unabated pace, to be ready when materials and equipment again are flowing into the market. For certainly no agency given the responsibility for the production of homes, for veterans or other civilians, can fail to see the obvious necessity of fulfilling the three conditions stated.

The hospital is one of the essential building types and hospitals for veterans will undoubtedly have preferences. The Veterans' Administration will soon be calling upon the architectural profession to plan the permanent hospitals for its immense and necessary program. It is indicated that architects in private practice will be called upon to do this work at top speed under lump-sum professional contracts. Requirements and standards will soon be worked out. The standards worked out so thoroughly and efficiently by the U. S. Public Health Service (Marshall Shaffer, Senior Hospital Architect) should prove invaluable to architects engaged in or contemplating hospital planning. We are happy to be privileged to publish them at this opportune time. Hospitals too are essential buildings.

Seweth K. Stowell

get complete Just mail the or Company.

By an

matter

below

ystems in 28

tenant

re also

PANY
nesota
Control for:

.....

ingineer [

RECORD

ELEMENTS



U. S. PUBLIC HEALTH SERVICE

Federal Security Agency

THE GENERAL HOSPITAL


Eugene Marlin


News from Washington indicates that necessary non-residential building projects are going forward, and that hospitals should be well up in the list of those permitted to escape the restrictions growing out of the G. I. house program. And reports from the field show plenty of current activity in hospital building. This has no direct reference to any federal-aid program that might result from the proposals of the U. S. Public Health Service for more hospital facilities in rural areas, which is embodied in a bill now before the Senate (S.191) and reported in Architectural Record in August, 1945.

A wide variety of demands for information on hospital planning from the Hospital Facilities Section (Technical Services Unit) of the Public Health Service has resulted in the publication of the material herewith, which amounts to a veritable planning guide for architects and hospital administrators. Architects who have come to know what a wealth of planning information has been gathered by Marshall Shaffer, chief architect, and staff, will welcome the publication of this series of plans of typical elements of the general hospital.

Physical requirements of hospital structures have changed extensively in recent years. Development of new diagnostic and therapeutic methods has brought about the need for new facilities and equipment. Improved methods of hospital administration have engendered similar problems. New construction materials and advances in construction design have resulted in basic revisions of building plans. These plans have resulted from innumerable consultations with doctors, nurses, hospital consultants, dietitians, hospital architects, hospital administrators, technicians, manufacturers and members of the U. S. Public Health Service and other agencies. The series starts in this issue of the Record, will continue next month.

ADMINISTRATION SUITES






1. Administration Suite for a 50-Bed General Hospital

Except for a few points, these plans speak for themselves. The medical record room is separate from the business office, where only business records are kept. Medical record room is placed opposite the staff lounge so that the medical librarian has a chance to catch physicians, in case it is necessary to urge them to get their records up to date. Doctors should be routed past the

information desk to simplify keeping of the in-and-out register. The director of nursing is located near the hospital administrator, who naturally gets the sheltered corner location. In this small hospital suite, social service is combined with the admitting office since the small amount of social service work enables one person to handle both assignments

2. Administration Suite for a 100-Bed General Hospital

In this larger suite social service is given a separate office, since the increased load justifies separate personnel. And, in addition to general expansion of facilities, there has been added a retiring room, for the use of bereaved relatives





In the 200-bed hospital the administration suite logically becomes a separate wing, or indeed, as here, virtually a separate building. The same facilities are provided as in the 100-bed hospital, but naturally enlarged for the increased load, and the same prin-

ciples hold: the staff lounge and library, here with conference facilities added, is still near the medical records room; administrator and director of nursing, with secretarial staff, are together in a protected suite; social service near the general business office

Legends: 1. Administration Suite for a 50-Bed General Hospital. 1. Waste paper receptacle. 2. Executive-type desk. 3. Executive-type chair. 4. Straight chair, upholstered. 5. Built-in bookshelves. 6. Typist's desk. 7. Typist's chair. 8. Filing cabinet. 9. Straight chair. 10. Safe. 11. Counter, 40 in. high, cash drawer, with cabinets and drawers below. 12. Telephone switchboard. 13. Doctor's in-and-out register. 14. Costumer. 15. Typewriter table. 16. Card index file. 17. Table, 34 by 60 in. 18. Hat shelf with clothes rod below. 19. Shelf, 2 ft. above floor. 20. Easy chair. 21. Conference table. 22. Table. 23. Built-in bench. 24. Water cooler. 25. Shelf. 26. Janitor's service sink. 27. Mop truck. 28. Bulletin board, 26 by 24 in.

2. Administration Suite for 100-Bed General Hospital.

1. Waste paper receptacle. 2. Executive-type desk. 3. Executive-type chair. 4. Straight chair, upholstered. 5. Built-in bookshelves.

2. Typist's desk. 7. Typist's chair. 8. Filing cabinet. 9. Straight hair. 11. Counter, 40 in. high, cash drawer, with cabinets and rawers below. 12. Telephone switchboard. 13. Doctors' in-and-out register. 14. Costumer. 15. Typewriter table. 16. Card index lie. 17. Table, 34 by 60 in. 18. Hat shelf with clothes rod below.

19. Shelf, 2 ft. above floor. 20. Easy chair. 21. Conference table.

22. Table. 23. Built-in bench. 24. Water cooler. 25. Shelf. 26. Janitor's service sink. 27. Mop truck. 28. Wire mesh partition with sliding gate. 29. Glass screen. 30. Counter, 48 in. high, open below. 31. Three passenger settee. 32. Spiral stairway down to dead record room. 33. Collapsible partition. 34. Bulletin board, 26 by 24 in.

3. Administration Suite for a 200-Bed General Hospital.

1. Waste paper receptacle. 2. Executive-type desk. 3. Executive-type chair. 4. Straight chair, upholstered. 5. Built-in bookshelves.

6. Typist's desk. 7. Typist's chair. 8. Filing cabinet. 9. Straight chair. 11. Counter, 40 in. high, cash drawer, with cabinets and drawers below. 12. Telephone switchboard. 13. Doctors' in-and-out register. 14. Costumer. 15. Typewriter table. 16. Card index file. 17. Table, 34 by 60 in. 18. Hat shelf with clothes rod below. 19. Shelf, 2 ft. above floor. 20. Easy chair. 21. Conference table. 22. Table. 23. Built-in bench. 24. Water cooler. 25. Shelf. 26. Janitor's service sink. 27. Mop truck. 28. Wire mesh partition with sliding gate. 29. Glass screen. 30. Counter, 48 in. high, open below. 31. Three passenger settee. 32. Table, 34 by 72 in. 33. Colapsible partition. 34. Bulletin board, 26 by 24 in. 35. Bookcase. 36. Translucent glazing. 37. Counter, lift top and gate front.

register. nistrator,


nis small

ng office


e person

added a

8-0




4. Laboratory for a 50-Bed General Hospital



m C 36 si Li de V

H be per st be hit N

5. Laboratory for a 100-Bed General Hospital



6. Laboratory for a 200-Bed General Hospital

Legends: 4. Laboratory for a 50-Bed General Hospital.

1. Desk, 2. Filing cabinet. 3. Microscope table, 30 in. high, with cabinets and slide drawers below. 4. Cup sink with gooseneck spout. 5. Microscope. 6. Analytical balance with weights. 7. Acid resisting counter, 36 in. high. 8. Cabinets below counter. 9. Wall cabinets. 10. Book shelves. 11. Acid resisting laboratory sink with gooseneck spout. 12. Air, gas and electric outlets. 13. Single element hot plate. 14. Bunsen burner. 15. Acid resisting laboratory sink with peg boards. 16. Table, 30 by 54 in. 17. Straight chair. 18. Stool. 19. Sanitary waste receptacle. 20. Closet. 21. Wheel cart for frozen sections. 22. Laboratory autoclave, 16 by 24 in. 23. Hot air sterilizer, 18 by 14 by 14 in. 24. Incubator, 12 by 12 by 12 in. 25. Water bath. 26. Centrifuge. 27. Shaking machine on stand. 28. Waste paper receptacle. 29. Refrigerator, 8 cu. ft.

5. Laboratory for a 100-Bed General Hospital. 1. Desk.
2. Filing cabinet. 3. Microscope table, 30 in. high, with cabinets and slide drawers below. 4. Cup sink with gooseneck spout. 5. Microscope. 6. Analytical balance with weights. 7. Acid resisting counter, 36 in. high. 8. Cabinets below counter. 9. Wall cabinets. 10. Book shelves. 11. Acid resisting laboratory sink with gooseneck spout. 12. Air, gas and electric outlets. 13. Single element hot plate. 14. Bunsen burner. 15. Acid resisting laboratory sink with peg boards. 16. Chemistry table. 17. Straight chair. 18. Stool. 19. Sanitary waste receptacle. 20. Closet. 21. Wheel cart for frozen sections. 22. Laboratory autoclave, 16 by 24 in. 23. Hot air sterilizer, 24 by 14 by 14 in. 24. Incubator, 19 by 16 by 14 in. 25. Water bath. 26. Centrifuge. 27. Shaking machine on stand.

28. Waste paper receptacle. 29. Refrigerator, 8 cu. ft. 30. Refrigerator, 6 cu. ft. 31. Arnold sterilizer. 32. Shelves over chemistry table. 33. Hospital bed. 34. Cubicle curtain rod and curtain. 35. Basal metabolism apparatus. 36. Electrocardiograph apparatus. 37. Hook strip. 38. Table, 30 by 36 in. 39. Shelving. 40. Sliding window curtain. 41. Adult scale. 42. Bedside table.

6. Laboratory for a 200-Bed General Hospital. 1. Desk.
2. Filing cabinet. 3. Microscope table, 30 in. high, with cabinets and slide drawers below. 4. Cup sink with gooseneck spout. 5. Microscope. 6. Analytical balance with weights. 7. Acid resisting counter, 36 in. high. 8. Cabinets below counter. 9. Wall cabinets. 10. Book shelves. 11. Acid resisting laboratory sink with gooseneck spout. 12. Air, gas and electric outlets. 13. Single element hot plate. 14. Bunsen burner. 15. Acid resisting laboratory sink with peg boards. 16. Chemistry table. 17. Straight chair. 18. Stool. 19. Sanitary waste receptacle. 20. Closet. 21. Wheel cart for frozen sections. 22. Laboratory autoclave, 16 by 24 in. 23. Hot air sterilizer, 30 by 24 by 18 in. 24. Incubator, 28 by 18 by 20 in. 25. Water bath. 26. Centrifuge. 27. Shaking machine on stand. 28. Waste paper receptacle. 29. Refrigerator, 8 cu. ft. 30. Refrigerator, 6 cu. ft. 31. Arnold sterilizer. 32. Shelves over chemistry table. 33. Hospital bed. 34. Cubicle curtain rod and curtain. 35. Basal metabolism apparatus. 36. Electrocardiograph apparatus. 37. Hook strip. 38. Table, 30 by 36 in. 39. Shelving. 40. Sliding window curtain. 41. Adult scale. 42. Fume hood. 43. Executive-type desk. 44. Executive-type chair. 45. Counter, 36 in. high, cabinets below. 46. Bedside table.

Legends: 7. Morgue and Autopsy Room for a 50-Bed General Hospital. 1. Mortuary refrigerator for two bodies. 2. Waste paper receptacle. 3. Combination instrument and scrub sink with gooseneck spout and spray and knee control. 4. Instrument sterilizer, 9 by 10 by 20 in., on stand. 5. Shelf over sink. 6. Cabinet below counter. 7. Double recessed view box. 8. Counter, 36 in. high, open below. 9. Floor drain. 10. Autopsy table with sink. 11. Mayo table. 12. Scales. 13. Footstool. 14. Kick bucket. 15. Light. 16. Hook strip. 17. Specimen cabinet with glazed doors. 18. Metal top table, 16 by 20 in. 19. Suction apparatus. 20. Ventilator fan. 21. Telephone outlet. 22. Obscure glass.

8. Morgue and Autopsy Suite for 100- or 200-Bed General Hospital. 1. Mortuary refrigerator; for 100-bed hospital, two bodies; for 200-bed hospital, not less than three bodies. 2. Waste paper receptacle. 3. Combination instrument and scrub sink with gooseneck spout and spray and knee control. 4. Instrument sterilizer, 9 by 10 by 20 in., on stand. 5. Shelf over sink. 6. Cabinet below counter. 7. Double recessed view box. 8. Counter, 36 in. high, open below. 9. Floor drain. 10. Autopsy table with sink. 11. Mayo table. 12. Scales. 13. Footstool. 14. Kick bucket. 15. Light.


16. Hook strip. 17. Specimen cabinet with glazed doors. 18. Portable observation stand. 19. Suction apparatus. 20. Ventilating fan. 21. Telephone outlet. 22. Obscure glass. 23. Stretcher. 24. View panel.

9. Morgue and Autopsy Suite for 200-Bed General Hospital. 1. Mortuary refrigerator for four bodies. 2. Waste paper receptacle. 3. Combination instrument and scrub sink with gooseneck spout and spray and knee control. 4. Instrument sterilizer, 9 by 10 by 20 in., on stand. 5. Shelf over sink. 6. Cabinet below counter. 7. Double recessed view box. 8. Counter, 36 in. high, open below. 9. Floor drain. 10. Autopsy table with sink. 11. Mayo table. 12. Scales. 13. Footstool. 14. Kick bucket. 15. Light. 16. Hook strip. 17. Specimen cabinet with glazed doors. 18. Portable observation stand. 19. Suction apparatus. 20. Ventilating fan. 21. Telephone outlet. 22. Obscure glass. 23. Stretcher. 24. View panel. 25. Table, 30 by 84 in. 26. Closet.


NOTE: This arrangement is recommended for a 200-bed or larger hospital when facilities are to be utilized by a medical examiner.

The small morgue in Fig. 7 is about the minimum room in which any autopsy work can be done. The next larger one, Fig. 8, might do for either a 100-bed or a 200-bed hospital; for the larger one it should have refrigerated space for at least three bodies. The separation of body refrigerator from autopsy room permits removal of a body while an autopsy is in progress in the other room.

The size of the morgue depends to a certain extent on whether or not the facilities will be used by a medical examiner. In any case, of course, the morgue should be located so as to prevent unnecessary contact of the general public, convenient to the elevator, with an isolated exit, if possible, to the service yard. Adequate ventilation is an obvious requirement, usually a window exhaust fan



7. Morgue for a 50-Bed General Hospital



8. Morgue for a 100- or 200-Bed General Hospital




9. Morgue for a 200-Bed General Hospital

hemistry tain. 35. paratus. Sliding

1. Desk. cabinets spout. 5. resisting cabinets. ooseneck hot plate. with peg tool. 19. or frozen Hot air 20 in. 25. tand. 28. rigerator, table. 33. 35. Basal atus. 37. ding wintive-type , cabinets

ECORD



10. Radiographic Suite for a 50- or 100-Bed General Hospital

The X-ray department should be conveniently located with respect to the out-patient department as well as the rest of the hospital, for it will be heavily used for outside patients. A first-floor location will usually be found to keep traffic at a minimum. The X-ray room itself should be enclosed in partitions with lead linings, the size and extent of which will vary. The toilet is needed because barium solutions must be evacuated. The arrangement of dressing booths shown is recommended, to permit patients to enter or leave without going through the X-ray room itself. The increased load in the larger hospital requires two radiography units and a separate area for viewing and filing films. There is also space for storing a mobile X-ray unit for use in other rooms



Photo Courtesy of U. S. Public Health Service

Legends: 10. Radiographic Suite for a 50- or 100-Bed General Hospital. 1. Combination radiographic and fluoroscopic unit. 2. Cassette changer. 3. Control unit. 4. Leaded glass view window. 5. Lead lining (size and extent varies). 6. Lead-lined door, light proofed. 7. Barium sink. 8. Recessed cabinet. 9. Light-proof shade. 10. Low cabinet for supplies. 11. Straight chair. 12. Storage cabinet. 13. Cassette pass box. 14. Film loading counter with cabinets below. 15. Film storage bin. 16. Film hanger racks. 17. Safe light. 18. Ceiling light, white and red. 19. Two-door film dryer. 20. Film dryer exhaust. 21. Developing tank with thermostatic mixing valve. 22. Timer. 23. View box, wall mounted. 24. Sink. 25. Towel bar. 26. Stereoscope. 27. Adjustable stool. 28. Wall-mounted view box, 2 units of 4 each. 29. Executive-type desk. 30. View box. 31. Filing cabinet, letter size, 4 drawers. 32. Film filing cabinet, 3 drawers. 33. Footstool. 34. Waste paper receptacle. 35. Telephone outlet. 36. Costumer. 37. Fluoroscopic ceiling light. 38. Hook strip. 39. Mirror. 40. Hook on door. 41. Obscure glass. 42. Movable partition. 43. Light-proofed door. 44. Seat.

NOTE: Maze should be painted dull black. If mobile X-ray unit is to be kept in this area, a storage closet should be provided.

11. Radiographic Suite for a 200-Bed General Hospital.

1. Combination radiographic and fluoroscopic unit. 2. Cassette changer. 3. Control unit. 4. Leaded glass view window. 5. Lead lining (size and extent varies). 6. Lead-lined door, light proofed. 7. Barium sink. 8. Recessed cabinet. 9. Light-proof shade. 10. Cassette tunnel. 11. Straight chair. 12. Storage cabinet. 13. Cassette pass box. 14. Film loading counter, 36 in. high, with cabinets, cassette bins and film storage bins below. 15. Wall cabinet (bottom 3 ft. 8 in. above counter). 16. Film hanger racks. 17. Safe light. 18. Ceiling light, white and red. 19. Film dryer. 20. Film dryer exhaust. 21. Developing tank with thermostatic mixing valve. 22. Timer. 23. View box, wall mounted. 24. Sink. 25. Towel bar. 26. Stereoscope. 27. Adjustable stool. 28. Wall mounted view box, 2 units of 4 each. 29. Executive-type desk. 30. View box. 31. Filing cabinet, letter size, 4 drawers. 32. Film filing cabinet, 3 drawers. 33. Footstool. 34. Waste paper receptacle. 35. Telephone outlet. 36. Closet. 37. Fluoroscopic ceiling light. 38. Hook strip. 39. Mirror. 40. Hook on door. 41. Obscure glass. 42. Executive-type chair. 43. Light-proofed door. 44. Refrigerating unit. 45. Book case. 46. Typist's desk. 47. Typist's chair. 48. Shelving, 18 in. wide. 49. Dutch door. 50. Door with light-proof louver in lower panel. 52. Seat.


NOTE: Maze should be painted dull black.

12. X-Ray Therapy Suite for a 200-Bed General Hospital.
1. Deep therapy unit. 2. Superficial therapy unit. 3. Adjustable stool. 4. Supply cabinet. 5. Lead lining (size and extent varies for floors, walls and ceiling). 6. Lead-lined door. 7. Leaded glass view window. 8. Control unit. 9. Counter, 42 in. high. 10. Sanitary waste receptacle. 11. Telephone outlet. 12. Bedside table. 13. Bed light. 14. Nurses calling station. 15. Bed. 16. Straight chair. 17. Waste paper receptacle. 18. Typewriter desk. 19. Typist's chair. 20. Desk chair. 21. Film filing cabinet. 22. Desk. 23. Table, 12 by 26 in. 24. Wheel chair. 25. Wheel stretcher. 26. Bookcase. 27. Cautery. 28. Examining table. 29. Instrument sterilizer, 4 by

71-6" 3'-6" 9-6" 13-6" 11-6" 41 V-30 27 29 35 DARK RM. 11 150 18'-0" FILM FILING OFFICE & RADIOGRAPHY FLUOROSCOPY ⊕ 37 RADIOGRAPHY 47 46 WALTING 31 34 CORRIDOR FEET

11. Radiographic Suite for a 200-Bed General Hospital

6 by 16 in. 30. Combination instrument and scrub sink, with gooseneck spout and knee control. 31. Instrument cabinet. 32. Shelf — 31 in. high. 33. Mirror. 34. Hook strip. 35. Stool with back. 36. Non-metallic treatment chair. 37. Dome-light and buzzers. 38. Footstool. 39. Easy chair.



12. X-Ray Therapy Suite for a 200-Bed General Hospital

the large hospital may be expected to have a heavy load of X-cay therapy, and will require separate facilities—separate facilities—separate for madiography and fluoroscopy. The department should be in a sead-end location so that no through traffic will be necessary. The description of the should be located near the waiting room, for pre-

treatment consultation, also near the examination room. A rest room is provided convenient to the deep therapy room, as such treatment frequently requires a period of rest following it. The control room is separate from either X-ray room, with lead-lined partitioning, for the safety of the operators

100-Bed oroscopic dass view ead-lined 9. Lightchair. 12. g counter ger racks. door film a thermomted. 24. stool. 28. tive-type nwers. 32.

h respect

hospital,

-floor lo-

num. The

ith lead

toilet is

The ar-

to permit

y room ito radiog-

ns. There

her rooms

door. 44. Cray unit

ste paper oroscopic door. 41.

Hospital.
Cassette
. 5. Lead
t proofed.
shade. 10.
sinet. 13.
sigh, with
15. Wall
ger racks.
dryer. 20.
tatic mixSink. 25.
28. Wall
ype desk.
32. Film
r receptasic ceiling
. Obscure
r 44. Re-

Hospital. Adjustable varies for glass view. Sanitary table. 13. ight chair. Typist's 23. Table, Bookcase. dizer, 4 by

RECORD

ight-proof

PHYSICAL THERAPY SUITES

Legends: 13. Physical Therapy Suite for a 50-Bed General Hospital. 1. Treatment table. 2. Short wave unit. 3. Table. 4. Linen closet. 5. Soiled linen hamper, closet over. 6. Ultra violet unit. 7. Infra red unit. 8. Straight chair. 9. Ceiling mirror. 10. Combination arm and leg whirlpool. 11. Adjustable chair for arm or leg treatment. 12. Posture mirror. 13. Non-skid mat with crutch markings. 14. High shelves. 15. Shoulder ladder. 16. Stall bars. 17. Walker. 18. Glazed door. 19. Desk, 28 by 48 in. 20. Low filing cabinet, 21. Waste paper receptacle. 22. Hanging rod. 23. Adjustable shelves. 24. Sink. 25. Glass shelf. 26. Wringer. 27. Curtains and rods. 28. Bulletin board, 26 by 24 in.


14. Physical Therapy Suite for a 100-Bed General Hospital. 1. Treatment table. 2. Short wave unit. 3. Table. 4. Linen closet. 5. Soiled linen hamper, closet over. 6. Ultra violet unit. 7. Infra red unit. 8. Straight chair. 9. Ceiling mirror. 10. Combination arm and leg whirlpool. 11. Adjustable chair for arm or leg treatment. 12. Posture mirror. 13. Non-skid mat with crutch markings. 14. High shelves. 15. Shoulder ladder. 16. Stall bars. 17.

Walker. 18. Glazed door. 19. Desk, 28 by 54 in. 20. Filing cabinet. 21. Waste paper receptacle. 22. Glazed panel. 23. Adjustable shelves. 24. Sink. 25. Glass shelf. 26. Wringer. 27. Curtains and rods. 28. Paraffin tank. 29. Low voltage unit. 30. Steps. 31. Bulletin board, 26 by 24 in.


15. Physical Therapy Suite for a 200-Bed General Hospital. 1. Treatment table. 2. Short wave unit. 3. Table. 4. Linen closet. 5. Soiled linen hamper, closet over. 6. Ultra violet unit. 7. Infra red unit. 8. Straight chair. 9. Ceiling mirror. 10. Combination arm and leg whirlpool. 11. Adjustable chair for arm or leg treatment. 12. Posture mirror. 13. Non-skid mat with crutch markings. 14. High shelves. 15. Shoulder ladder. 16. Stall bars. 17. Walker. 18. Glazed door. 19. Desk, 32 by 48 in. 20. Filing cabinet. 21. Waste paper receptacle. 22. Hubbard tank. 23. Mono-rail over. 24. Sink. 25. Glass shelf. 26. Wringer. 27. Curtains and rods. 28. Paraffin tank, built into treatment table. 29. Low voltage unit. 30. Steps. 31. Bulletin board, 26 by 24 in. 32. Typewriter table. 33. Locker, 15 by 15 in. 34. Bench. 35. Wheel stretcher.

Physical Therapy Suite for a 50-Bed General Hospital


Physical therapy suites, like X-ray rooms, should be located for use by out-patients as well as in-patients. Flexibility is a highly important planning consideration, as needs in physical therapy are constantly changing. Also the equipment should be movable wherever possible. The problem is to provide enough flexible, sub-divided space so that patients can engage in the prescribed type of activity without interference with each other, and with privacy when required. However, it is found that the availability of a competent physical therapy technician is frequently a question, one which may in the end have much to do with the facilities provided



14. Physical Therapy Suite for a 100-Bed General Hospital



15. Physical Therapy Suite for a 200-Bed General Hospital



cabinet.

4. Linen unit. 7. Combinam or leg h crutch bars, 17. cabinet. Iono-rail and rods. voltage

ljustable ains and teps. 31.

al Hospewriter tretcher.


35

ECORD

OCCUPATIONAL THERAPY SUITE

16. Occupational Therapy Suite for a 200-Bed General Hospital. 1. Desk. 2. Chair. 3. Bookcase. 4. Filing cabinet. 5. Waste paper receptacle. 6. Bulletin board, 26 by 24 in. 7. Glazed partitions. 8. Glazed panel. 9. Non-staining sink and drainboard. 10. Shelf over. 11. Adjustable shelves. 12. Leather work bench. 13. Metal work bench. 14. Carpentry work bench. 15. Bicycle jig saw. 16. Electric grinder. 17. Electric lathe. 18. Table loom. 19. Stool. 20. Counter, 30 in. high. 21. Storage under counter.


In this suite storage facilities are important, for there will be a wide variety of tools and paraphernalia. Where possible tables should be arranged for the supervisor to walk around them




16. Occupational Therapy Suite for a 200-Bed General Hospital




Photo courtesy of Presbyterian Medical Center



 Pharmacy for a 50-Bed General Hospital



 Pharmacy for a 100-Bed General Hospital



Here is another department that needs a location near the out-patient department, though here the problem is one of transportation only: there would be no patient traffic to the pharmacy. For the small hospital there is just the one room for the pharmacist; it is assumed that the small institution would not support even one pharmacist for his full time. In the next larger hospital a solution room is added, for it is considered advisable wherever possible to have the pharmacist mix all solutions. In the still larger one, manufacturing is undertaken on a fairly large scale, and the pharmacy begins to be a source of income

19. Pharmacy for a 200-Bed General Hospital



PAUL PARKER Proto—Courtesy of Presbyterian Medical Center
Orderliness and accuracy are essential in the pharmacy

Legends: 17. Pharmacy for a 50-Bed General Hospital.


1. Refrigerator, 8 cu. ft. 2. Drug cabinet. 3. Filing cabinet, letter size, 4 drawers. 4. Telephone outlet. 5. Desk. 6. Book shelves. 7. Straight chair. 8. Waste paper receptacle. 9. Dutch door. 10. Table, 30 by 54 in. 11. Sanitary waste receptacle. 12. Cabinet below drainboard. 13. Acid proof sink and drainboard. 14. Drawing pegs. 15. Graduate rack. 16. Double element hot plate on bracket. 17. Stool. 18. Prescription counter with cabinets below. 19. Fluorescent light below cabinet. 20. Narcotics safe. 21. Window guards. 22. Prescription balance with weights. 23. Counter scale with weights.

18. Pharmacy for a 100-Bed General Hospital. 1. Refrigerator, 3 cu. ft. 2. Drug cabinet. 3. Filing cabinet, letter size, 4 drawers. 4. Telephone outlet. 5. Desk. 6. Book shelves. 7. Straight chair. 8. Waste paper receptacle. 9. Dutch door. 10. Table, 30 by 54 in. 11. Sanitary waste receptacle. 12. Cabinet below drainboard. 13. Acid proof sink and drainboard. 14. Drawing pegs. 15. Graduate rack. 16. Double element hot plate on bracket. 17. Stool. 18. Prescription counter with cabinets below. 19. Fluorescent light below cabinet. 20. Narcotics safe. 21. Window guards. 22. Prescription balance with weights. 23. Counter scale. 24. Counter, 36 in. wide with water resistant top. 25. Shelf, 18 in. above counter. 26. Cabinets below counter. 27. Water still, 5 gal. per hr. 28. Shelf, 36 in. above counter. 29. Rectangular sterilizer, 24 by 24 by 36 in., nickel clad. 39. Locker.

19. Pharmacy for a 200-Bed General Hospital. 1. Refrigerator, 8 cu. ft. 2. Drug cabinet. 3. Filing cabinet, letter size, 4 drawers. 4. Telephone outlet. 5. Desk. 6. Book shelves. 7. Straight chair. 8. Waste paper receptacle. 9. Dutch door. 10. Table, 30 by 54 in. 11. Sanitary waste receptacle. 12. Cabinet below drainboard. 13. Acid proof sink and drainboard. 14. Drawing pegs. 15. Graduate rack. 16. Double element hot plate on bracket. 17. Stool. 18. Prescription counter with cabinets below. 19. Fluorescent light below cabinet. 20. Narcotics safe. 21. Window guards. 22. Prescription balance with weights. 23. Counter scale. 24. Counter, 36 in. wide with water resistant top. 25. Shelf, 18 in. above counter. 26. Cabinets below counter. 27. Water still, 5 gal. per hr. 28. Shelf, 36 in. above counter. 29. Rectangular sterilizer, 24 by 24 by 36 in., nickel clad. 30. Locker. 31. Opaque glass insert in counter. 32. Gas, compressed air and vacuum outlets. 33. Drawers below counter. 34. Adjustable metal shelves above counter height, cabinets below. 35. Sink and drainboard. 36. Table with soapstone top.

9-6" Z O 15 CORRIDOR


21. Nursery for a 50-Bed General Hospital




20. Milk Room

The milk room, for the preparation of babies formulas, can be located either in the dietary quarters or near the nurseries. This one is designed for the so-called "terminal sterilization," in which everything is sterilized together, only "kitchen cleanliness" is required until bottles are filled and capped, then everything is sterilized in the 'autoclave '

These nurseries (see ARCHITECTURAL RECORD May, '43, pp. 76-771 are designed to minimize cross infections, especially for such highly contagious diseases as infant diarrhea, which has caused so many tragedies among new-born babies. Thus each unit has cribs for not more than eight infants, each in its separate cubicle. Each baby cubicle has its own supplies. Every precaution is taken to keep traffic to a minimum: nursery rooms are entered only through the work space, to improve control; work space is partitioned off, also treatment rooms and nurse's station, to keep all possible operations outside of the nursery room itself. Aside from the obvious benefits of isolation, this scheme makes it possible to shut off one room should there be any faint sign of infection, and other unaffected areas can continue in operation. Where such dispersion is not followed, it might be necessary to close virtually all nursery and obstetrical operations to end an epidemic. These plans were developed in cooperation with Chilmen's Bureau, U.S. Department of Labor



22. Nursery for a 100-Bed General Hospital



23. Nursery for a 200-Bed General Hospital

Legends: 20. Milk Room. 1. Desk. 2. Chair. 3. Waste paper eptacle. 4. Refrigerator. 5. Lavatory with knee control. 6. unter, 36 in. high. 7. Cabinets under counter. 8. Bulletin board, by 24 in. 9. Sink. 10. Two element hot plate. 11. Sanitary waste eptacle. 12. Rectangular pressure sterilizer, nickel clad. 13. k cart. 14. Partition, 5 ft. high. 15. Holder for formula record k. 16. Electric bottle washer. 17. Dutch door. 18. Access door. Telephone outlet.

Nursery for a 50-Bed General Hospital. 1. Bassinet.
 Bedside cabinet. 3. Table, 16 by 24 in. (for infant scale). 4.
 Lavatory with gooseneck spout and knee control. 5. Waste paper receptacle. 6. Sanitary waste receptacle. 7. Linen hamper. 8.

Pass window with shelf and sliding sash. 9. Table, 24 by 36 in 10. Nurses' desk with chart rack for 8 charts. 11. Telephone outlet. 12. Straight chair. 13. Hook strip. 14. Sink in counter with gooseneck spout and knee control. 15. Counter, 36 in. high, with cabinets below. 16. Instrument sterilizer, 4 by 6 by 16 in. 17. Wall cabinet. 18. Single element hot plate. 19. Refrigerator, 6 cu. ft. 20. Counter, 36 in. high, open below. 21. Stool. 22. Chart rack for 2 charts. 23. Incubator. 24. Gown hook. 25. Cubicle partitions, 5 ft. 6 in. high, clear glass in upper panels.

NOTE: Where use of large incubators is contemplated, cubicle size should be increased accordingly.

ter size, 4 . Straight Table, 30 low drainving pegs. acket. 17. . Fluoresw guards. scale. 24. elf, 18 in. still, 5 gal. sterilizer. 1. Refrigtter size, 4 7. Straight ble, 30 by rainboard. 5. Gradu-Stool. 18. scent light 22. Pree counter. 28. Shelf. by 36 in., unter. 32.

3

s a loca-

though

he phar-

s just the

imed that

ort even

the next

dded, for

possible

ns. In the

rtaken on

cy begins

Hospital.

net, letter

helves. 7.

door. 10.

. Cabinet 14. Draw-

plate on

ets below. 21. Win-

. Counter


Refrigera-


vers below er height,

with soap-


RECORD

OPERATING SUITES






The operating suite is one of the hospital departments that requires a cul-desac location, as there is enough going on without any through traffic. The several entrances help separate the traffic and serve to minimize confusion



Usually there is a minimum of two operating rooms, one for major, one for minor surgery. One room for major operations is considered adequate for 50 beds of a general hospital; thus one more major room is added for each 50 beds, though it is not necessary to provide additional rooms for minor operations. The actual operating rooms always take the most isolated locations



All of these departments are here planned to adjoin the central sterilizing and supply rooms. In the smaller building they can be within the operating department (with separate entrance) but in

larger ones there gets to be too much traffic; the same general principle prevails, but central sterilizing moves out of the suite, somewhat farther from operating rooms, nearer hospital center




HUGH STERN Photo

is not neces-The actual ons

15'-3"

SURGICAL DEPARTMENT ROOMS



STORAGE 19,61 ESTHESIA STERILE RECORDER CORRIDOR 29. Fracture Room CORRIDOR CORRIDOR FEET

30. (See legend)

31. (See legend)

In Fig. 27 sterilizing facilities are only for instruments, and for emergency work — most sterilizing is done in central room. In Fig. 28, cystoscopic room, both the toilet and the dark room are

essential adjuncts. In the fracture room, Fig. 29, the doors must be large since many fracture cases are strapped up with rather ungainly contraptions. Plaster and splint closets must be large

Legends: 27. Operating Rooms. 1. Sink and drainboard. 2. Counter, 36 in. high, open below. 3. High speed pressure sterilizer, 16 by 24 in. 4. Water sterilizers, 15 gal. ea. 5. Blanket and solution warmer. 6. Mercury switch. 7. Floor drain. 8. Glass shelf over scrub sinks. 9. Scrub sink. 10. Soap dispenser. 11. Clock. 12. Alcohol dispenser. 13. View window, clear glass. 14. Portable emergency light. 15. Sponge rack. 16. Double basin stand. 17. Instrument table, 24 by 48 in. 18. Mayo table. 19. Operating table. 20. Operating light. 21. Footstool. 22. Kick bucket. 23. Single basin stand. 24. Anesthetist's table. 25. Anesthetist's stool. 26. Anesthesia unit. 27. Pack table. 28. Explosion proof electric outlet. 29. Adjustable stool. 30. Irrigator stand. 31. Adjustable open let. 29. Adjustable stool. 30. Irrigator stand. 31. Adjustable open shelving, 18 in. wide. 32. Vision panel. 33. Clock and interval timer. 34. Double recessed view box. 35. Aspirator below view box. 36. Flush ceiling fixture for general illumination. 37. Explosion proof calling station, foot operated. 38. Corridor dome light.

28. Cystoscopic Room. 1. Shelf. 2. Sink in counter with gooseneck spout and knee control. 3. Counter, 36 in. high, open below. 4. Light proof shade. 5. Wall cabinet. 6. Adjustable stool. 7. Urological X-ray table. 8. Ceiling light. 9. Kick bucket, 10. Wheeled catheter tray. 11. Examining light. 12. Electric cautery. 13. Urological instrument cabinet, 19 by 30 in. 14. Irrigator stand. 15. Film hanger rack above counter. 16. Safelight. 17. Exhaust fan. 18. Light proofed door with light proof louver. 19. Ceiling light, white and red. 20. Towel bar. 21. Developing tank, 18 by 22 in. 22. Film drying bracket for 12 films. 23. Sink with shelf over. 24. Timer. 25. Waste paper receptacle. 26. Counter, 36 in. high,

with cabinets below. 27. View panel. 28. Double recessed view box. 29. Footstool.

29. Fracture Room. 1. Instrument table, 18 by 36 in. 2. Galvanized iron can. 3. Counter, 36 in. high, open below. 4. Plaster vanized from ean. 3. Counter, 36 in. high, open below. 4. Plaster sink. 5. Plaster trap. 6. Light proof shade. 7. Fracture table. 8. Footstool. 9. Ceiling fixture. 10. Double recessed view box. 11. Linen hamper. 12. Vision panel. 13. Three shelves, 12 in. wide. 14. Plaster drawer, 3 in. deep, open below. 15. Adjustable stool with back. 16. Plaster bin. 17. Six shelves, 18 in. wide. 18. Step ladder. 19. Two rows of 3/4 in. diameter dowels, 12 in. o.c., staggered; top row 6 ft. from floor; bottom row, 5 ft. from floor.

NOTE: Corridor doors should be light proofed.

30. Anesthesia Storage and Cleanup Room. 1. Shelving 18 in, wide. 2. Sink with gooseneck spout and knee or elbow control. 3. Counter, 36 in. high, open below. 4. Cabinet below counter, 2 ft. wide. 5. Sanitary waste receptacle. 6. Waste paper receptacle. 7. Linen hamper. 8. Double compartment laundry tray with drainboards. 9. Wringer. 10. Clinical sink. 11. Vision panel. 12. Dome light and buzzer set 5 ft. 6 in. from floor.

NOTE: Radiator to be omitted in Anesthesia Room.

31. Instrument and Sterile Supply Room, Surgical Supervisor and Recorder for a 200-Bed General Hospital. 1. Step ladder, 2. Shelving 18 in. wide, 3. Instrument cabinet, 4. Vision panel. 5. Waste paper receptacle. 6. Straight chair. 7. Desk. 8. Telephone outlet. 9. Shelving 12 in. wide. 10. Glazed door and partition, clear glass. 11. Blackboard.

CENTRAL STERILIZING AND SUPPLY ROOMS, LOCKER ROOM

Legends: 32. Doctors' and Nurses' Locker Rooms in Surgical Suite. 1. Mirror, 84 by 24 in., above counter. 2. Counter, 30 in. high, open below. 3. Stool, 18 in. high. 4. Waste paper receptacle. 5. Easy chair. 6. Linen hamper. 7. Bulletin board, 26 by 24 in. 8. Lockers. 9. Telephone outlet. 10. Desk. 11. Straight chair. 12. End table. 13. Instrument cabinets. 14.

33. Central Sterilizing and Supply Room for a 50-Bed General Hospital. 1. Counter, 36 in. high, open below. 2. Shelf. 3. Sink and drainboard. 4. Wall cabinet. 5. Supply cart. 6. Waste paper receptacle. 7. Multiple rubber tube washer. 8. Table, 42 by 72 in. 9. Counter, 36 in. high, cabinets and drawers below. 10. Dressing sterilizer, 24 by 24 by 36 in. 11. Water still, capacity 5 gal. per hr. 12. Ventilated mechanical space. 13. Pass window. 14. Telephone outlet. 15. Desk. 16. Step ladder. 17. Sterile supply cabinets. 18. Glove drying rack. 19. Dutch door. 20. Bulletin board, 26 by 24 in. 21. Straight chair. 22. Hot air sterilizer, 18 by 14 by 14 in. 23. Floor drain.

NOTE: Convenient to this room provide a storage room for unsterile supplies and equipment.

34. Central Sterilizing and Supply Room for a 100-Bed General Hospital. 1. Counter, 36 in. high, open below. 2. Shelf. 3. Sink and drainboard. 4. Wall cabinet. 5. Supply cart. 6. Waste paper receptacle. 7. Multiple rubber tube washer. 8. Table with shelf over, 42 by 96 in. 9. Counter, 36 in. high, cabinets and

drawers below. 10. Dressing sterilizers; one, 24 by 24 by 36 in.; one, 20 by 36 in. 11. Water still, capacity 5 gal. per hr. 12. Ventilated mechanical space. 13. Pass window. 14. Telephone outlet. 15. Built-in desk, 30 in. high with drawer. 16. Step ladder. 17. Sterile supply cabinet. 18. Glove drying rack. 19. Dutch door. 20. Bulletin board, 26 by 24 in. 21. Straight chair. 22. Hot air sterilizer, 24 by 14 by 14 in. 23. Floor drain. 24. Dumbwaiter.


NOTE: Convenient to this room provide a storage room for unsterile supplies and equipment.

35. Central Sterilizing and Supply Room for a 200-Bed General Hospital. 1. Counter, 36 in. high, open below. 2. Shelf. 3. Sink and drainboard. 4. Wall cabinet. 5. Supply cart. 6. Waste paper receptacle. 7. Multiple rubber tube washer. 8. Table with shelf over, 42 by 96 in. 9. Counter, 36 in. high, cabinets and drawers below. 10. Dressing sterilizers; one, 24 by 36 by 48 in.; one, 24 by 24 by 36 in. 11. Water still, capacity 5 gal. per hour. 12. Ventilated mechanical space. 13. Pass window. 14. Telephone outlet. 15. Desk. 16. Step ladder. 17. Sterile supply cabinet. 18. Glove drying rack. 19. Dutch door. 20. Bulletin board, 26 by 24 in. 21. Straight chair. 22. Hot air sterilizer, 30 by 24 by 18 in. 23. Floor drain. 24. Dumbwaiter. 25. Laundry chute. 26. Glazed partitions. 27. Adjustable stool.


NOTE: Convenient to this room provide a storage room for unsterile supplies and equipment.

All of these recommended hospital elements are based on the plan of having central sterilizing and supply rooms, from which all departments are supplied. With supplies thus handled and sterilized there is considerable saving in equipment installations.


as otherwise many departments would have duplicate facilities. There is also the possibility of high efficiency in having skilled personnel do all such work, with adequate equipment and adequate space. And the central room can use autoclaves



32. Doctors' and Nurses' Locker Rooms



33. Central Sterilizing and Supply Room for a 50-Bed General Hospital



34. Central Sterilizing and Supply Room for a 100-Bed General Hospital

35. Central Sterilizing and Supply Room for a 200-Bed **General Hospital**

ECORD

OR FELT

7-6"

RECORDER

...

legend)

ors must

th rather

be large

sed view

. 2. Gal-. Plaster table. 8. box. 11. in. wide. ble stool 18. Step .c., stag-loor.

elving 18 control. nter, 2 ft. ptacle, 7. th drain-

2. Dome

Surgical

lospital. binet. 4. 7. Desk.

door and


JUNE 1946

EMERGENCY SUITES

The emergency suite is one department which has no relation to the size of the hospital. The determining factor is simply the amount of emergency work the hospital is called upon to handle. The smaller one is considered a minimum department, and contains no beds at all. The plan at the top of the page shows something much more suitable for regular emergency department work; the hospital might well require still more facilities



36. Small Emergency Suite



37. Large Emergency Suite

The observation beds in this larger emergency suite are for observation of patients who might not be admitted to the hospital; drunkards are a familiar variety. Office is for police officers. Double operating facilities for multiple cases like automobile accidents


Legends: 36. Small Emergency Suite. 1. Telephone outlet. 2. Wheel stretcher. 3. Wheel chair. 4. Waste paper receptacle. 5. Explosion proof outlet. 6. Clock. 7. Portable emergency light. 8. Mayo table. 9. Adjustable stool. 10. Kick bucket. 11. Examining table. 12. Footstool. 13. Resuscitating apparatus. 14. Anesthesia unit. 15. Instrument table, 16 by 24 in. 16. Single basin stand. 17. Mercury switch. 18. Clinical sink with bed pan flushing attachment. 19. Combination instrument and scrub sink with gooseneck spout and knee control. 20. Instrument sterilizer, 9 by 10 by 20 in., on stand. 21. Counter, 36 in. high with cabinets below. 22. Wall cabinet. 23. Locked wall cabinet with inner locked narcotic compartment and inside light. 24. Vision panel.

25. Obscure glass.

37. Large Emergency Suite. 1. Telephone outlet. 2. Wheel stretcher. 3. Wheel chair. 4. Waste paper receptacle. 5. Explosion proof outlet. 6. Clock. 7. Portable emergency light. 8. Mayo table. 9. Adjustable stool. 10. Kick bucket. 11. Examining table. 12. Footstool. 13. Resuscitating apparatus. 14. Anesthesia unit. 15. Instrument table, 16 by 24 in. 16. Double basin stand. 17. Mercury switch. 18. Clinical sink with bed pan flushing attachment. 19. Combination instrument and scrubsink with gooseneck spout and knee control. 20. Instrument sterilizer, 4 by 6 by 16 in. 21. Counter, 36 in. high with cabinets below. 22. Wall cabinet. 23. Locked wall cabinet with inner locked narcotic compartment and inside light. 24. Leg stand.

25. Sanitary waste receptacle. 26. Curtain and rod. 27. High speed pressure sterilizer, 16 by 24 in. 28. Single soap dispenser. 29. Hook strip. 30. Straight chair. 31. Shallow tub. 32. Towel bar. 33. Linen hamper. 34. Lavatory with gooseneck spout and knee control. 35. Blanket warmer. 36. Dome light and buzzer, set 5 ft. 6 in. from floor. 37. Filing cabinet, letter size, 4 drawers. 38. Desk. 39. Locker. 40. Bedside cabinet. 41. Bed light. 42. Nurses' calling station with duplex receptacle. 43. Adjustable hospital bed. 44. Cubicle curtain and rod. 45. Sliding window curtain. 46. Cubicle partition, 7 ft. high with obscure glass in upper panels. 47. Night light. 48. Wall bracket light, switch controlled. 49. Corridor dome light. 50. Vision panel. 51. Obscure glass.


The obstetrical department is also a deadened unit, which should have the end location on a separate maternity floor. In the typical general hospital about 12 to 20 per cent of the patients will be maternity cases. And the rule is to provide one delivery room for each 20 maternity beds or less, regardless of the size of the hospital. Similarly one labor bed is provided for each 10 maternity beds, or two for each delivery suite. The delivery suite is very similar to a regular operating department. Here is shown the wide corridor, for the volume of traffic that might have to move swiftly. A dumbwaiter off this corridor, connecting with the central sterilizing and supply room, is a very handy appurtenance. The cots in the doctors' locker room are for those weary ones who must wait through the wee small hours for the stork to visit their patients



38. Delivery Suite for a 100-Bed General Hospital

Legend: 38. Delivery Suite for a 100-Bed General Hospital.

1. Combination box spring and mattress on legs. 2. Night table.
3. Straight chair. 4. Telephone outlet, 5. Waste paper receptacle.
6. Table. 7. Double recessed view box. 8. Lockers. 9. Bulletin board, 26 by 24 in. 10. Linen hamper. 11. Wheel stretcher. 12. Double compartment laundry tray with drainboards. 13. Wringer.
14. Clinical sink with bed pan flushing attachment. 15. Dome light and buzzer set 5 ft. 6 in. from floor. 16. Counter 36 in. high, open below. 17. Cabinet below counter, 2 ft. wide. 18. Sanitary waste receptacle. 19. Vision panel. 20. Adjustable open shelving, 18 in. wide. 21. Clock with sweep second hand. 22. Explosion proof outlet. 23. Corridor dome light. 24. Mercury switch. 25. Single basin stand, 26. Explosion proof calling station, foot operated. 27. Aspirator. 28. Heated bassinet. 29. Adjustable stool. 30. Portable emergency light. 31. Anesthetist's table. 32. Anesthetist's stool. 33. Anesthesia unit. 34. Instrument table. 35. Kick bucket. 36. Delivery table. 37. Obstetrical light. 38. Mayo table. 39. Kick basin. 40. Flush ceiling fixture for general illumination. 41. View window, clear glass. 42. Scrub sink. 43. Soap dispenser. 44. Clock. 45. Shelf over scrub sinks. 46. High speed pressure sterilizer, 16 by 24 in. 47. Floor drain. 48. Water sterilizers, 15 gal. ea. 49. Sink in counter. 50. Wall cabinet set 42 in. from floor. 51. Blanket and solution warmer. 52. Lavatory with gooseneck spout and knee control. 53. Examining light. 54. Nurses' calling station with duplex receptacle, 55. Bed light. 56. Bedside cabinet. 57. Obstetrical bed. 58. Footstool. 59. Shelving. 60. Dumbwaiter connecting with central sterilizing room. 61. Labor bed. 62. Water conlect.



39. Delivery Suite for a 200-Bed General Hospital

Note the change of scale here — though this suite appears smaller, actually it is the larger one. Equipment would be the same as in the suite in the top plan; the major addition is a third labor room

o. Curtain sterilizer, enser. 29. L. Shallow hamper. pout and mer. 36. 6 in. from r size, 4 D. Bedside es' calling 43. Adle curtain rtain. 46. h obscure ght light. controlled.

RECORD

ion panel.

INDEX TO HOSPITAL PLANS

IN THIS ISSUE

ADMINISTRATION DEPARTMENT

- 1. Administration Suite for a 50-Bed General Hospital
- 2. Administration Suite for a 100-Bed General
- 3. Administration Suite for a 200-Bed General Hospital

ADJUNCT DIAGNOSTIC AND TREATMENT FACILITIES

- 4. Laboratory for a 50-Bed General Hospital
- 5. Laboratory for a 100-Bed General Hospital
- 6. Laboratory for a 200-Bed General Hospital
- 7. Morgue for a 50-Bed General Hospital
- 8. Morgue for a 100- or 200-Bed General Hospital
- 9. Morgue for a 200-Bed General Hospital
- 10. Radiographic Suite for a 50- or 100-Bed General Hospital
- 11. Radiographic Suite for a 200-Bed General Hospital
- 12. X-Ray Therapy Suite for a 200-Bed General Hospital
- 13. Physical Therapy Suite for a 50-Bed General Hospital
- 14. Physical Therapy Suite for a 100-Bed General Hospital
- 15. Physical Therapy Suite for a 200-Bed General Hospital
- 16. Occupational Therapy Suite for a 200-Bed General
- 17. Pharmacy for a 50-Bed General Hospital
- 18. Pharmacy for a 100-Bed General Hospital
- 19. Pharmacy for a 200-Bed General Hospital

NURSERY

- 20. Milk Room
- 21. Nursery for a 50-Bed General Hospital
- 22. Nursery for a 100-Bed General Hospital
- 23. Nursery for a 200-Bed General Hospital

SURGICAL DEPARTMENT

- 24. Operating Suite for a 50-Bed General Hospital
- 25. Operating Suite for a 100-Bed General Hospital
- 26. Operating Suite for a 200-Bed General Hospital
- 27. Operating Rooms
- 28. Cystoscopic Room
- 29. Fracture Room
- 30. Anesthesia Storage and Cleanup Room
- 31. Doctors' and Nurses' Locker Rooms in Surgical
- 32. Doctors' and Nurses' Locker Rooms
- 33. Central Sterilizing and Supply Room for a 50-Bed General Hospital
- 34. Central Sterilizing and Supply Room for a 100-Bed General Hospital
- 35. Central Sterilizing and Supply Room for a 200-Bed **General Hospital**

EMERGENCY DEPARTMENT

- 36. Small Emergency Suite
- 37. Large Emergency Suite

OBSTETRICS DEPARTMENT

- 38. Delivery Suite for a 100-Bed General Hospital
- 39. Delivery Suite for a 200-Bed General Hospital

NEXT MONTH

NURSING DEPARTMENT


- 40. 25-Bed Nursing Unit Southern Exposure With Offset Corridor
- 25-Bed Nursing Unit Southern Exposure
 25-Bed Nursing Unit East-West Exposure
- 43. 34-Bed Nursing Unit Open Ward East-West Exposure
- 44. Contagious Disease Nursing Unit
- 45. Bedrooms for Contagious Disease Nursing Unit
- 46. Utility Room and Nurses' Work Room, Kitchen and Dishwashing Room for Contagious Disease Nursing Unit
- 47. Pediatric Nursing Unit
- 48. Bedroom for Pediatric Unit
- 49. Bathroom for Pediatric Unit
- 50. Typical 1-Bed Room
- 51. Typical 2-Bed Room
- 52. Bedrooms with Connecting Shower and Toilet
- 53. Typical 4-Bed Room
- 54. Open Ward
- 55. Isolation Suite
- 56. Treatment Room for Nursing Floor
- 57. Nurses' Station and Stretcher Space
- 58. Service Group for Nursing Unit
- 59. Utility Room
- 60. Floor Pantry (for Central Tray System)

SERVICE DEPARTMENT

- 61. Kitchen for a 50-Bed General Hospital Using Central Tray Service
- 62. Kitchen for a 100-Bed General Hospital Using **Central Tray Service**
- 63. Kitchen for a 200-Bed General Hospital Using
- **Central Tray Service** 64. Laundry for a 50-Bed General Hospital
- 65. Laundry for a 100-Bed General Hospital
- 66. Laundry for a 200-Bed General Hospital
- 67. Central Storeroom for a 100-Bed General Hospital
- 68. Record Storage for a 100-Bed General Hospital
- 69. Nurses' Locker Room for a 100-Bed General Hospital

OUTPATIENT DEPARTMENT

- 70. Outpatient Department for a 50-Bed General Hospital
- 71. Outpatient Department for a 100-Bed General Hospital
- 72. Outpatient Department for a 200-Bed General Hospital
- 73. Examination and Treatment Room with Dressing Cubicles
- 74. Examination and Treatment Room
- 75. Two Examination and Treatment Rooms with **Waiting Room**
- 76. Combined Doctor's Office, Examination and Treatment Room with Waiting Room
- 77. Doctor's Office with Two Examination and Treatment Rooms
- 78. Surgical Room
- 79. Eye, Ear, Nose and Throat Room for a 200-Bed **General Hospital**
- 80. Eye, Ear, Nose and Throat Room for a Small Outpatient Department
- 81. Dental Suite with Two Operating Rooms



SIX VETERANS ADOPT A BASIC PLAN

FOR THEIR HOMES IN ST. LOUIS, MISSOURI

Joseph Dennis Murphy, Architect

SELDOM would a single plan suit six different owners and six sites, but six veterans, all graduates of Washington University, acquired a strip of land on which all lots adjoin and naturally have the same orientation. This simplified one architect's problem and through an extensive survey of individual family needs and desires he was able to develop a functional and efficient basic plan to suit all six families.

The kitchen, in which the housewife must spend much time, was made the center of the plan, placed to overlook a terrace on which children can play under a mother's watchful eye. There is direct access from the kitchen to the garage which is placed conveniently at the north front of the house. The kitchen itself is ample and airy, having windows on two sides, and dining is provided for in the kitchen, but can be conveniently arranged in the living room or on the terrace, as the season or occasion may demand.

The living room has high windows to the north, but is open to the sunshine to the south, with windows from door to ceiling, and it also overlooks the play terrace, hielding it from the street. One wall of the living room is entirely devoted to storage and closet space, and the high north windows allow plenty of wall space for turniture.

The bedrooms are placed at the south for quiet and for sunshine, and two baths are insurance against early



morning congestion. Large closet space is provided most conveniently, fully equipped with storage facilities and sliding panel doors.

There is no basement and the concrete floor is equipped with radiant heating. Since the houses are of brick, with large glass areas, a minimum of lumber is necessary in the construction. Concentrated plumbing also saves scarce material. Economy and convenience spell true functionalism in the homes of these 6 families.

all Out-

With

-West

n and

Using

Using

ospital

General

General

General

General

ressing

s with

d Treat-

d Treat-

200-Bed

oital

ECORD


CO-OP SCHEME CUTS HOUSE COSTS


Sunlight Knolls Project, Yonkers, N. Y.

Pomerance & Breines, Architects


WITH the so-called Wyatt program now dominating the small house field, the age-old problem of architectural services for small houses rears up again in still more serious form. Architects — and their clients — might find something interesting in the current experience of Pomerance & Breines in this cooperative project. Perhaps cooperative is not exactly the right word; "group action" might be better. Each owner bought his own lot after the site plan was worked out. The same architects (the same builders, too) did all the houses together; that's the important cooperation. Or maybe it's more important that in such an operation the architects were able to find a saving of something like 10 per cent, which is rather a significant figure in small houses.


Individual design service was given on each house; each client got a complete custom design. There is, of course, the obvious benefit of fitting each one into the group project, which should be well worth the cost of architectural services even without monetary savings. But there were savings in group purchasing, in similar detailing to a certain extent, and in contractors' charges.














Cooperation pays in small project, for four M. I. T. professors at Winchester, Mass. David J. Abrahams and Associates, Architects

FOUR HOUSES IN GROUP EFFORT

That group action in building houses pays even in small projects is shown by the experience of four professors at M. I. T., who found many satisfactions and several economies in building their own houses. The cooperation began quite naturally in casual conversations, grew into a positive effort by more than a dozen families. These four dissented when the others bought another site, then got together again when they grew fond of this site and managed to make a fortunate purchase. The same architect did all the houses: the same builder erected three of them. Aside from the many benefits of group planning, the owners found many human satisfactions and not a few economies in working together over landscaping projects, pipe trenches, and so on.




HASKELL Photos


The site is a wooded hillside overlooking Mystic Lake, an estate bought and divided by the group. The owner's interest in their project, it is said, was a factor in their securing a favorable price; and their determination to build in traditional styles was one of the factors responsible for his benevolent helpfulness!

1. FOR MR. & MRS. GERALD B. TALLMAN

The Tallmans felt a "Garrison Colonial" best fitted to their typical New England site with its hemlock grove, and, incidentally, best calculated to give maximum space at minimum cost. The front has conventional windows toward the street, but large glass areas toward the lake. Space under the steep roof is developed for storage; over the garage will be a future bedroom and bath. The architect angled the double garage slightly away from the street to keep the doors from being too dominant.









2. FOR MR. AND MRS. ALBERT DIETZ

Because the owner of this house teaches at M. I. T. in the field of building engineering he has frequently been asked why he wanted the services of an architect. It was precisely because, he explains, he has seen so many houses designed by non-architects fail to achieve the grace, pleasing proportions and deft detail that only long experience can give. The plan itself was largely done by the Dietzes, but they were content to leave detailing and proportioning to their architect.




The large picture window in the living room, flanked by two doublehung windows, proves a magnet for all who enter the house, including members of the family, who



Orientation made it inevitable that principal rooms should be on the lake side. With some trepidation the owners decided to combine living and dining rooms into one large area running the length of the house. The arrangement has proved "completely satisfactory, especially when large groups have been entertained." Living-dining area here does not become a highway to other rooms





CORD



3. FOR MR. AND MRS. M. S. MCILROY

The McIlroys wanted proximity to the lake, a large front yard, and quiet. They made an extensive survey with an electronic noise-level meter, and found an important diminution of noise below the crest of the slope. Advantage is taken of this fact by placing study and guest bedroom on the lower level; thus the house becomes a cottage as seen from the road, but has two useable stories facing the lake.

BED ROOM 10'-9'-14'-6' CL RECREATION 12'-9'-70'-0' UNEXCAVATED BASEMENT DINING 11'-0'-15'-0' BED PM. 11'-0'-12'-3' LIVING 11'-0'-15'-0' BED PM. 11'-0'-15'-0' CC. CC. CC. CC. CC. PC-15'-0' BED PM. 11'-0'-15'-0' BED PM. 11'-0'-15'-0' CC. CC.

4. FOR MR. AND MRS. R. H. ROBNETT

The Robnett house is the only one not featuring a picture window toward the lake. Two matching bay windows, glass door to porch, and the half-wall between dining and living rooms were worked out to give a view from any point in both rooms. The large kitchen has worked out to good advantage; the normal work space is compact, but there is extra space for many people to help with informal entertaining.






ARCHITECTURAL RECORD

Prepared in collaboration with Motion Picture Herald — Better Theatres

THE SMALL MOTION PICTURE THEATER (400 Seats)



Prepared under the direction of Ben Schlanger, Architect, by Jedd Stow Reisner, Architect Daniel W. B. Warner, Architect Max O. Urbahn, Architect

Edward Content, Acoustical Engineer

William A. Hoffberg, Engineer


Frederick E. Sutton, Mechanical Engineer

with an article on the small theater budget by Chester Friedman, editor of the Managers' Round Table Department of Motion Picture Herald

SDOM.

ORD

THE SMALL MOTION PICTURE THEATER (400 Seats)



Salient features are: the "Continental" auditorium, having widely spaced rows of seats, with side-aisles only, and plenty of exits; the lounge and soda bar opening to a garden; large parking areas; over-all attractiveness used as "exploitation" instead of blaring lights

THE TYPICAL BUDGET*

To THE architect fresh in this field, there are quite a few puzzles in the rather irrational arrangements that govern theaters. A few preliminary remarks may help to orient him in regard to the main headaches of the owner.

Theater gross income depends, of course, on how many admissions can be sold at how high a price. It is generally assumed that a theater, in order to earn a profit, must make total average daily sales equal to its seating capacity. In other words, a 400-seat theater should sell an average of 400 admissions a day. Whether there will really be a profit depends on how high a price can be charged. This depends on (a) the "draw" (the potential of the neighborhood in terms of population density, incomes, radius of appeal, competition, etc.) and (b) the "available product" or quality and timing of films. Factors relating to neighborhoods and the "draw" are discussed more fully in AR, June, 1944, pages 83—

102. The question of available product is complex; basically the problem is whether the owner can obtain product of comparable quality early enough in comparison with his rivals. Admission prices in the new theater are normally less, in a few cases the same, rarely higher than those obtaining among established competitors.

The gross income, then, is estimated by multiplying the seating capacity by the number of days in the year and by the admission price obtainable.

Against this there is an expense budget, in which the cost of "product" or film is the principal item, exceeding the item of building rent. The leading film distributors in the United States anticipate collecting from 30 to 45 per cent of the theater gross for their product. The film (Continued on page 107)


*Contributed by Chester Friedman, Editor of Managers' Round Table Department, Motion Picture Herald.

SITE DEVELOPMENT

Commercial districts are divided into narrow deep lots suitable for stores. Site planning is, therefore, a matter of the owner's financial ability to assemble a parcel of lots. The 400-seat theater developed in scheme B (overleaf) can be built on a 40 ft. lot. If there is an alley at the rear (as we have assumed) then an interior lot is suitable, otherwise a corner lot is necessary. Note that an exit court must be provided whether the plot is interior or on a corner since most codes preclude the obstruction of sidewalks with exterior stairs and the old fashioned fire escape is discouraged.


A more pleasant problem is the small movie theater built as a free-standing unit of a planned shopping center or as a separate enterprise in a suburban semicommercial zone (scheme shown across page). Here the building is visible from many angles and must be considered as a whole design. Lower land costs permit a more generous and more adaptable site. Proper attention must be paid to facilities for parking since a large proportion of the patronage will come from the trade of the far-ranging motorist. The site may be planned to include such income-producing amenities as a day nursery to care for children during parents' attendance at the movie and refreshment gardens. The parking lot can be arranged so that a fee can be charged for parking at certain hours of the day in order to accommodate shoppers in the neighborhood.

The suburban householder is accustomed to think of the movie house as a large brick hulk covering 100 per cent of its lot and equipped with a blatantly lit front, spoiling property values. His eagerness to keep it at arms length is understandable. Scheme A, however, illustrates a theater intended to obviate these prejudices.



TREATMENTS must vary with circumstances. Top sketch conveys the authors' idea of pleasant treatment for a highway theater. This will not interfere with neighboring property values, will attract desirable patronage. The middle sketch represents the unthinking transfer into the countryside of blare and glare which belong more properly in the less happy urban scene below

THE SMALL THEATER



"SCHEME B" seen on this page was developed by the authors to illustrate the possibilities in a theater occupying a lot of only 40-ft. frontage on a downtown street. Use of so narrow a lot is made possible by the "Continental" seating plan of widely spaced seat rows and only two aisles (permitted by the fire underwriters' code but prohibited by many local codes). To prevent the auditorium from becoming unduly long, some of the seats are placed on a "mezzanine" which is cleverly designed as a "pseudo stadium" — meaning that a considerable part of the foyer area is tucked away under these seats. Discussion of auditorium width and of aisles will be found in text



The tiresome marquee of the immediate past is replaced here by a projecting overhang and attraction board. Coming-attraction poster displays are built into the front, which acts as placard

THE AUDITORIUM


THE 400-seat motion picture theater for small towns and rural areas presents an interesting problem because its success depends upon the design which can be built most economically and be operated with a minimum of cost and maintenance. Its design from an optical and acoustical standpoint can be ideal because of the minimum viewing and hearing distances from the projected picture. It would be the ideal package size for the prefabricated motion picture theater, yet it is not very likely that it will appear in prefabricated form because the likely number of sales for such units would not be sufficient to tempt a developer to finance the necessary research and planning. The varying topography of ground sites, the lack of a uniform building code, and variations in operating policies also present important obstacles for the prefabricated development. The one logical method which is left for substantially reducing the cost of the 400 seat unit would be to promote the construction of a number of these units from one set of plans. These units would necessarily be placed where building code restrictions and operating policies would be uniform. Approximately a minimum of 10 such units would make the scheme workable. Actually this scheme would involve a certain amount of prefabrication advantages. The standardization of many of the parts of the structure would decrease the total cost substantially. The individual motion picture exhibitor can and does build a very low-cost motion picture theater and in many instances it is done without professional help.

It would be desirable to bring about some method

whereby this type of construction could have the benefit of proper planning because the results obtained in the past have been most inadequate. The material presented in this compilation may help in avoiding some of the basic errors in planning and at least point to the elements which should be given special attention.

The 400-seat motion picture theater becomes an interesting unit because it can be used equally effectively for the projection of 16-mm. as well as 35-mm. film and, with the proper design provisions, can be made adaptable to the display of television pictures more easily than is possible in the case of larger theaters. The new arc-lamp projection machines made for 16-mm. film permit projection of a usable picture as wide as approximately 14 ft., a size that is readily adaptable for 35-mm. film as well as for these small units. At the present time, television pictures can be projected for a distance of as much as 70 ft. from the projector to the screen. This dimension comes within the range of the small theater plan. While television equipment may as yet be too costly, it is highly possible that in the very near future costs will be reduced sufficiently to make television a possibility in the small unit. Of course, the motion picture industry may reserve priority for larger motion picture theaters and may, therefore, delay its adaptation in a small house.

The diagrams seen below present an analysis of the governing factors in placing 400 chairs for viewing the motion picture. Diagram 1 shows all of the seats placed on one level with aisles only against each side



AUDITORIUM TYPES. 1. Aisles against side walls only — good viewing angles, but rear seats give too small a view of screen which has to be larger; 2. very desirable seating, bringing rear seats forward on semi-stadium at somewhat greater expense; 3. preferred type on adequate ground, all on one level-but requires numerous side exits; 4. meeting demands of almost all codes for bad seating

sl. To of the signed part of sion of

authors

of only

lot is

widely

he fire

raction blacard

CORD

THE SMALL THEATER

wall. This seating plan is too elongated because of the restricted number of seats from aisle to aisle dictated by most of the building codes. The specified number is 14 in most instances. This seating form compels an unnecessarily large picture size for the seating capacity involved. This form is also difficult to handle acoustically.

Scheme number 2 (previous page) suffers under the disadvantage of the extra cost of mezzanine construction. The mezzanine seats, however, are very desirable for viewing the picture.

In order to devise a seating plan for 400 seats having all the seats on one floor and yet retaining a pleasing form, we introduce diagram number 3 in which there are more than 14 seats from aisle to aisle. This type of plan is usable only if local laws will permit such an arrangement or if there are no laws governing theater construction. This arrangement provides even greater safety in case of emergency in completely emptying the theater than the type of plan in which there are exit doors only at the screen end of the auditorium and a restricted back-to-back row spacing of 32 to 34 in. The National Board of Fire Underwriters Building Code




STAGGERING of seats frames the screen between the two heads in the next row forward; second row ahead may be safely ignored

permits a greater number of seats from aisle to aisle, as shown in this diagram number 3.

The specific conditions under which this design can be used are set forth in the 1943 edition of the National Board of Fire Underwriters suggested code, under Article 13, "Places of Assembly, Theaters, Motion Picture Theaters, Assembly Halls and Garages." Section 1300 further deals with "seats in rows." Paragraph 1 (d):

"When individual fixed seats are provided or required, no seat shall have more than six seats intervening between it and an aisle; provided that if the seats are fixed chairs with self-raising seats so spaced that when



Small theater, "Continental" seating, by Peter and Stubbins

Photo courtesy The Westsider



the seats are raised there is an unobstructed space of not less than 18 in. horizontal projection between the rows of seats, and doorways leading directly to exit corridors are provided not more than 5 ft. apart along the sides of the auditorium, the number of seats in a row shall not be limited."

In diagram number 4, 400 seats are arranged in a manner so as to reduce the objectionable depth of seating indicated in diagram 1. This is done by placing 7 seats against each side wall and having a section of seats in the center, 14 chairs wide with aisles as shown. This arrangement conforms to most building codes. It has many disadvantages, however. The aisles are necessarily placed in areas which are otherwise most valuable for viewing positions. The number of seats which come outside of the 60° viewing angle and afford poor viewing positions are far too many compared to any of the other diagrams illustrated. This shape should be avoided for this size theater.

FLOOR SLOPES

Unobstructed vision of the projected picture can be assured with various types of floor slopes. Steep inclinations are entirely unnecessary if a proper staggered placing of the chairs is arranged. A minimum of floor slope is always desirable. The slope of the main floor seating can vary from one that slopes downward only toward the picture to one that slopes partially downward toward the picture and thence slopes upward toward the picture. And in some special instances, the longest slope is upward toward the picture, with a downward slope toward the picture for only those rows which are most remote from the picture. In any case the amount of slope in any direction in so small a theater can be limited to a total of approximately 28 in. if a staggered seating arrangement is used. The topography of the ground or the inclusion of an upper level of seating will determine the type of floor slope for the main floor seating. A slope inclined downward only towards the picture is recommended when an upper level of seating is not contemplated and when the natural ground slopes downward toward the proposed picture position more than approximately 3 ft. Such a slope will place the exit door sills in closest proximity to outside grades thereby avoiding ramps and steps at exit doors.

Where the natural ground is more or less level or slopes upward toward the picture position and where there is no upper level of seating contemplated, the main floor slope should be one that is inclined partially downward and partially upward toward the picture. This



the rows corridors e sides of all not be

ged in a h of seatplacing 7 n of seats wn. This s. It has re necesvaluable ich come r viewing the other oided for

e can be p inclinastaggered 1 of floor iain floor ard only ly downupward nces, the , with a iose rows case the a theater 8 in. if a pography of seating nain floor vards the

level or nd where the main lly downure. This

RECORD

of seating

nd slopes

ion more

e the exit

s thereby

Recessed vent grilles


Spot lights

Plaster

Stationary drape

Corrugated wood sections natural finish

Plaster soffit



AUDITORIUM INTERIOR should be neutral; all attention on the screen

again will place exit door sills at desirable levels. Where the natural ground is as above stated and an upper level of seating is contemplated then the amount of slope upward toward the proposed picture position should be as great or slightly greater than the amount inclined downward toward the picture. This is advisable because it places the picture at a position which is more equally favorable to both the main level and the upper level seating and it also makes it possible to use minimum riser heights between seating platforms on the upper level seating. Only in isolated instances is there an upper seating level to be considered along with a strong upward ground slope of 4 ft. or more in a direction toward the picture position that is contemplated. In such instances the seating slope should be almost entirely upward toward the picture.

SIGHT LINES

The bottom of the projected picture should be not more than 72 in. above the floor of the row of seats nearest to the picture, regardless of the floor slope design. A higher picture position will create too sharp an upward viewing angle for those seated in the rows nearest the picture. Each slope should be carefully calculated. The slopes form very flat curves; also, the slope per row varies for every row. The eye of any viewer should have a direct straight sight line to the desirable arrival point of sight at or near the bottom of the picture (explained in the next paragraph). This line must clear the top of the head of all persons seated two heads or more in front of the eye in question. In any properly designed slope all heads three or more rows in front of the eye in question will be automatically cleared if the head two rows ahead is cleared.

Explanation of arrival point of sight: The arrival

point of sight may advisedly be directly at the bottom of the projected picture or slightly above or slightly below this point subject to the particular row for which sight line clearance is being calculated. For example, in the 22nd row it is desirable to have the arrival point of sight approximately 10 in. below the bottom of the picture, whereas for the 5th row, the arrival point of sight can be as much as approximately 14 in. above the bottom of the picture. In the rows most remote from the picture, the arrival point of sight should come below the picture to provide a margin of safety because obstruction created by a person having an above-the-average torso is more serious than it is in rows close to the picture. This is so because in the remote rows a greater part of the width of the picture is blotted out by a head than is the case in the near rows. The reason for deciding to set the arrival point of sight somewhat above the bottom of the picture in the nearest rows is that a head in this area blots out only a very narrow part of the width of the picture. Great care should be exercised in the design of any floor slope and only a person wellversed in this art should be depended upon for best results. (See Time-Saver Standards, page 129.)

TYPES OF CHAIRS, SIZE AND SPACING

Lift-up seat cushions have been used in theater seating mostly because of the minimum back-to-back row spacing in past practice. This spacing, in accordance with most building codes and popular practice, has averaged about 32 in. A tendency now is towards increasing this dimension. A 33-in. spacing is now closer to the average mark with 34 in. being quite common in receding and new chair installations. If 36 in. were to be used (and there are many instances where it is being used) it is entirely possible that the chair with the lift-up

THE SMALL THEATER

seat cushion may change to a chair with a fixed seat cushion. This would make for a more comfortable and more practical chair because of the more sturdy construction made possible and the elimination of moving parts. The type of seating plan that calls for more than 14 chairs from aisle to aisle would require more than 34 in. row space. In order to conform with the National Board of Fire Underwriters Building Code, the row spacing for fixed seat cushions would be greater than the row spacing if self-raising seats were used.

Upholstery and fabric covering are desirable on the backs of theater chairs more for psychological and acoustical reasons than for actual comfort. There is no particular heavy pressure of the body against the back of the chair and, therefore, excessive spring or padded upholstery is unnecesary especially since any thickness in the chair back greater than 1 in. unnecessarily encroaches into the back-to-back row spacing. The seat cushion, however, requires sturdy and resilient spring construction because of the heavy pressure imposed on the cushion. Chair widths have been for the most part 18, 19, 20 and 21 in. The 18-in. width is entirely undesirable and the 20-in, is the average. The tendency now is towards using 20 in. as a minimum and as much as 22 in. wherever possible. More thought should be given to better arm block design in the wider chairs. Arm blocks now are of a very meager dimension and unstudied form. Chairs 23 and 24 in. wide have to be used in any staggered seating arrangement. Most staggered seating plans have chair widths ranging from 20 in. to 24 in. These varying widths help to control the position of the heads immediately in front of any particular viewer in a properly arranged staggered plan. The heads of the two people immediately in front of the viewer must be on either side of the horizontal lines of sight formed from the viewer's eyes to the extreme edges of the picture width. The angle thereby formed is comparatively narrow for the rows most remote from the picture and is too wide for the rows nearest the picture to make staggered seating usable in the close rows. The point at which the angle narrows down sufficiently to permit the start of the staggered arrangement is determined by the width of the picture and its distance from the viewer. In the portion of the seating area near the picture where staggered seating is made impossible by this wide angle, the floor sloping must provide for the viewer in this section to be able to see clearly over the head of the person directly in front. The floor slope in the staggered area is designed to provide a clear sight line from the viewer over the head of a person seated two rows in front. By fortunate coincidence the floor slope in the unstaggered area does not have to change appreciably because of the steeper vertical angles of vision in this area.

STANDING VIEWING SPACE

Standing viewing space behind the last row of seats on any tier of seating is undesirable because of the annoyance created for people in the last rows of seats. Moreover, the number of people that can be accommodated for viewing the picture from this area is very limited because only two persons in depth can view the picture in this manner at all successfully. It would be better to devote the depth usually given over to this area to foyer space in back of the auditorium. The so-called standing viewing space would then be converted to a minimum dimension cross-over used primarily for circulation to the auditorium seats.

Upper level seating may be either balcony type, stadium type or a type that looks like a balcony but really functions more like a stadium. A balcony is really a tier of seats on a level above the main floor seating and partially or wholly overhangs the rear rows of the main floor. A stadium upper level of seating consists of platforms on steep levels, the lowest level often being as little as 2 ft., approximately, above the level of a crossover between the main floor seating and the stadium. When the stadium is set as low as this, a considerable portion of the area under it becomes waste space because of lack of head room. There are, therefore, many examples of stadiums raised sufficiently to create head room underneath for lounges, fover, toilet and other required spaces. A further development of the stadium is the type in which the first few rows of seating overhang the cross-over behind the main floor seats, thereby bringing all of the stadium seats closer to the screen. This enables reduction of the picture size and permits double use of the floor area normally devoted to a main floor cross-over only. This latter scheme is one which appears to be a balcony but actually is a modification of the stadium. This scheme is illustrated in diagram 2 and page 102, showing reduced viewing distance and reduction of excessive tunnel-like auditorium shape. Upper level seating creates more seating area on a plot of ground that is short in depth, and upper level seating schemes of the projecting stadium type create more main floor area for the lobby, fover, lounge, etc. The extra cost of the upper tier is almost entirely offset by savings in not having to extend the main floor area for the various auxiliary spaces required outside the auditorium proper.

Building codes governing theater construction should be strictly adhered to. In areas where there is no local code, the National Board of Fire Underwriters Building Code may be followed. However, in no case should chairs be placed as close together as the 30 in. allowed by this code. In any area where there is no building code in force, a 400-seat theater with all seats on one level should have at least one emergency exit on either side of the screen end of the auditorium. There should also be at least two entrance ways at the point of entry furthest from the screen. Each exit or emergency door should be at least 5 ft. in clear width, measurement being taken between a pair of doors swung open at right angles to the wall in which they are set. No exit door should obstruct any exit passageway in swinging into the passageway. All doors should open outward toward a street or alley, or safe passageways terminating in a street or alley. Likewise where a local building code doesmodated nited beicture in better to to foyer standing ninimum lation to

ype, staut really really a ting and he main isists of being as a crossstadium. siderable because iany exte head id other stadium ng overthereby screen. permits a main e which ification agram 2 nce and

offset by area for ide the n should no local Building should allowed ing code one level her side allowed also

shape.

n a plot

seating

te more

etc. The

her side her side uld also of entry acy door urement at right xit door into the oward a ang in a ode does

ECORD-

not prevail, balconies should have stairways not less than 4 ft. in width, with emergency exit stairways as well as entrance stairways. Where there are 100 seats or less in the balcony there should be at least one entrance stair and one emergency stair. Extra stairs should be added when this capacity is exceeded. All stairways should lead to the street or alley or safe passageway to a street or alley. In no case should they lead onto any part of the main floor.

The width of the projected picture is determined for best viewing conditions by dividing the maximum viewing distance by 5.2. The height of the picture to the width is as 6 is to 8.25, this ratio varying somewhat when the projection angle is greater than zero degrees. The greater the distance of the projection machine from the picture, the longer the focal length of the projection lens becomes, thereby improving picture quality. There is no loss in light because of greater projection distance; the proper selection of a lens takes care of delivering proper light intensity to a given picture size. In other words, a given light intensity will equally illuminate a 15-ft. wide picture for a projection distance of 50 ft. or 100 ft., the design of the lens being different in each case for projecting the light.

The first row of seats nearest the screen should be a distance away equal at least to the width of the picture. It is desirable to make this distance one and a quarter times the picture width wherever possible. Unless it is required for specific purposes a platform or stage in front of the picture should be eliminated since it serves as a distracting element in the picture's field of vision. The curtain used to conceal the screen from the public after or between showings should not be used during picture projection. Sufficient space should be provided for the curtain to be drawn completely out of view. A dull black material is frequently used to surround the picture proper, supposedly to absorb the fuzzy edge of the projected picture and make it stand out more satisfactorily. Actually this black area has been found to create a contrast with the brightly illuminated picture, creating eye fatigue. This masking can be reduced to about 3 or 4 in. in width and be made of a dark gray material instead of black to absorb the fuzzy edges. The area beyond this masking can be of a still lighter gray.

The projection room should be placed at as low a level as possible and yet high enough so that projected rays are not caught either by structural objects or persons walking in their path. It is advisable to reduce the downward projection angle as much as possible (the line formed from the lens center of the projection machine to the center of the picture). To eliminate noticeable distortion of the projected image on the screen this angle should be 10° or less. The projection room should be at least 10 ft. deep, with 12 ft. preferable. In small theaters it is frequently desirable to use the entire width of the building, or as nearly as possible, for projection room requirements.

For further details on projection room planning see page 115 and Time-Saver Standards, page 131.



Fixed seats a possibility if row spacing is adequate in Continental seating plan. One of these appears tight (auditorium in Poland)

BUDGET (Continued from page 101)

renting and buying business is so complicated that several volumes would be required to explain its workings. Suffice it to say here that the principal factors affecting the picture's availability are the seating capacity of the theater in question and its location in relation to other theaters. If your client's theater is a small house and the only one in the community, he may be compelled to follow other theaters in surrounding towns as much as 30 to 50 miles distant, and may have to wait as long as 21 days after his nearest competitor has completed a showing.

Although building rentals or rental equivalents vary widely, the items so classified begin to become excessive when they go much over 20 per cent of the average annual gross.

The following itemization, while very general, gives a glimpse of the small theater operator's budget:

Budget Item Percentage of	Total Budget
*Film (including shipment)	30
Advertising	3
*Salaries and Wages	6
Rent (or Taxes, Interest, Repair, etc.)	25
*Electrical Power	2.75
Depreciation	8
Maintenance	6
License (negligible) and fuel	0.05
*Insurance (Liability)	1.50
Miscellaneous overhead	2.75
Total	85.05

* Highly variable, depending on local labor conditions, physical condition of theater, location of theater, etc.

Important caution: In many cities the wage scale set up by the motion picture projectionists union is based on the seating capacity of the individual theater. Donot try for extra seats without checking this.


AUDIENCE ACCESS AND CONVENIENCES

PHE amount of space given over to auxiliary requirements outside of the auditorium will vary according to budget. The scheme on page 102 illustrates minimum space for auxiliary requirements and the scheme seen below increases the areas to an amount consistent with their maximum usefulness. Space limitations are always important and, as previously demonstrated, more area on the main floor is obtainable by employing an upper level of seating. The lobby space between the first and second set of doors leading from the street can always be a minimum area because its chief function is to act as a weather lock. The foyer space beyond this area, on the other hand, should be as large as possible and, if space permits, should include a portion designated as a lounge. A ladies' powder room for a 400-seat theater should be a minimum of approximately 6 ft. 6 in. by 8 ft. 6 in. and should be arranged to have one complete wall for mirrors and benches. The manager's office should, if possible, be directly connected with the ticket

selling office. The drinking fountain should be located in the foyer and in a space outside of the heaviest lines of circulation. Candy stands are popular and should be placed where they will be visible on entering the foyer.

TICKET OFFICE


Most admissions are made through the sale of tickets from an electrically-operated ticket-dispensing machine, requiring a ticket seller and a ticket-collecting attendant. While it might be possible to eliminate both of these employees by using a coin inset turnstile, such a scheme leaves the problem of change-making unsolved. It also eliminates the valuable asset of having someone to answer questions, of which there are many from the ticket buyers. Sometimes a turnstile is used to eliminate the ticket collector. The ticket seller trips the turnstile arm to allow the customer through. This is a compromise solution; but since the ticket collector in the (Continued on page 110)



FOYER AND LOBBY, above, are fully developed, for a situation where land costs are not too high. The lounge is off to one side of traffic where it can be used at leisure. Men's and women's rest rooms are easily found by patrons. (Door to men's room shows in the rendering but is covered by the arrow in plan). A standee screen is needed behind the auditorium entrance to block stray light from the street. PHOTOGRAPHS, opposite page, show clean design solutions for problems parallel to ours but not quite the same. The upper view shows sumptuous accommodations in a 500-seat theater in Finland — the plentiful daylight is kept out of the auditorium by the right-angle placement of the doors. The turnstile arrangement in a newsreel theater is possible but not recommended for the regular 400-seater

e located iest lines hould be he foyer.

of tickets machine, tendant. of these a scheme I. It also neone to from the eliminate turnstile is a comfor in the page 110)



Above: Foyer and balcony stair well in a small theater of approximately 500 seats at Turku, Finland; Eric Bryggman, architect. Below: Turnstile in Telepix newsreel theater in Boston, Mass.; Peter and Stubbins, architects



de of traffic e rendering the street. view shows right-angle 400-seater

RECORD

THE SMALL THEATER


(Continued from page 108)

small rural theater is usually the assistant manager at the same time, it might be more practical in most instances to stick to a standard ticket-selling scheme.

The ticket office should be accessible from the interior of the building and should be convenient to the manager's office. Both heating and ventilation should be provided. Public and intercommunicating telephone instruments should be provided because the ticket seller answers all questions in the manager's absence.

TOILET ROOMS

Toilet rooms for the 400-seat theater should be of minimum area sufficient only to accommodate properly the required number of plumbing fixtures. The minimum number of fixtures would be two water closets and one wash basin for the women and one water closet, two urinals, and one wash basin for men. Ceiling height should be minimum so that the entire wall height can be tiled. Recommended water closet compartments are of the ceiling-hung type, leaving the floor completely free for washing and hosing. Toilet room floors should drain for rush cleaning. Toilet rooms should have an independent exhaust ventilating system. Fresh air intake can be provided by making the toilet room doors 21/2 in. short of the saddle. Toilet room entrance doors should be off the foyer and in such position as to be away from the main lines of circulation to and from the auditorium. A view into any part of the toilet room interiors should be avoided by arranging the doors and walls to block possible sight lines.



s and one
oset, two
ng height
eight can
nents are
ompletely
rs should
have an
'resh air
om doors
nee doors
as to be
from the
ilet room
loors and

"EXPLOITATION" FOR THE SHOW



The exploitation problem is entirely different for a 400-seat rural or small-town theater than anywhere else. Customers do not have to be picked off the street in competition with other houses.

The theater marquee extending over the sidewalk has become a fixed institution and a fixed idea among owners, and yet the small theater surely does not need this appendage. Its first cost is high; it consumes considerable electric current; maintenance is burdensome.

The small theater exhibitor's exploitation problem consists chiefly in keeping his patrons informed of the current and coming attractions. He has at his disposal local newspaper advertising, film trailers, and direct mail advertising, as well as interior and exterior poster displays. A large number of small theaters has now been built without the marquee, and the operation of these theaters has been completely successful.


Display frames for posters, placed on the front of

the building and in the lobbies, should have interior illumination. This requires space for the lamps around the margin, and a depth of at least 14 inches. Common poster dimensions: in paper (from producers or National Screen Service): "1-sheet," 27 by 41 in.; "3-sheet," 41 by 81 in.; in cardboard (from National Screen Service) 30 by 40 in. or 40 by 60 in.

High illuminated towers or vertical illuminated signs are not necessary unless the theater patronage is largely derived from automobile traffic on main highways. For a 400-seat theater they are a doubtful luxury.

One of the most important possibilities — not often thought of as "exploitation"— is the provision of comfort and cleanliness for the patron. The things which are most certain to keep patrons coming back are adequate and suitably maintained rest rooms; comfortable seeing and hearing; and a friendly atmosphere. These head the list as factors of effective exploitation.


FROM THEN TO NOW — Pictures on these two pages show the trends. Early theater fronts, if naïve, were quite engaging Later came the agglomeration of Egyptian and Colonial columns, still later "modernistic" gunke. The trend today is toward simple directness. At top, this page, the projecting hood disembarrassed of the clumsy marquee, an "attraction board" remaining, to the right, below, a glittering facade of glass mosaic attracts attention to the institution



INTERIOR MATERIALS AND DESIGN

The proper selection of decorative materials is becoming more and more important in progressive theater design. Latest thinking stresses simplicity of wall surfaces, floors and ceilings and greater interest in surface texture. It is, therefore, important that the covering materials be honest in their application. Imitation marble walls of painted plaster and manufactured board to simulate tiles and wood have no rightful place in correct architectural design. Ideas on the design of space within the theater and materials in that space have changed so much in recent years that the majority of today's theaters are outmoded in appearance. Maintenance of materials has also been long ignored and in consequence the annual upkeep, especially of small theaters, becomes a critical factor.

The periods of gilded plaster and garish modernistic modern of the 1930's are too evident in their bad taste to form a pattern for the modern small theater of the future. The use of metal moldings for decorative effect has been greatly overdone. Use a metal molding if you must to cover a joint in the wallboard but do not apply it on the wallboard to satisfy a decorative urge. Use sculpture, paintings and drapery or plants for decoration. Economy of budget and the effect desired within the concept of modern design dictate the use of the right material in the right places. For instance, cement as-



If budget prohibits marble, avoid imitations. Floor to ceiling mirrors reflect other decorative details, suggest spaciousness

bestos board may be used as a decorative wall covering. Its mottled gray texture harmonizes with any colors desired elsewhere and its hard surface makes it ideal for easy maintenance.


Hard surface permanent finishes of time-tested materials should be used wherever they come into contact with the public. Marble, slate, brick, cement, asbestos board, hardwood, plywoods and asphalt tile should give a range in color, texture and cost to please the most exacting. Painted surfaces should be kept to a minimum since they require constant maintenance. Painted dado finishes which are subject to hard usage should be avoided. Wherever carpets are used as a floor covering subject to constant traffic, plain colors should be avoided unless they be in shades of earth brown or gray. A general over-all abstract pattern carefully selected as to color and kept in scale with the size of the space in which

it is used is the most satisfactory. (Some carpeting should be bought in excess of actual requirements to be used in repair of damaged places.) Linoleum, rubber and asphalt tile when selected with care as to color and pattern can be used effectively as a floor covering within the range of a minimum budget.

This type of floor covering can be extended as dado covering provided proper backing and adhesives are provided. Terrazzo, marble and glass mosaics make for excellent decorative wall materials. The use of glass mosaic should be introduced cautiously and again in right places for a desired decorative effect.

In general, the same decorative finishes used in the lobby and lounge may be carried into the theater auditorium. The acoustic treatment in this room will become a major part of the finish and is best done when left in its natural manufactured state. Many acoustic materials have an integral finish and need no additional painting. Their color should be neutral as should all other auditorium colors. Very dark, very light or excessively strong colors distract the eye from the picture, especially technicolor. Strongest color may occur in seat upholstery. Strong patterns in curtains or wall decorations are to be avoided.

Simplicity of the modern decorative material applies not only to the material but to the wall on which it is placed. Generally speaking the small theater will have a lobby, foyer and rest rooms of small scale, and it is important that the appearance of the rooms be kept as large as possible. It becomes important, therefore, to eliminate wainscot treatments and let the wall material carry from floor to ceiling so that the eye is conscious of the total ceiling height unbroken by a change of wall material. Mirrors can be used decorauvely on walls when put from floor to ceiling at right angles to a major decorative wall. When done this way the color and richness of the major wall is carried on a greater distance through reflection in the mirror. The color of the mirror may be selected from several shades but the common error is to select a mirror color not in harmony with the general scheme. Glass sizes should be as large as possible and joints should not be at eye level.



Ceiling to floor wall treatment surrounding candy counter focusses attention on concession; apply same treatment to display panels

ARCHITECTURAL ENGINEERING

TECHNICAL NEWS AND RESEARCH

THE SMALL MOTION PICTURE THEATER (continued)

STRUCTURAL ECONOMY

STRUCTURAL FRAME: The following alternate types of roof are illustrated:

A. Triangular roof truss

- B. Flat roof truss or long-span steel joists
- C. Hipped rigid frame
- D. Gabled rigid frame

E. Arched frame

These may be fabricated of wood, steel or concrete, depending on the local economics of these materials. A fundamental choice of flat or sloping roof surface is presented. Sloping roofs reduce the heights of walls and snow loading. Parapets may be omitted if roof slopes exceed 20°, but gutters for drainage are necessary. For roof slopes greater then 20°, as in the hipped frame, the visibility of the finished roofing must be considered and an attractive material used.

The interior ceiling treatment varies as illustrated. A suspended plaque treatment may be used except for the

arched interior (E). Ventilating ducts and cove lighting are readily provided in all cases except the arched interior where sloping furred walls become necessary. The arched interior is not acoustically favorable.


For steel construction, a choice of riveted or welded trusses and frames is presented. A typical welded knee and column base is illustrated for a steel rigid frame which shows the simplicity of detail in welding. (Next page.)

Structure is a function of plan and section. The walls may be parallel or tapered in plan, but parallel walls are objectionable acoustically especially for narrow theaters; for tapered walls, the important cost issue of varying spans is raised. Economy in trussed roofs is obtained only in repetition of identical trusses and severe cost penalties result with varying spans. A great virtue of the rigid frame designs is that, with identical knee details, varying spans and column heights can be provided by changing

the in-filling lengths of members. This is illustrated in perspective of the gabled rigid frame (D), next page.

The insurance ratings for various materials and assemblies must be carefully investigated with the Fire Underwriters, since the possible cumulative savings in premium costs may be quite important.

PREFABRICATION: Standardization possibilities for the small theater naturally depend on a standardized plan for the auditorium for varying seat capacities and considerable repetition of identical units. The steel rigid frame (D), as previously described, can be economically shop fabricated, with minimum field connection. The tendency in roof material would be to use rigid panels of minimum volume and of size permitting easy transit and handling. Pre-built wall panels must have required fire rating and rigidity and successful joint treatment. Interior treatment would tend to



Varying structural treatments are discussed in text. More diagrams on next page

carpeting

ents to be ubber and r and pating within

d as dado esives are make for e of glass again in

sed in the

ater audiill become hen left in

materials painting. ther audixcessively

especially

eat uphol-

ations are

ial applies

which it is

will have

and it is

s be kept

therefore,

vall mate-

conscious

ge of wall

on walls

o a major

and rich-

r distance

the mirror

common


with the

is possible

iter focusses play panels

ARCHITECTURAL ENGINEERING

TECHNICAL NEWS AND RESEARCH



rigid panels or may be applied at the site and variety introduced.

Many studies on prefabricated possibilities for the smaller theater are progressing but no structures have yet been built. Successful fermentation in the general field of pre-built panel materials will, of course, be reflected in theater construction.

STRUCTURAL DIAGRAMS

Previous page. **A**, triangular roof truss, **B**, flat roof truss or long-spanned steel joists; **C**, hipped frame.

This page: **D**, detail and perspective of rigid frame construction for gabled roof taking care of varying spans as theater widens; **E**, arched frame.

The curley-cue lines represent light coves

STRUCTURAL ANALYSIS


ITEM	FOUNDATIONS	FRAME	WALLS	ROOF	CEILING	FLOOR
Design factors to		Safety	Initial cost	Weather tightness	Maintenance	Insulation
consider	Soil capacity	Economy	Maintenance	Insulation	Lighting	Finish
	Necessity for piling	Fireproofing	Weather tightness	Initial cost	Ventilation	Maintenance
	Underground water	Bracing	Insulation	Maintenance	Treatment	Ground water
		Cross Section	Acoustics	Weight	Accessibility	Seat support
		(See Study of Types)	Appearance	Appearance	Acoustics	
			Thickness	Drainage		
			Weight	Climate		
			Condensation			
Choice of Materi	als Concrete	Steel girder	Brick	Built-up roofing	Gypsum, cement or	Concrete
(Suggestions—no	t Concrete masonry	Steel trusses	Hollow brick	Asbestos or asphalt	acoustic plaster	Cinder fill
intended as con	n-	Steel rigid frames	Concrete masonry	shingles	Acoustic tile	Gravel fill
plete checklist)		Steel long-span joists	Structural clay tile	Slate	Corrugated asbestos	Hollow tile under floo
	*	Concrete frames	Plastered furring	Clay tile		Cement finish
		Wood trusses	Rigid board furring	Corrugated asbestos		
		(See illustrations)	Corrugated asbestos	Metallic roofing		
Building Code	See Code	Wood trusses	8 in. solid masonry with	Wood, steel or	Fire-retardant, not less	Live loads
Requirements		Steel or concrete	piers or columns of	gypsum roof decks		Orchestra = 60 psf
(National Board	of	trusses or frames	max. spacing 13 ft.	•//	plaster or equivalent	Balconies = 60 psf
Fire Underwrite	ers		12 in. hollow masonry		,	Aisles, corridors and
-1943 Edition)		-max. 20 ft. high			lobbies = 100 psf
			(non-bearing)			Stage floor=150 ps
			No parapets for roof			(National Bureau of
			slope exceeding 20°			Standards—1945)


PROJECTION

STANDARDS for projection room planning published in the Society of Motion Picture Engineers Journal (Sept., '42) and abstracted as Time-Saver Standards (AR Feb., '43) persist as fundamentals for guidance in current practice. Time-Saver Standards in this issue give latest supplementary data on front wall and port planning, wiring, ventilation and fire shutter systems (page 131). Provisions for 16-mm equipment are not covered in these data.


Spurred by the extensive and effective use of 16-mm films for training in the armed forces, producers are presently at work creating a big product in this dimension, with one-reel special features designed primarily for use in smaller theaters where shorter throws make them most advantageous. Sketches below show correct and incorrect planning for 16-mm projection. Yielding to the urge for symmetry by placing the 16-mm projector between the 35's is bad because it gives preferred position to the machine least used. Placing it on the flank as shown achieves an acceptable image on the screen from the 16-mm with a minimum of distortion from the two 35's. Additional advantage may accrue in future use of the 16-mm port and position for television equipment. Dimensions given in the sketches below and in Time-Saver Standards are minimal. Architects should check carefully actual equipment to be used before specifying clearances and height of portholes.

It is well to emphasize again the vibration factor in projection room planning (see discussion by John J. Sefing, AR June '44, p. 95). In theaters of the size treated in this study, inadequate stiffness in construction, permitting as little as 1/500 in, vibration in the projection room floor, could cause half-inch jitters of images on the screen.





Above: Power equipment room. In 400-seat theaters, AC rectifiers replace generator shown here. Above, left: 35-mm projectors in position; exhaust flues connected to overhead duct, running directly to outside air, should provide minimum of 16 cu. ft./min. to each carbon arc lamp. Left: Separate rewind room should provide no less than 80 sq. ft. of floor space; observation ports are required into both the auditorium and projection room



ds

ra = 60 psf

s = 60 psf

porridors and

ile under floor finish

d at the site

cated possi-

er are pro-

have yet

entation in

panel mate-

eflected in

r roof truss;

anned steel

erspective of

gabled roof

as theater

light coves

ance

water

port

FILL FILL

orridors and
es=100 psf
oor=150 psf

ards—1945)

RECORD

SMALL THEATER ACOUSTICS

N treating a small 400-seat theater acoustically, we must consider four fundamental properties of the structure:

- 1. The relative proportion of length, width and ceiling height.
- 2. The reverberation time or the time required for sound to die away.
- 3. The elimination of standing waves and interference patterns.
- 4. The tonal characteristics of the

Each of these four considerations has been taken into account in the auditorium designs shown on page 101.

In the second plan, intended for a long narrow lot, it was found advisable to provide for the proper number of seats by an overlapping design making use of a balcony in reducing the total length of the auditorium. This has the good effect of bringing the ratio of length to width close to a value of 2 to 1. This value should never be greatly exceeded. The ceiling is high enough to clear all projection lines (see cross-section on page 102), yet it is low enough to hold the cubicle volume per seat somewhere between 110 and 140.

ACOUSTICAL DIAGRAMS: Though taken from a somewhat larger theater (by architect Ben Schlanger) these illustrate basic methods for the smaller theater as well. In the longitudinal section (below) may be seen the splaying of the ceiling to avoid sections parallel to the floor. Cross-section, seen to the right, shows acoustical offsets in the sidewall. (Projection portholes show in center.) Above is a construction detail for the "stadium" of the theater.

REVERBERATION TIME AND INTERIOR SURFACES


In a house of this size, having upholstered seats with upholstered backs, no additional absorbent materials are needed. The audience, the carpeted aisles, and the effect of the empty seats will provide a sufficient amount of sound absorption to reduce the time required for sound to die away. If more absorbent materials were used, the house would merely sound too "dead."


"Standing waves" and sound interference patterns are caused by opposing parallel surfaces. By placing the walls out of parallel to even a slight degree, the wall may be dispersed so as to be no longer objectionable. This sound dispersion may be arranged for by splaying

in both the vertical and the horizontal plan. Avoid the occurrence of concave surfaces which would tend to collect reflected sound at their focal points.

TONAL CHARACTERISTICS

The tonal response of a house seating 400 may tend to be more brilliant at the higher voice and musical harmonic tones than the response in a larger house. In order to keep the sound pleasant, it may be necessary to modify the sound system by increasing the sound loss from 2 to 6 decibels at 8,000 cycles per second, over and above the 18 decibels indicated in the Recommended Frequency Characteristics published by the Research Council of the Academy of Motion Picture Arts and Sciences for the guidance of theater owners and theater architects.





TICS

horizontal of concave to collect points.

se seating iant at the tonic tones house. In the tonic tones house. In the tonic tones are to the tonic tones of the tonic tone of the tonic tone of the tonic tone of the tonic tone of the tone of t

ADJ BLDO

RECORD

HEATING, VENTILATING & AIR CONDITIONING

IN A 400-SEAT theater the total heat generated by the occupants, when the house is filled to capacity, would be equivalent to the heat emitted by 668 sq. ft. of equivalent direct steam radiation or 1060 sq. ft. of hot water radiation. This total heat is produced by the audience during all seasons of the year with little or no variation (400 btu's per hour per person).

This quantity of heat, in addition to that from other sources, such as lights, fan motors, sun effect, etc., is objectionable during hot Summer weather. Ventilation alone cannot be wholly satisfactory when the outside air is already too warm and humid for comfort. Air conditioning, with provision for cooling and dehumidification, would then be required.

During the Winter season in most of the United States, the internally generated heat and moisture is easily removed by the introduction of sufficient outside air, suitably tempered, if necessary, to produce the desired results. During cold weather the quantity of outside air should be reduced to the minimum needed for odor control. Heating of this amount of outside air will be necessary at times so that its final temperature will be such as to maintain desired conditions. It will thus be observed that heating of a theater is actually often a process of controlled cooling.

BEFORE PATRONS ENTER

Prior to the admission of the first patron and during the time of small occupancy, sufficient heat must be provided to balance the net heat losses that will occur in most areas of the country in the winter time. Conventional methods of heating include the recirculation of a part or all of the air handled by the ventilating system raised to a sufficient temperature above 70° F. or by the use of direct radiation distributed strategically throughout the theater or by both methods simultaneously.

As the number of patrons increase, the need for heating may change to a need for cooling. This shift in requirements can be readily satisfied by the ventilating and heating systems provided means for adjusting the quantity of outside air and heat supplied thereto has been incorporated in the design of the equipment.

BOILERS, STEAM OR HOT WATER

An automatically fired steam or hot water boiler will prove satisfactory for the furnishing of the necessary heat for tempering the ventilation air as well as heat for lobbies, toilets, rest rooms, offices, etc.

The use of a hot water heating system in lieu of a steam system will often prove desirable, because under-floor, gravity returns are not needed for the proper operation of a hot water system. Also it is not necessary to provide a depressed boiler room or pump pit for a hot water system. Hot water systems do not require radiator or blast coil traps; and adequate zoning of the various portions of the theater is easily provided.

ZONING IS NEEDED

Because of the fact that heating will be required in the lobby, rest rooms, lounges, toilets, offices, etc. at the same time that cooling is needed in the auditorium, adequate means for zoning are indicated. The use of forced circulated hot water with individual, thermostatically controlled, motor operated circulators in the returns from each zone will satisfy this requirement with a minimum investment.

The installation of a suitable safety control to prevent the possibility of freezing the outside air heating coils in the event of failure of a part of the mechanical equipment would be necesessary in the use of hot water. It should be pointed out, at this time, that steam systems, also, are vulnerable to damage from freezing, under certain conditions, and safety controls should be included in their design.

The projection booth and toilets must be ventilated by sufficient quantities of outside air, usually dictated by local codes or well established by general practice. Re-wind rooms, generator rooms, in fact, all interior occupied rooms, require some form of ventilation. (See projection room diagrams, page 115.)

THE QUESTION OF PANEL HEATING

Consideration has been given to the use of radiant or panel heating in theaters. The ever increasing interest in panel heating by the building industry and prospective building owners raises the question whether this form of heating may soon displace all other forms of heating systems in use today where a high degree of comfort is desired.

The more common forms of panel heating at present are constructed of grids or sinuous pipe coils buried in the concrete floors, in plaster ceilings or walls as required to provide sufficient heating areas. Hot water is circulated through these coils at relatively low

temperatures at varying degrees to conform to the weather conditions. Wrought iron, copper and steel pipe coils are used, depending upon the several governing factors entering into the design requirements.

The ability of a floor type radiant panel to change its heat output rate as rapidly as necessary in the auditorium of a theater is questionable.

Because the need for heating is greatest when a theater is empty and probably non-existent when filled to capacity, it would appear that the added human comfort attributed to the use of radiant heating cannot be realized in this application. Careful analysis of all the factors affecting the design of the heating system should be made before deciding to install panel heating in the auditorium of a theater. The use of radiant heating in lobbies, toilets, lounges, rest rooms, etc. would probably be quite satisfactory and desirable.

ADIABATIC WASHERS

In some portions of the United States, where the Summer relative humidities are always low, adequate air conditioning may be realized, at a low cost, by the use of an adiabatic washer. The term 'adiabatic" is descriptive of a process in which no heat is added to or removed from the medium being considered. In this system, outside air is caused to pass through a suitable spray type or capillary type washer in which the spray water is caused to recirculate through the spray nozzles. In passing through the water sprays, the air, initially at a high dry bulb temperature and low relative humidity, increases its moisture content by the evaporation of a part of the spray water. The heat absorbed by this evaporation is effective in lowering the dry bulb temperature of the air to a point close to its initial wet bulb temperature. This air can be used for air conditioning quite effectively where high dry bulb temperatures and low relative humidities are encountered. Its use is prohibitive, however, where high humidities prevail.

The possibility of digging a well and then finding insufficient water or water at too high a temperature offers a deterrent to the use of this type of system.

Among mechanical systems, the one common to the small theater consists of a reciprocating type compressor using freon-12 as the refrigerant and city water or an evaporative condenser for condensing purposes.

Direct expansion or water chilled cooling coils, depending upon the requirements of local codes, are used to cool and dehumidify the air.

THEATER LIGHTING

ALTHOUGH motion pictures are supposed to be seen "in the dark," auditorium lighting is important, involving

- a. comfortable vision
- b. safe movement
- c. pleasant atmosphere.

During operation the main light is of course on the screen itself. The standard of screen brightness is set at 20 foot lamberts maximum to 5 foot lamberts minimum, depending upon the viewing angle. Since patrons do not look at a blank white screen, actual brightnesses are lower: an average of approximately 3 to 4 foot lamberts when black-and-white pictures are shown, and not over half of that for technicolor. Lighting levels in the remainder of the room must be carefully subdued to avoid interference with this relatively low absolute brightness.

In the most economical of arrangements, spilled light from the screen is depended upon for general illumination during the show. If sidewalls are lined with a material such as corrugated asbestos cement, the part of the light which strikes the wall is reflected chiefly in a lateral direction. It therefore illumines the seated patrons from the side, making them visible to newcomers without throwing light in their faces or fogging the screen.

FULLY DEVELOPED LIGHTING technique for a somewhat larger theater, by C. M. Cutler of Nela Park Engineering Division, shows maximum use of auxiliary lighting. A, illumination on forward sidewalls; B, floods on ceiling, also additional light on sidewall; C, wainscot aisle lights; D, exit lights; E, possible germicidal lights for air irradiation (these shine diagonally across ceiling); F, G, backlighting on the surround of the screen, with objective of softening the strain-creating contrast between the picture and the neighboring dark; H, catwalk for lighting maintenance. Courtesy, The Magazine of Light

Aisle lights attached to the end seat in every fourth or fifth row should produce a brightness of perhaps 2/10 foot lambert on the aisle carpet, the incident light being 3 or less footcandles. Exit lights according to code. For general lighting of the auditorium outside of projection line, reliance is now generally put on cove or offset lighting of incandescent, fluorescent or cold-cathode type, with provision for the occasional introduction of a spot. The architect should not forget the problem of access (by catwalk or otherwise) for cleaning and relamping.

As the audience enters the theater, or leaves again after the show, there is a problem of gradual adjustment of the eye over a very wide range of brightness values. In this process the light under the entrance canopy will play a small part in daytime when, regardless of artificial illumination, it will represent a lessening of brightness in contrast with the usually brilliant street.


At night, however, depending on the surroundings, there will be a tendency to make this entrance light as brilliant as possible (closely spaced lines of cold-cathode light are a favorite expedient) and the progression from the foyer into the lobby must be rapidly downward. There are no "visual tasks" of any exacting kind along the way, so the general

light distribution is all that counts, and very simple deeply recessed bowl reflectors in the ceiling will do most of the necessary work. A random pattern may be used, throwing emphasis wherever it is desired as a matter of showmanship. In the lobby and lounge the general illumination level need not be above 5 footcandles.

In washrooms and rest rooms, the illumination level should be somewhat higher (10 footcandles recommended) to encourage cleanly use of the facilities. At mirrors, 20 fc.

The subject of "black light" or ultraviolet illumination that is invisible until reflected by fluorescent finishes is not treated here, for the reason that we are dealing with an economical theater type achieved with essentials. Care must be taken to shield such sources completely from the eye; colors are a special range.

In lighting the theater as in all other aspects of theater design, the successful architect does well to recall that his best art will be art which conceals itself. The show on the screen is what the audience chiefly comes to see; this show costs the owner half of his gross income to buy; he is selling motion pictures not statuary or fountains; the best theater is the one from which the audience will go thinking the picture was good!




TING

ounts, and bowl renost of the attern may cherever it wmanship, general ile above 5

ooms, the somewhat nended) to facilities.

" or ultraisible until
hes is not
nat we are
eater type
e must be
completea special

all other successful at his best itself. The audience how costs income to tures not theater is ace will go



RECORD

ACOUSTICS OF MODERN AUDITORIUMS

by Floyd Rowe Watson

Practically perfect conditions for speaking are realized when two people are conversing outdoors at a distance of about three feet. The sound is loud enough and, except for indistinct speaking, there is no distortion. If the distance between these people is increased, the conditions are not so perfect. The speaker must raise his voice and any nearby sounds begin to disturb the listening.

Requirements for music are not so exacting. Music is usually louder than speech so that it can be heard at greater distances, and there is also little question about intelligibility.

These ideal conditions are found to some extent in the Greek open-air theater. In such theaters, the speaker is aided by the reflections from the walls near him which allow him to "hear himself" and which amplify his voice by reflecting considerable sound to the audience. The listeners have the advantage of outdoor acoustics, which are generally regarded as good, provided the theater is in a quiet location.

It is a far cry from the Greek theater to the present-day auditorium, but the ancient structure has features that suggest acoustic improvements for the modern building. For example, the inadequate reflecting walls of the Greek theater might be amplified; but instead, the performer today is lost in a rather enormous stage house built primarily to accommodate voluminous scenery and the machinery for handling it. Provision is thus made for scenic and color effects, but apparently little consideration has been given to acoustics. It leads one to inquire about the real purpose of an auditorium.

Furthermore, the outdoor conditions of the Greek theater are not improved, for the surfaces needed to enclose the modern auditorium act as reflectors of sound and thus introduce possibilities for most of the acoustic defects—reverberation, echoes, resonance, interference and focusing. While the loudness is built up somewhat by reflected sound, the amount is small compared with the loudness of the direct sound; and any advantage is largely overshadowed by the defects of reflection.




Fig. 1: The ancient open-air theater (this is the Roman theater at Ostia) often had excellent acoustics. Reflections from wall amplify voices, permit a speaker to "hear himself"




Fig. 2: Perspective of a proposed stage shell. Sides and ceiling are constructed in panels, slightly convex to diverge sound and produce a more uniform distribution on the stage

ARCHITECTURAL ENGINEERING

TECHNICAL NEWS AND RESEARCH

How to provide good acoustics

How then can good acoustics be provided? There are two requirements, equally important:

1. to adjust the stage for generating sound as perfectly as possible; and,

2. to design the auditorium for comfortable and satisfactory listening.

These two objectives present separate problems, which will be discussed presently. Complaints have been voiced that an auditorium properly adjusted for listening is too dead for music. The correct complaint, in the opinion of the writer, is that the stage arrangements do not provide enough reverberation. The ideal is to generate perfect sound effects on the stage that pass out into the auditorium for satisfactory listening.

Generation of sound

Performers should have reflecting surfaces near them by which they can hear themselves, and thus allow them to adjust speaking and music until it sounds best to them. Without such reenforcement, performers complain that their voices are "lost" and that they can only guess at what they are producing. The reflectors should be reasonably close to the performers, less than 28 feet, according to Petzold*, if intelligibility of speech is to be obtained, and less than 24 feet for music. These reflecting surfaces should not be arranged in a box shape, because parallel walls tend to produce annoving resonances. Fig. 2 shows the perspective of a proposed stage shell. The sides and ceiling are constructed in panels, preferably slightly

convex to diverge sound and produce a more uniform distribution on the stage than plane panels. The paneled sections decrease in size toward the rear. To accommodate different sizes of performances, the sides could be made of portable sections. The ceiling could be provided by canvas hangings in folds as shown in Fig. 3. When not in use, the canvas could be pulled up out of sight.



Fig. 4: A permanent panorama on canvas could form the rear reflecting wall, with side walls and ceiling to form a stage

Another possibility is to use a permanent panorama as the rear reflecting wall, but its curvature and inclination should be adjusted to avoid disturbing focusing effects. Side walls and a ceiling should be added to make a stage room. A cloth panorama could also be considered to serve as the rear and sides of a room, but it should not be hung in the usual concave curve if focusing of sound is to be avoided. It could be arranged as shown in Fig. 4. Canvas is preferred to velour for such a curtain because it is a better reflector and not so sound absorbent.

While it is desirable to provide a reverberant stage room for performers, the stage house space should be deadened to reduce stage noise by lining the stage house walls with cinder concrete tile, and treating the ceiling with a fireproof absorbing material, such as an efficient acoustic plaster. The cinder concrete is sound-absorbent, fireproof and paintable.

The acoustic problems of stages have been investigated by Burris-Meyer.† In one experiment, a performer talking into a microphone had his words directed back to him by a small loud speaker connected to the microphone. The performer found this "reflected" sound very helpful.

Hearing of sound

Three objectives are considered in getting satisfactory hearing conditions in an auditorium:

- 1. adequate absorption of sound,
- 2. reflecting surfaces designed to reduce echoes and focusing,
 - 3. sufficient loudness.

Absorption of sound is accomplished by using upholstered seats, carpets, and acoustical materials applied to the walls and ceiling. The audience, because of the clothing worn, furnishes much absorption, but it is an uncertain factor so that the amount of absorption supplied for the empty room should be sufficient to make the auditorium largely independent of the number of auditors. Texts on acoustics of buildings give numerous examples of such adjustments.;

Reflecting surfaces should be studied geometrically in the design stage of an

Fig. 3: Stage room made of portable side panels and canvas ceiling, with convex surfaces to diverge and distribute sound




Fig. 5: When reflected sounds become stronger than the direct sound from the speaker, "dead spots" appear in auditorium. Short rays don't matter; longer ones blur sounds

^{*}Raum Akustik: See Watson, Acoustics of Building, third edition, page 92.

†Dramatic Use of Controlled Sound. Jour. Acous. Soc. Amer., 7, 74, 1935. Also, Science News Letter, May 17, 1941.

‡Knudsen, Architectural Acoustics, P. E. Sabine, Acoustics and Architecture Watson, Acoustics of Buildings.

CANVAS CEILING STAGE FLOOR SECTION PORTABLE SIDE PANELS PLAN

he stage tile, and fireproof efficient necrete is aintable. ges have eyer.† In king into directed speaker The perind very

lered in uditions

und, d to re-

lished by ets, and the walls cause of nuch abfactor so supplied sufficient ely indeauditors, ngs give stments.; e studied ge of an

luilding, third Soc. Amer., 7, 41 Acoustics and

40 FT.

speaker, lur sounds

RECORD




Fig. 6. The loud speaker acts as an acoustical headlight in piercing the fog of reverberant sound. Loud speakers would be arranged to send direct sound to all not near stage

auditorium, and arranged in shape and position to reduce possibilities of distortion of sound distribution. See illustration.

Sufficient loudness. The loudness of a sound obviously depends on the strength of the source and on the size of the room. Music usually has enough volume to be heard easily in most auditoriums, and band music can be too loud unless some of the more powerful instruments are subdued. Chamber music is generally supposed to sound best in rooms of rather small volume, and this would be true for the weaker passages of compositions. It seems likely, however, that special stage reflectors would allow chamber music to be given in larger rooms.

Speech differs from music in two respects - it is generally weaker than music and it must be intelligible to be understood. Speech must not be distorted by the room acoustics. Amplification usually is desirable for speaking, particularly since many listeners are hard-of-hearing. By means of loud speaker amplification, it is possible to use large auditoriums for all types of sound, weak or not, but the services of an intelligent expert are needed in the selection and adjustment of the highfidelity apparatus required. In very large rooms, the question of vision becomes more important than the sound especially for auditors in the rear seats.

"Dead spots" in auditoriums

Fig. 5 shows typical rays of sound proceeding from a speaker S to an auditor A. Ray 1 travels the short distance from S to A and its sound is loud enough and intelligible. The same is true of rays 2 and 3 which have not traveled far and which reenforce ray 1 acceptably. But rays 4 and 5 have traveled 56 feet

more than ray 1 and they tend to blur the speech somewhat, according to Petzold's experiments. For auditors further from the speaker, the hearing gets worse. The direct sound is weaker and the competition of the reflected sounds is greater. so that dead spots appear, which means that the intelligibility of the direct sound is largely lost. This conclusion was tested experimentally. The auditorium selected for test was empty and quiet; it had an acoustical ceiling and a padded carpet floor, but the side walls were of painted plaster and highly reflective. Speech became blurred at a position, rather sharply defined, about 26 feet from the speaker. In an auditorium with an audience and attendant general hum of noise, the blurring would doubtless be more marked. At the blurring point and beyond, a loud speaker would increase the direct sound and thus allow auditors to understand speech in spite of any disturbing reflected sound. An obvious im-




Fig. 7: A dome ceiling focuses sound, makes it louder than direct stage sound

provement would be to deaden the side walls, also the rear wall to "kill" the reflection of the direct loud speaker sound. Figuratively, the loud speaker may be regarded as an "acoustical headlight" which pierces the "fog" of reverberant sound, as shown in Fig. 6.

Curved walls

Concave surfaces present an important acoustical problem, since they always concentrate sound, sometimes creating defects so serious as to make an auditorium unusable. Plane surfaces are safer, but even in this case some modification is desired by use of panels of acoustical material or other devices to break up the reflected sound. Fig 7 shows how a concave wall concentrates sound compared with a plane wall. Concave walls can be changed by convex




Fig. 8: Sound waves are concentrated by concave surfaces. But the same curved wall can be of alternate convex panels and flat panels of sound absorbing material

ARCHITECTURAL ENGINEERING

TECHNICAL NEWS AND RESEARCH

panels, by zigzag panels, by deeply recessed niches or false windows, etc. Fig. 8 gives a graphical presentation to show the diverging effect of a convex panel to overcome the focusing of the concave surface. Alternating convex panels with panels of absorbing material produces an arrangement that simultaneously scatters and absorbs sound. An arrangement of this kind was used in the Pentagon Building auditorium, Fig. 9.

Plane walls

Generally, large surface areas should be broken so that the reflected sound will be scattered and thus aid in getting more uniform distribution in a room. Acoustical material in decorative panels modifies the reflected sound and produces more absorption than if installed in a continuous area. Convex panels also serve beneficially in diverging the reflections. An unusual arrangement of convex surfaces is shown in Fig. 10, which pictures a small room used for listening experiments at RCA. For auditoriums, the convex panels may have a bulge at the center equal to about onetenth of the panel span. In rooms with high ceilings, particularly churches, the side walls should be broken in some manner to minimize horizontally reflected sounds. Paneling is helpful, but architectural modifications, such as side balconies, recessed windows, etc., give more pronounced results. As a general rule, it should be remembered that

"direct sound makes for clearness, reflected sound produces confusion."

Purdue University Music Hall

Figures 11 and 12 give the front and rear views of the Purdue University Music Hall auditorium. It is a large hall, seating 6,208 people. The sound absorption is furnished by upholstered seats, by a large area of carpeting and by a generous application of acoustical material on the rear walls and on the rear parts of the ceiling and side walls, with some paneling effects toward the stage. Reflection of sound from the curved rear wall was eliminated by constructing the surface in rectangular sections, backed





Fig. 10: An RCA listening studio: good sound distribution with convex panels






Fig. 9: The arrangement shown in Fig. 8 works well in the Pentagon Building



Fig. 11 and 12: Two views of Purdue University Music Hall, Walter Scholer, architect. Reflections broken by balconies, paneled rear wall surfaces, and sound-absorbing materials

by efficient absorbing material. The zigzag side walls, following generally the gentle curves narrowing the auditorium at the stage, were made up of short sections set at different angles, thus obviating the focusing effect of the curve.

A permanent band shell is located at the back of the stage, so that a band can participate in programs given on the stage. By means of a curtain, the shell can be cut off for band practice.

The basement of the building accommodates a number of rooms that required acoustic planning - a practice band shell, broadcasting studios with adjacent directive rooms, various offices and conference rooms. These rooms are constructed to be entirely soundproof, and the walls and ceiling literally float. There was some question whether or not the loud music would disturb meetings being held in the auditorium directly above these music rooms, so that a special insulation was constructed, as shown in Fig. 13. The building has been in use for six years, and the architect, Mr. Scholer, writes: "The acoustics have proved perfect in every respect, and strange as it may seem I have never heard one complaint either by a listener or performer."

good

panels

aterials

CORD

Indiana University Auditoriums

The University of Indiana Hall of Music contains two auditoriums—a large one seating 4,000, the adjoining theater 400, and the stage space connecting the two halls 600, and the foyer linked with the stage by a public address system 500, making the total seating capacity 5,500. The sound absorption is




Fig. 13: A band practice room isolated from auditorium by double-hung ceiling

supplied by upholstered seats, carpets and absorbing material on the walls and ceiling. The shape of the ceiling and side walls is determined by a series of elliptical surfaces diminishing in funnel fashion as they approach the stage to create the maximum in intimacy between the audience and the performers. The slope of the panels is such as to reflect sound efficiently to the audience. Rear seats are preferred by some auditors because of the good hearing conditions there. It was necessary to apply heavy padding



Fig. 15: Indiana University Theater. Walls funnel in toward the stage, walls and ceiling being paneled with sound-absorbing material and broken surfaces to control sound

on the ceiling panel over the orchestra pit to minimize some of the louder instrumental sounds, the reflections being shown in Fig. 14.

Arrangement for smaller audiences in the larger auditorium is made possible by means of a large acoustical curtain of heavy velour which is mechanically controlled and can be drawn across the auditorium at the front cross aisle, extending from ceiling to floor, thereby providing a seating capacity for 1,500 people. The curved side walls are broken by deeply recessed blank window spaces, backed by efficient absorbing material behind the grill work. One of the unique features of the building is a stage used by both auditoriums, but equipped with a heavy soundproof door that can be lifted for the transfer of scenery, and lowered in place when the auditoriums are being used simultaneously. Fig. 15 pictures the small theater auditorium which was adjusted acoustically by the methods already described.

Conclusion

It is obviously impossible in a short article to compress material that otherwise would fill a book. However, for the information of architects who plan auditoriums of either usual or unique design, attention has been called to some of the important things that should be considered in getting good acoustics, also to the objectionable features that should be avoided. The following list gives some important suggestions:

1. Make geometrical study of the interior surfaces of the room. Change the design or shape of those walls that will produce focusing of sound.

 Modify large areas of walls or ceiling by panels of absorbing material, by convex panels, by grillwork backed by absorbing material, by balconies or other architectural features.

3. Provide enough sound absorption in auditorium in accordance with the usual rules, and install the greater part of it on surfaces remote from the stage.




Fig. 14: Loud instrument sounds, reflected as shown, softened by heavy padding


Upholstered seats are an important element in absorption.

4. Provide reflectors on the stage near the performers so that they can hear themselves. If possible, make the reflectors into a stage room with some reverberation. Quiet the stage noise outside this stage room by lining the stagehouse with absorbing material.

Provide a high-fidelity public address system.

TECHNICAL NEWS AND RESEARCH

PRODUCTS for Better Building



Trip-key equipped door saddle designed to seal out drafts, water automatically

DRAFT-PROOF SADDLE

To prevent water and drafts from entering, the pivoted center section of the Weather-Tite door saddle rises as the door is closed, and seals the space under the door. This action is accomplished automatically by a trip-key attached to the door. Saddle and door insert are made of high-grade aluminum alloy for strength and durability. There are no springs, cams or felts to require replacing. By use of this device considerable savings in heating and air conditioning costs are said to be effected. Standard lengths of 30, 32 and 36 in. are furnished to fit all doors. Columbia Industries, 19th Ave. & 36th St., Long Island City 3, N. Y.

COATED SHEATHING

The asphalted-gypsum core of the new U.S.G. sheathing is covered on both faces by a special water-resistant "Tri-pleseal" treatment. This process is stated to weatherproof the material so that it remains undamaged when drenched by the rain while piled on the job or nailed to the building framework. It has the fireproof qualities of all gypsum building products, as well as strength and stability. Tongue-andgrooved for wind-tight fit and rigidity, the sheathing eliminates the need for building paper. As the sheathing units may be readily scored and broken to size, and only four nails per stud are required for attachment, sheathing may be quickly accomplished. U. S. Gypsum Co., Chicago 6, Ill.

HEATING Steel Gas Furnace

A new gas-fired domestic furnace, the Bryant steel furnace, has almost completely eliminated flat surfaces with the purpose of overcoming rattling and noise. Combustion chamber and heat exchanger have been arranged in updraft layout to prevent corrosion due to entrapment of condensate. The burner unit is regtan-

gular to concentrate heat transfer without hot spots. Available for gravity or forced-air systems, the furnaces are rated 70, 90, 120 and 140,000 Btu. The Bryant Heater Co., Cleveland, Ohio.

Vacuum-Draft Furnace

A new vacuum-draft oil-burning furnace eliminates the need for the standard chimney to create a draft. The Norge-Heat "chimneyless" furnace also filters and humidifies the heated air. It is designed to create its own draft with a suction fan which pulls air through the combustion chamber, an exhaust vent being substituted for the chimney. The furnace is being made available in three models, the largest having a bonnet output of 120,000 Btu. Norge-Heat Division, Borg-Warner Corp., Muskegon, Mich.

Packaged Heating Unit

New combustion principles and materials have been combined to eliminate the conventional boiler and hot water storage tank in the Whirl-O-Magic packaged heating unit. Steam or hotwater heat, and domestic hot water are reported to be produced instantaneously at high over-all efficiencies and at economical operating cost. Adaptable to either steam or hot-water heat, the unit is supplied with all necessary parts and controls, 3-pass horizontal high pressure steam unit, flash boiler and hot-water coils. The unit is 36 in. high, 42 in. long and 22 in. wide. Persiro Mfg. Corp., 38 Keer Ave., Newark 8, N. J.

Electric Wall Heater

To control the movement of warm air downward for more effective distribu-



A silently-operating gas-fired steel furnace

tion, a directional grille front has been added to the *Thermador* electric-fan-type wall heater. Behind the heating element the unit contains a turbine type 16-blade fan driven by a 4-pole induction motor. For the circulation of air in summer, the fan may be used without the heating element. Models are made to fit easily between studs. Heaters are available with either manual or thermostatic control in 2, 3 or 4 KW models. Thermador Electrical Mfg. Co., 5119 District Blvd., Los Angeles 22, Calif.

pe la

B

ANTI-STATIC GROUND

A new safety device, the Hospital Electro-Static Grounding Intercoupler. is being produced to provide a dependable means for grounding electricity in operating rooms. An inset 8 in. square brass box with a hinged cover has six sockets, which are connected through resistors to a water pipe ground. To lead off static charges during operations, bead chains covered with transparent plastic are plugged into the sockets, and are attached by various connections to equipment and personnel. A rack is supplied on which to hang the chain assemblies. Cannon Electric Development Co., 3209 Humboldt St., Los Angeles, Calif.

CALL-BACK INTERCOM

A combined call-back and sound reproducer unit, the Executone C-18, is designed especially for use with high noise level coverage industrial communication systems. In combination intercom and amplified voice-paging systems, it reproduces the paging call and permits the person called to reply and converse directly with the person originating the call. Anyone at an intercom master station can originate a paging call or have regular two-way communication. Call-back may be accomplished from any call-back station, other units being automatically silenced during conversation. At other master stations a busy signal light indicates that the system is busy, thus preventing interruption. Executone, Inc., 415 Lexington Ave., New York 17, N. Y.

STEEL CROSS-ERIDGE

The hard steel shaft of the self-adjusting X-Bridge is made to provide bracing of floor joists quickly and easily, and flexibility to accommodate changes in beam dimensions due to swelling and shrinking. The bridging consists of a light U-shaped member, with two points at the head joined by a curved section to build up progressive resistance as they penetrate into the beam. The heel has a curved cutting edge. To set the bridge, a head point is jabbed into the wood near the top of the joist, the heel is brought up about 1 in. above the bottom of the adjoining joist, and pushed across into

is been in-type lement 6-blade motor. ier, the heating t easily vailable tic conrmador Blvd..

lospital coupler, lependicity in square has six hrough To lead rations. sparent ets, and tions to is supassement Co., s, Calif.

und re-C-18, is th high mmunin interng syscall and ply and n origintercom paging mmuniaplished during stations hat the g interexington

he selfprovide d easily, changes ling and of a light oints at ection to as they eel has a bridge, a brought m of the ross into

ECORD

position. The companion piece is similarly set. Installation can be done by unskilled labor. It is stated that natural wood shrinkages and floor vibrations imbed this bridging, and set it more firmly. Geo. E. Eichenlaub, 2519 Broadway, Beaumont, Texas.

GAS WATER HEATER

To effect rapid and efficient heat transfer, the heat exchanger of the Smithway-Burkay instantaneous water heater exposes 30 sq. ft. of heat transfer area to a total water content of only four pints. This unit is designed for use where hot water requirements are complicated by abnormal demands, intermittent peak loads, sterilizing heat, etc. Thermostatic control is said to hold water outlet temperatures within two degrees of the



Dual-heat instantaneous water heater

thermostatic setting. When installed with a tank, hot water up to 140° may be supplied from the tank, while water may be recirculated through the heater to supply water at 180° for sterilizing purposes. A. O. Smith Corp., Milwaukee, Wis.

PLASTIC FLOOR TILE

Made of a material that has been proved in many other applications, Koroseal flooring embodies superior flame resistance and resistance to wear and weather. The product is made in square, flexible tile form unsupported by fabric. It is expected that the new flooring will be available in midsummer for installation where long wear and minimum maintenance are sought. A wide range of solid colors will be offered. Sloane-Blabon Corp., Trenton, N. J.

PLASTIC MESH GLAZING

In the new plastic-mesh Vimlite, developed to overcome the difficulty of obtaining the steel wire used as reinforcement in the original product, 20 per cent better light transmission has been achieved. The new product is credited

by its manufacturers with having all of the virtues of its predecessor with regard to strength, lightness and being virtually weatherproof. Ultra-violet transmission is higher, and it has a more pleasing appearance. It can be cut with an ordinary knife or household scissors, and, because of a tendency to contract slightly, it has the ability to be selffitting. Celanese Plastics Corp., 180 Madison Ave., New York 16, N. Y.

FLOOR MACHINE

A new machine developed for floor maintenance, the *Tennant all-purpose* floor machine, cleans, sands, waxes and polishes. Of rugged construction, it may be used on wood, asphalt, cork, linoleum and concrete, with either 8 in. or 16 in. accessories. A high torque motor operates the revolving drum and vacuum fan. The drum has a two-step pulley for speeds of 800 and 1400 RPM. Accessories include steel wool roll, steel wire brush, sanding drum, tampico or palmetto brush, and bar wax cartridge. G. H. Tennant Co., 2530 North Second St., Minneapolis 11, Minn.

WATER TREATING UNIT

Rust and lime deposits in water supply are prevented by the *Micromet Feeder*, which feeds a specially prepared form of the phosphate compound, Calgon, into the water system at a uniform rate. Valves permit recharging without shutting off main supply. Effective on the incoming line of a hot water tank to prevent clogging of the heating coils, it can also be used with air-conditioning units, mechanical washers, or to protect the entire system. Sizes are available for domestic, commercial or industrial application. No-No Specialty Co., Quincy Ave, at East 69th St., Cleveland 4, Ohio.

GREASE INTERCEPTOR

Hydraulic filtering plus gravity differential separation accomplished by the new HydraFilter grease interceptor offers an efficient method of preventing greaseclogged drainage systems. Accumulated grease rises to a storage compartment away from the main current, and is free from solids, so that it is commercially salvageable. Heavy solids such as broken glass and china, bone fragments, etc., are retained in the trap. Special hand fasteners eliminate the use of tools for attaching the cover, which is of lightweight aluminum for easier handling during cleaning operations. Sizes are made for homes, restaurants, hotels, food processing and other industrial plants whose waste lines contain grease, fats or oils. Wade Mfg. Co., Elgin, Ill.

SWING SPOUT FAUCET

Fabricated from stampings and screw machine parts rather than castings, the Commodore ledge type swing spout



Smoothline wide-swing swivel faucet

kitchen faucet has been designed for maximum ease of cleaning, working clearance and radius of coverage. The lines are simple and modern. This fixture is equipped with the *Autospray* for rinsing, which is operated with one hand by applying slight pressure on the lever of the spray head. When pressure is relaxed, water-flow is automatically diverted to the spout. It is stated that the nozzle construction is such that it cannot clog, and always gives the same full spray. General Tire & Rubber Co. of Calif., 608 South Fair Oaks Ave., Pasadena 2, Calif.



Space-saving sanitary duo-washfountain

DOUBLE WASHFOUNTAIN

The space-saving and sanitary features of the larger industrial models have been incorporated in the new Bradley Duo-Washfountain for general use in small plants, offices, schools, etc. This fixture has a spray-head which replaces four faucets, and enables two persons to be served at the same time. Besides the economy of space and the reduced number of piping connections, the fact that the spray is foot-treadle operated, and the bowl flushes itself automatically, offers sanitary advantages, since it is unnecessary for the hands to touch any part of the fixture. The bowl is furnished either in stainless steel or white enamel iron, with the pedestal panel which encloses the connections and mixer finished in the same material. Bradley Washfountain Co., North 22nd and West Michigan Sts., Milwaukee 1, Wis. (Continued on page 134) TECHNICAL NEWS AND RESEARCH

MANUFACTURERS' LITERATURE

CONVEYORS

Utilize the "Air Rights" of Your Ceilings. Overhead chain conveyor systems, their design and application to specific uses in various types of plant operations are discussed in this booklet. Typical layouts of assembly line installations are shown. The adaptability of the systems to old plant conversions is also given consideration. 20 pp., illus. Lamson Corp., Syracuse 1, N. Y.*

ELECTRICAL WIRING

Four Degrees of Home Electrification. Basic major equipment for the
home is listed in four categories ranging
from thrift to luxury, to conform electrical services with the means of the
individual homeowner. For each degree
of electrical living the circuit requirements and arrangement are indicated.
Minimum wiring and outlet requirements. Suggested wiring specifications.
12 pp., illus. Westinghouse Electric
Corp., Better Homes Dept., Pittsburgh
30, Pa.*

FACING SLABS

Mo-Sai Masonry Facing Slabs. Folder describes characteristics of precast masonry for exterior facing. Construction details for walls, spandrels and parapets. Methods of using slabs as exterior forms in poured concrete construction. Typical architectural specifications. Photographs of erection and completed installation in a variety of buildings. 8 pp., illus. The Dextone Co., P. O. Box 606, New Haven, Conn.*

FLOORING

Emeri-Crete, The Modern Concrete Industrial Flooring. Folder discusses use of emery aggregate cement flooring to provide long-wearing, non-slip surface required in industrial buildings. Shows many heavy-duty installations in plants where operations require extremely resistant flooring. 8 pp., illus. Walter Maguire Co., Inc., 330 West 42nd St., New York 18, N. Y.

HEATING AND HOT WATER

I-B-R Installation Guide—One Pipe Steam Heating Systems. Handbook for calculation and design of the domestic heating plant. Typical calculation sheet. Tables of heat loss factors for various materials, radiation and conversion tables. Recommended installation practice includes layouts and line drawings of details. Suggested control arrangements for systems using the various conventional types of firing. 16 pp.,

*Other product information in Sweet's File, 1946.

illus. The Institute of Boiler & Radiator Manufacturers, 60 East 42nd St., New York 17, N. Y. 25 cents.

Supertherm Systems. Details of an industrial process heating system which circulates superheated water under pressure are discussed in an illustrated folder. Analysis of advantages of the use of this closed type system as applied to a variety of processing industries. Tables give heat losses of steam due to flash-off, and comparative heat content of water and steam. 12 pp., illus. Blaw-Knox Co., Power Piping Div., Pittsburgh, Pa.*

Tankless Taco Water Heater for Residential Installations. Data sheet presents dimensions, capacities and installation details for four standard size residential water heaters. 2 pp., illus. Taco Heaters, Inc., 342 Madison Ave., New York 17, N. Y.*

KITCHENS

How To Make Your Kitchen Dream Come True. A complete line of metal kitchen sinks and cabinets is illustrated, and dimensions given. Various kitchen layouts are shown. Suggestions are offered for modernization schemes. 20 pp., illus. Mullins Mfg. Corp., Warren, Ohio.*

LIGHTING

Fluorescent Lamps and Auxiliary Equipments. Catalog lists dimensions, electrical data, lumen output and brightness of standard fluorescent lamps. Details and dimensions for auxiliary equipment are given. Hookup diagrams for various combinations of lamps. 6 pp., illus. General Electric Co., Nela Park, Cleveland 12, Ohio.*

Lighting That Attracts and Pleases. Ideas for the effective lighting of the exterior and interior of the modern restaurant. Construction details of cove, doorway, step and other special lighting features. 12 pp., illus. General Electric Co., Lamp Dept., Nela Park, Cleveland 12, Ohio.*

ORNAMENTAL METALWORK

Beautify and Protect with Metal Mouldings. A wide variety of mouldings and tubing in various metals and finishes is offered for use with composition wall surfacing materials. Detailed information is given regarding moulding dimensions and thicknesses of materials with which each type of moulding is designed to be used. 32 pp., illus. The Loxit Moulding Co., 1217 West Washington Blvd., Chicago 7, Ill.*

Catalog No. 5. Comprehensive catalog of architectural and ornamental metalwork. Metals included are iron, steel, brass, bronze and aluminum in rolled, cast, wrought and extruded forms. Classifications cover treillage, grilles, partitions, rails and balusters, ornaments, saddles, tubing and shapes. Sizes listed. Many full scale details of mouldings and forms. Installation and assembly details. Julius Blum & Co., Inc., 532 West 22nd St., New York 11, N. Y.

PAINT

Paint Progress, Vol. 6, No. 1. Interesting bulletin discusses: (1) effect of zinc oxide on properties of exterior paint; (2) value of color in wall treatments as educational aid; (3) characteristics of resin-oil emulsion paints; (4) improved luminescent paints. 12 pp., illus. The New Jersey Zinc Co., 160 Front St., New York 7, N. Y.

PERSPECTIVE AIDS

True Perspective Drawing Aids. Pamphlet presents information about special perspective scales, and perspective charts of planes and circles in space, designed to aid the draftsman in preparing accurate perspective drawings. 8 pp., illus. Chas. W. Downs & Son Co., Detroit 16, Mich.

REGISTERS AND GRILLES

Waterloo Air Diffusers. Data are given for the selection of grilles of proper capacity for both supply and return openings. A series of grilles, louvers and dampers is illustrated and described. Dimension tables. Installation details. 16 pp., illus. Waterloo Register Co., Waterloo, Iowa.

REPRODUCTIONS

Bruning Black and White Prints. A direct printing process for reproducing drawings and tracings is discussed, with emphasis on the possibility of printing on various weights of paper, and making changes on the finished prints. 4 pp., illus. Charles Bruning Co., Inc., 4754 Montrose Ave., Chicago 41, Ill.

SOLAR HOUSES

An Architectural Lift in Living. The theories and principles of design involved in the solar house. Charts and diagrams show the effects of orientation and solar angles. Table gives percentage of sunshine hours at various locations. Numerous drawings and photographs of interiors and exteriors of sun-seeking houses. 24 pp., illus. Libbey-Owens Ford Glass Co., Toledo, Ohio.*

STRUCTURAL STEEL

Otiscoloy High Tensile Steel. Technical information, suggested applications and other useful data about a (Continued on page 148) catanental
iron,
im in
ruded
illage,
isters,
napes.
iils of
a and
c Co.,
ck 11,

extension wall charmaints; s. 12

Aids. about rspecspace, reparigs. 8 in Co.,

ta are proper return rs and cribed. letails. r Co.,

Prints.
ducing
l, with
rinting
naking
4 pp.,
, 4754

design rts and ntation centage cations. aphs of seeking as Ford

Steel. ed apabout a age 148)

CORD



YOU JUDGE a camera on performance. And the precision-engineered parts inside the camera decide its quality of performance.

In building materials, too, it's what's inside that counts. For example—the long, wiry sugar cane fibres in the core of so many Celotex building and insulating products.

These closely-woven fibres imprison millions of minute air cells which create the ideal insulating qualities of Celotex board.

Examined under a magnifying glass, the serrations on each sugar cane fibre—more like bamboo than any other domestic fibre—look like small interlocking fishhooks. These multiple, matted, interlocking hooks are the reasons for the superior structural strength and durability of Celotex products.

All Celotex cane fibre products are specially processed to make them water and vermin resistant. All are easy to handle, easy to apply, economical to use.

Remember, too—on hundreds of thousands of jobs these Celotex products have proved beyond any doubt that they have the *inside* quality that counts.

Zuick Facts on Celo-Siding A typical Celotex cane-fibre building product

Ideal for most low-cost building. Does 4 jobs in one application: 1. Sheathing 2. Insulation 3. Exterior Finish 4. Structural Strength.

Tongue and Groove joint on long edges of 2'x 8' panels.

Core of genuine Celotex Cane Fibre Board furnishes structural strength and insulation.

All edges and sides sealed against moisture by coating of asphalt.

Extra coating of asphalt on exterior side.


Exterior surface of firmly imbedded mineral granules, providing durable, colorful finish.

Colors: Green or Bufftone.

Sizes: \%" thickness-4' x 8' with square edges. \%" thickness-2' x 8' with T & G joints on long edges. \%" thickness-4' x 8' and 4' x 10' with square edges.



THE CELOTEX CORPORATION . CHICAGO 3, ILLINOIS



t's the fixture that determines the value and quality of a lighting installation—the fluorescent tube produces only light.

Only sturdily built, scientifically designed fixtures can give you all the benefits of modern fluorescent lighting-overall, glareless, abundant light-lasting efficiency and easy maintenance.

The demand for fluorescent fixtures is greater than the present production capacity of qualified manufacturers. Waiting a little longer for better fixtures will pay in the long run.

Day-Brite Lighting, Inc., 5465 Bulwer Ave., St. Louis 7, Me, Nationally distributed through leading electrical supply houses. In Canada: address all inquiries to Amalgamated Electric Corp., Ltd., Toronto 6, Ontario



JUNE 1946

ARCHITECTURAL RECORD

TECHNICAL NEWS AND RESEARCH


THEATER AUDITORIUM FLOOR SLOPES

UNIT of reference in motion picture theater design is projection screen width, W. Distance from screen to first row of seats should be no less than 1 W. Best viewing distance is zone 3 W to 4 W; next in desirability are areas 2½ W to 3 W, and 4 W to 4½ W.

In theater of 22 rows, screen 11 ft. high by 15 ft. wide is good for maximum viewing distance; hence, first row of seats should be about 15 ft. from screen. Recommended row spacing at least 34 in. back to back.


Upward floor slope should start as far back from screen as possible, since slopes greater than 3 in. between rows require risers. In diagrams shown, staggered seating, except in first rows of reverse-pitch schemes, reduces rear floor slope by half, and avoids dangerous variable step heights necessary with aligned seating. When steps are used, if uniform height (fixed by rear rows) is adopted as standard, slope increases, and stadium type scheme results. *Elevated* stadium type is useful to permit space beneath for passage and services.

Drawings show all levels in relation to datum line, lowest point of floor, All pitches and rises noted in inches and decimal parts of an inch.




SINGLE SLOPE AUDITORIUM

On ground sloping 3 ft or more downward toward screen. Without staggered seats, risers required starting tenth row.



DOUBLE SLOPE AUDITORIUM

On level ground, or on ground sloping of less than 3 ft. in any direction. First six rows aligned to allow view of entire screen



DOUBLE SLOPE AUDITORIUM WITH STADIUM

On level ground or on ground sloping less than 3 ft. in any direction. Seats in at least first six rows aligned. Crossover under first few rows of stadium saves seating area. Staggered seating, and minimum clearance in crossover, prevent intermediate steps.

ECORD



fire-safety . . . permanence . . . lasting beauty






N the drafting board, Milcor Metal Lath gives you unlimited freedom to develop structural forms and shapes.

On the job site, Milcor Metal Lath provides maximum rigidity with light weight. The whole wall and ceiling is held together in one fireresistant monolithic slab, free from cracking, warping, and shrinking tendencies.

Although not plentiful easily obtained than substitutes which do not have the fire-safety, permanency, or vermin-resis-




tance of steel . . . and which have never equalled metal lath as a satisfactory plaster base.

Steel-reinforced plaster faithfully expresses your

conception of form and color tone. The entire plastered surface remains at practically the same temperature, thus avoiding condensation and re-

> sultant plaster blemishes such as lath streaks. The plaster stays new-looking longer, a credit to your reputation.

Consult the Milcor catlog in Sweet's. Or write today for the Milcor Manual.



Milcor Specialmesh Metal Lath

MILCOR, STEEL COMPAN

MILWAUKEE 4, WISCONSIN

BALTIMORE 24, MARYLAND KANSAS CITY B. MISSOURI

CHICAGO 9, ILLINOIS LOS ANGELES 23, CALIF.

ROCHESTER 9, NEW YORK



TIME SAVER STANDARDS

ARCHITECTURAL ENGINEERING

TECHNICAL NEWS AND RESEARCH

JUNE 1946

ARCHITECTURAL RECORD




Fig. 1. Front Wall Plan

Fig. 2. Porthole Shutter System

Fig. 3. Floor Plan and Wiring

Fig. 4. Ventilation Plan

and

alled

isfac-

laster

your tone. mains ature, d re-

nishes . The


oking

your


r catite tonual.

ECORD

Fig. 5. Equipment and Room Duct Systems




IF 3-PHASE TUNGAR-TYPE RECTIFIERS OR COPPER OXIDE RECTIFIE STALLED, A RELAY CIRCUIT OF 2° 12 BRC MUST BE RUN DIREC EACH RECTIFIER TO BACH PEDESTAL THIS CIRCUIT NOT SHOWN ARE I




4

CEILING REEL LIGHT DUPLEX CONV. OUTLET 6" ABOVE FLOOR CEILING LIGHT WITH PULL, SWITCH OVER REWIND TABLE 3-WAY SWITCH FOR





TICKET BOOTH LAYOUTS



Service requirements: (1) Public and intercommunicating telephones; (2) Lighting; (3) Heating; (4) Ventilation

CENTRAL BOOTH (attached or freestanding)



"Roberta," the human-comfort meter, is one of the prima donnas of the Trane Laboratories. And she certainly deserves the title. She's so sensitive that she'll record the heat of the sun during a snowstorm. Or react to the air motion created by a wave of the hand. She measures the factors that affect human comfort better than the human body itself and then proceeds to record them accurately and completely.

When Trane engineers in the development of new heating systems wanted to know just what made a person comfortable they had two alternatives. They could take a score of human guinea pigs and subject them to all kinds of heat, wind and sun effects or they could turn to electronics and make a machine that would do the same thing. They did the latter and created "Roberta," the Eupatheometer. "Roberta" is not for sale. She has too many jobs to do in Trane laboratories. Jobs such as testing the effect of cold walls in warm rooms and finding out what's comfortable about radiant heat, convected heat, and conducted heat.

The Eupatheometer is another example of the genius of Trane engineers who carry out a constant program of research in the development and refinement of Trane products. It is this genius that has contributed so much in creating more effective Weather Magic.

More than 200 Trane field engineers in principal cities all over the country cooperate with architects, engineers, and contractors in the application of Trane systems. National advertising is advising customers to secure Trane information from architect, engineer, or contractor.



A POST-WAR TRIUMPH OF TRANE ENGINEERING . THE TRANE CUSTOM-AIR SYSTEM



Another Trane FIRST can now be announced! Trane research engineers have worked for ten years to perfect the new Trane Custom-Air System — the ideal solution to the problem of air conditioning multi-story, multi-room buildings.

Here is a completely modern air conditioning system. This latest result of Trane engineering combines the advantages of a central system with the flexibility of individual units, and affects new savings in space in new or old buildings. The new Trane Custom-Air System automatically provides a new standard of comfort — summer, winter, and between seasons.

This newest example of Trane Weather Magic, like all Trane systems, makes efficient use of many of the complete line of Trane products for heat transfer and air handling. Complete information and technical details on the new Trane Custom-Air System are available only through your Trane field engineer.

TRANE COMPANY
The House of Weather Magic

LA CROSSE . WISCONSIN

MANUFACTURING ENGINEERS OF HEATING AND AIR CONDITIONING EQUIPMENT



Roddiscraft doors in Michigan Maple

A combination of Beauty and Toughness













HARD Michigan Maple faces over RODDISCRAFT cores and crossbanding welded into a solid, waterproof unit, under heat and pressure, by the RODDISCRAFT process, creates a door that will stand up under heavy traffic and harsh treatment.

In contrast to the delicate color and warmth of Michigan Maple, is its ingrained hardness-resistance to chipping and scuffing-which makes it an ideal wood for facing doors used in public buildings.

Roddis offers the pick of Michigan Maple from its 30,000acre northern Michigan tract - selected and cut by Roddis woodsmen - matched and finished by Roddis craftsmen. Specify RODDISCRAFT Doors in Michigan Maple to get long life and lasting beauty. Available in selected white, or unselected for painting. Consult your local millwork and fixture manufacturers - and lumber dealers.



Roddiscraft warehouses

LOUISVILLE 10, KENTUCKY, 1201-5 S. 15th St.

CAMBRIDGE 36, MASS., 229 Vassar St.
CHICAGO 8, ILL., 1440 W. Cermak Rd.
CINCINNATI 2, OHIO, 457 E. Sixth St.
DALLAS, TEXAS, 2615 Latimer St.
KANSAS CITY 8, MISSOURI,
2729 Southwest Bivd.
LOUISVILLE 10, KENTUCKY, DEALERS IN ALL PRINCIPAL CITIES

Consult Your Local Millwork and Fixture Manufacturers — and Lumber Dealers

HIHIM

ECORD

ARCHITECTURAL ENGINEERING

TECHNICAL NEWS AND RESEARCH

(Continued from page 125)

HOME STEAM OVEN

A low pressure steam oven using less than one pound of pressure, the Vendo 4th Zone, is being readied for introduction to the public after two years of research. Both temperature and pressure are controlled automatically by a springless valve. Foods prepared in this gasoperated steam oven are said to be ready to serve much more rapidly than with other methods, and with savings of up to 40 per cent in minerals and vitamins. The unit may also be used for sterilizing and preserving. When field tests are completed, it will be offered for domestic use in a self-contained floor model or built in as part of a standardsize range. The Vendo Co., 1907 Grand Ave., Kansas City 8, Mo.

LIQUID PAINT BOND

To prepare glossy finished surfaces for covering coats, and for removing wax and grease, Bull Dog Hold Tite is recommended. Wiping with this liquid cleans the surface, and removes gloss of paint, enamel and varnish, to give a firm grip to new coats. Addition to new paint in the ratio of 1/4 pint of the liquid to a gallon of paint, it is claimed, will bind new paint more securely to old finishes. Gillespie Varnish Co., Dey & Howell Sts., Jersey City 6, N. J.

TUBULAR LATCH

In order to give greater strength and service at low cost, the Corbin tubular latch has been redesigned, and more rugged parts adopted. Made for fast and easy installation, it also conforms to the Fir Door Institute specifications for use in premortised doors. When this latch becomes available in the near future. there will be a variety of designs, including a standard set, a closet door set, and a bedroom or bathroom set made with a locking button and emergency key. P. & F. Corbin, New Britain, Conn.

ILLUMINATED PLATES

In addition to the switchplate previously announced, which incorporates a tiny, neon-type safety glow lamp, a LumiNite safety plate for wall-type duplex convenience outlets is being introduced. The plate is molded plastic with a sealed-in glow lamp, said to consume less than two cents worth of current per year. Making it easy and convenient to plug in lamp, and appliance cords in darkened or obscured areas, the plate also is a permanent safety light at night. Associated Projects Co., 80 East Long St., Columbus 15, Ohio.

MATCHED METAL TRIM

Balanced production is being maintained on a series of matching metal trims to assure availability for making complete installations with a single design. The Chromedge group includes designs for wainscot caps, wall panel strips, corner and cove base trims. Sizes are available for linoleum, tile, rubber, wall board and plywood. B. & T. Metals Co., 425 West Town St., Columbus, Ohio.

SAFETY STAIR TREAD

For safety and protection, the Double-Duty Stair Tread covers stair treads and risers with a single rubber mat which wraps around the nosing. Scored to give non-slip grip, the pad protects steps against wear from foot traffic, and risers against kicking and scuffing. The mats are made in 18 in. and 24 in. widths, and will cover a 9 in. tread plus a 7 in. riser. American Mat Corp., 1797 Adams St., Toledo, Ohio.

REMOVABLE SLAT BLIND


For easier cleaning of the Walker Removable Slat Blind, the cord runs through notches at the edge of the slat, (Continued on page 136)

KITCHEN PLAN NO. 36:

successful mass-feeding kitchen plans.

Thirty-sixth of a series of

This kitchen at Montauk Manor, Montauk, Long Island, is designed for sumptuous dining room, night club and room service meals to be served fully a la carte.



KEEP FOR HANDY REFERENCE

COOKING EOUIPMENT USED:

BAKE SHOP: (a) 1 No. 982 BLODGETT GAS-FIRED OVEN

PASTRY SHOP:
(b) 1 No. 963 BLODGETT GAS-FIRED BLODGETT BAKE OVEN

(c) 1 Trunnion kettle (d) 1 Gas-fired confectioner's stove

(d) 1 Gas-fired confectioner's stove
MAIN EITCHEN:
(a) 4 Stock kettles
(f) 1 Vegetable steamer
(g) 1 No. 983 BLODGETT GASFIRED ROAST OVEN
(h) 5 Gas-fired solid top ranges with
two spreader plates
(i) 1 Gas-fired deep fat fryer
(j) 2 Gas-fired ceramic broilers

Designed by: A. Mathesius, of the H. F. Rutley Co., Brooklyn, N. Y.



THE NO. 982 BLODGETT GAS-FIRED BAKE OVEN in the bake shop of this installation provides 8-pan capacity with two heat controls; THE 963 BLODGETT BAKE OVEN in the pastry shop furnishes capacity for 36 10" pies or six bun pans, in three individually controlled sections. THE 953 BLODGETT ROASTING OVEN in the main kitchen bank has capacity for more than 600 lbs. of roasts in its three individually controlled sections. For details and specifications of BLOD-GETT OVENS consult your equipment house or write

The G. S. BLODGETT CO., Inc.

50 Lakeside Avenue

Burlington, Vermont

Reprints of this new series will soon be available to architects on request



his liquid es gloss of to give a on to new the liquid imed, will ly to old ., Dey &

ength and in tubular and more or fast and rms to the ns for use this latch ar future, ns, includor set, and ade with a ency key. Conn.

late previrporates a lamp, a l-type dueing introlastic with o consume urrent per venient to cords in the plate t at night. East Long

eing mainning metal or making single decludes deanel strips, Sizes are abber, wall Metals Co., as, Ohio.

the Doubletreads and mat which red to give tects steps and risers The mats widths, and 7 in. riser. Adams St.,

ND

he Walker cord runs of the slat, on page 136)

RECORD



The Texas Method of Lighting

Schoolrooms gives:

A STARTLING

INCREASE IN EDUCATIONAL GROWTH . .

A Significant Reduction in Classroom Visual Difficulties and Energy Problems!

Your School can do it, too!



It is not difficult to get the remarkable results Texas has in its experimental program for using light in schools.* This consists of proper painting of walls and ceilings with Luminall-the light-reflective paint and proper fenestration and seating arrangements. Here is a challenge to school authorities to find the way for their community to give greatly improved well-being and an amazing increase in educational growth to their school children.

Send today for descriptive literature. Address National Chemical & Mfg. Co., 3610 S. May Street, Chicago 10, Ill.

* Developed in the Mexia Texas Public Schools under the direction of D. B. Harmon and reported in-Illuminating Engineering; Architectural Record, etc.

the light-reflective paint for interiors

ARCHITECTURAL ENGINEERING

TECHNICAL NEWS AND RESEARCH

(Continued from page 134)

instead of through the center, thus permitting the individual slats to be lifted out. The cord is next to the rear tape on one side of the blind, and next to the front tape on the opposite side, equalizing the lifting balance of the blind. In addition to the convenience of the removable slat, other advantages claimed are that the new arrangement permits complete closure of the blind, and that the slats themselves are much stronger by reason of not being pierced in the

center. The blinds are made with wood, steel or aluminum slats. Rupert N. Hoye, 2323 South Michigan Ave., Chicago 16, Ill.

AIRPORT LANDING STEPS


A portable passenger landing step unit has been designed so that it is adjustable for use with any airplane which has an entrance door sill within the range of 86 to 126 in, above the ground. Constructed of light-weight aluminum alloy, the unit is easily moved from ship to ship. It can be folded into an almost horizontal position when not in use. By adjusting the two telescoping sections, the height can be varied between eleven and sixteen steps. There are wider platform steps inserted in both the upper and lower sections for added convenience. Steps have a non-skid metal surface for safety. Positive lock brakes are provided on all truck wheels and casters. Lights installed in the lower sections of the handrails and step guards provide illumination during night operations. The Glenn L. Martin Co., Baltimore 3,

FLOATING TRIANGLES

Neater drawings are produced by the Instrumaster "floating triangles," because integral embossed buttons elevate the lower surface from the drawing paper. Shifting between 45° and 30°-60° triangles is much reduced, as 45° triangles have 30°-60° triangular openings, and vice versa. The application of the elevator buttons accomplishes a triple purpose: to provide a ready fingerlift on all edges; to prevent ink runbacks between triangle and paper; to minimize smudging. They are available in even sizes from 4 in. to 12 in. Instrumaster Industries, Inc., Greenwich, Conn.

CORRECTION

The new air sterilizer shown on page 20 of the March issue of AR may be used in connection with an air conditioning system, but it is not in itself an airconditioning unit, as was indicated. Disinfection of the air is accomplished in the Glycolizer, the unit mentioned, by means of triethylene glycol vapor mixed with a small volume of air in the unit, and released directly into the room. Other equipment produced by the same manufacturer for complete air conditioning employs triethylene glycol vapor for dehumidification as well as sterilizing. Rogers Diesel and Aircraft Corp., 1120 Leggett Ave., New York 59, N. Y.



Vaporizing unit for air disinfection

To Architects, Builders and Officials Interested in Jail & Prison Equipment

THE STEWART IRON WORKS COMPANY, CINCINNATI

Stewart has been designing and building jail and prison equipment since 1886, and numbers among its installations some of the largest penal institutions in this country. One of the most recent is the Criminal Courts Building and City Jail, Borough of Manhat-

Stewart products include Grating and Plate Cells; tan, New York, N. Y. Doors; Lock and Locking Devices; Bunks; Tables; Seats; Iron Stairways, and all modern jail equipment for a federal penitentiary or a village lockup.

Our engineers will be glad to give architects, builders and prison officials the benefit of many years' experience. Without cost or obligation we will submit layouts, estimates and complete information for entirely new construction, remodeling, or the rehabilitation

You are cordially invited to avail yourself of the techof existing equipment. nical facilities offered by the Stewart jail and prison engineers. Address The Stewart Iron Works Co., Inc., 1365 Stewart Block, Cincinnati 1, Ohio.

Designers and Builders of Jail and Prison Equipment Since 1866



rom ship n almost use. By sections, en eleven der platne upper convennetal surrakes are I casters. ctions of provide perations.

timore 3.

ed by the des," beas elevate drawing d 30°-60° 45° triopenings, on of the a triple gerlift on backs beminimize in even trumaster onn.

on page y be used ditioning f an airindicated. mplished tioned, by por mixed the unit, he room. the same ir condicol vapor s sterilizaft Corp., 59, N. Y.




infection

RECORD

Sanymetal "PORCENA"

(Porcelain on Steel)


Toilet Compartments Elevate Toilet Room Environments Into Keeping with Other Environmental Treatments of a Building



Sanymetal Porcena Normandie Type Toilet Compartments impart a moderately streamlined effect to a toilet room environment. Streamlined design wedded to utility fulfills all requirements.


Sanymetal Century Type Ceiling Hung Toilet Compartments are particularly appropriate for schools. They impart dignity, refinement, and cheerfulness to

the toilet room environment.



Sanymetal "Porcena" Toilet Compartments embody the results of over 32 years of specialized skill and experience in making over 70,000 toilet compartment installations. Ask the Sanymetal Representative in your vicinity (see "Partitions" in your phone book for local representative) for further information about planning suitable toilet room environments for modern school, industrial, and institutional types of buildings. Refer to Sanymetal Catalog 19B-5 in Sweet's Architectural File for 1945, or write for file copy of Catalog 84.

THE SANYMETAL PRODUCTS COMPANY, INC.
1689 URBANA ROAD . CLEVELAND 12, OHIO



Sanymetal Catalog 84 illustrates several typical toilet room environments.



Sany metal*

"PORCENA"

(Porcelain on Steel) TOILET COMPARTMENTS

possess the natural structural strength of steel, not one sheet, but two 16-gauge sheets securely bonded on opposite sides of dense insulating core, strengthened by porcelain enamel (four layers on each sheet) which provides a non-porous, flint-hard, glass-smooth surface that is positively impervious to odors, acids and moisture. Sany metal *
Trade Mark Reg. U. S. Pat. Off.

TOILET COMPARTMENTS, SHOWER STALLS AND DRESSING ROOMS floor and tile on the second. Walls will have a reddish brown terra cotta dado, with a clear glaze ivory-colored tile above it.


The new building will provide steam air and power at the plant; CO³ gas from the furnaces will be used in the manufacturing of quick process lead. Three boilers will be installed, each with a normal continuous output of 65,000 lb. of steam per hour, and a maximum four-hour capacity of 75,000 lb. per hour. The

boilers will be equipped with traveling grate stokers, economizers, draft fans and dust collectors.

Coal for the operation of the plant will be carried to the power house by an inclined belt conveyor for distribution to a coal bunker located at the top of the building over the center aisle. The bunkers will feed the boilers by gravity after the coal is weighed on automatic scales. Provision has been made to use natural gas or fuel oil if desired later.

MACOMBER

STANDARDIZED SERVICE IN STEEL CONSTRUCTION



MACOMBER — Masters of the One Story Steel Building, have a real service for you. It includes:

- 1—Fabrication and erection of the complete building.
- 2—Fabrication of the roof supporting members only where masonry walls are used.
- 3—A wealth of engineering information as a result of specialization in this type of construction.

Here is standardization in steel building products that does not limit either you nor the occupant in the kind of building that serves his needs best. Your contractor knows Macomber products. He will expend far less equipment in their erection. If you are interested in some helpful suggestions and further information drop us a line.



MACOMBER

ANTON • OHI

MEMBER OF THE STEEL JOIST INSTITUTE

Hospitals

The Veterans Administration hopes to complete construction of two new hospitals and 12 additions to existing structures by the end of the year.

The new hospitals, at Lebanon, Pa., and Tomah, Wis., will supply beds for 1,699 neuropsychiatric patients, will cost about \$7,888,000. Completion dates are estimated as August and November.

Remodeling

Rehabilitation plans totaling nearly \$250,000 for a score of buildings under its management have been announced by Charles F. Noyes Company, Inc., New York. Work will be started immediately on four of the group, one of which is the 25-story Heckscher Building at Fifth Avenue and 57th Street. This large building, covering a plot of 26,000 sq. ft., will be completely rehabilitated under the direction of Walker & Gillette, architects. A new ground floor front covering all stores on the Fifth Ave. and 57th St. frontages is on the docket: the two facades between the first and third stories will be revamped, and limestone in vertical blocks will be placed to conform to the limestone architecture of the nine floors above. The ornamental metal now extending from the second to the third story will be entirely eliminated, and the exterior of the building cleaned.

WARSAW PLANS

Helena and Szymon Syrkus, the two Polish architects in charge of the planning and rebuilding of Warsaw, made their first public report at a meeting held at the New School for Social Research, New York City, on April 20. The meeting was sponsored by the New York Chapter of the A.I.A., the American Society of Planners and Architects, the Building Industry Committee of the National Council of American-Soviet Friendship, and the International Congress of Modern Architects.

The Warsaw plan is not limited to the 55 square miles of the city's former boundaries, but involves the entire city region covering an area of about 700 square miles. It subdivides the region into working, residential and recreational areas - a scheme made possible by the passing last October of a bill concerning the communization of land. The plan of the community development is taken as the basic unit of the town structure. The size of this basic city unit is based on the walking distance of grown men, the size of the smaller groups of houses into which the basic unit is subdivided is determined "by the stride of small children or of the woman carrying her baby." The entire unit is closed to through motor traffic. Four hundred square feet per person are considered the requirement for the sound development of a unit of 10,000 people.

hopes o new xisting

n, Pa.,
eds for
s, will
dates
ember.

nearly under ounced , Inc., ed imone of uilding . This 26,000 litated illette, front re. and et: the d third tonein

onform

ne nine

e third and the

he two
e plan, made
ng held
esearch,
e meetv York
nerican
ets, the
of the
-Soviet

al Conto the former entire about les the al and made ober of ation of ity deic unit of this walking of the nich the ermined

e of the nich the ermined or of the e entire traffic. rson are a sound people.

ECORD

LATEST "KNOW HOW" ON SUMMER COOLING Balsam-Wool data sheets!



• You'll want this complete file of Balsam-Wool Data Sheets because it gives you the latest, most complete information on insulation application. Here's a really valuable source of insulation reference data—carefully compiled, accurate and trustworthy. Send today for your set of Balsam-Wool Data Sheets—yours for the asking.



IMPORTANCE OF

ATTIC VENTUATION

Balsam-Wool

SEALED INSULATION

BALSAM-WOOL • Products of Weyerhaeuser • NU-WOOD

WOOD CONVERSION COMPANY

Dept. 115-6, First National Bank Building

St. Paul 1, Minnesota

Please send me set of Balsam-Wool Application Data Sheets.

.....

ADDRESS

CITY..... STATE.....

PRIORITIES APPROVED

Applications for priorities involving 400,000 new dwelling units were approved by the FHA, acting for the CPA, between January 15 and April 26, 1946. The total consists of applications to construct 350,000 new homes, of which 55 per cent will be for sale at less than \$7.500 or for rent below \$60 a month. Another 50,000 units are covered by applications to remodel existing structures for the creation of additional units.

The FHA also approved over 9,000 applications for repair and alteration jobs between April 12 and April 26, many of them covering authorization to construct without priorities assistance, under the Veterans Emergency Housing Program.

AWARD DIVIDED

For the first time since its establishment in 1942, the John Wesley Hyatt Award was made a dual one when two men were honored for outstanding achievement in the plastics industry at the annual dinner of the Society of the Plastics Industry in April. A gold medal and half of the \$1,000 award was presented to each of the winners: Virgil E. Meharg, superintendent of development. Bakelite Corp., and Paul D. Zottu, consulting electronic engineer of Newton, Mass. The winners were selected for their individual work in developing the use of electronic heating of thermosetting plastic materials. The award is sponsored by Hercules Powder Co.

COMPETITION

A competition to select a design and an architect for the proposed Minnesota State Veterans Service Building is now being conducted by the commission in charge of the project.

The building is to be erected on the grounds of the State Capitol in St. Paul. A total sum of \$2 million has been appropriated by the State Legislature for the purpose. Roy Jones, F.A.I.A., head of the School of Architecture, University of Minnesota, is the professional adviser for the competition; Leon Arnal of Minneapolis, Harvey W. Corbett of New York, and John W. Root of Chicago, form the jury. The competition has been approved by the Competition Committee of the A.I.A.

First, second, third and fourth prizes, of \$5,000, \$2,500, \$1,500, and \$1,000 respectively, will be awarded to the four most meritorious designs submitted. Winner of the first prize will be commissioned to design and supervise the erection of the building.

Prospective competitors should apply to John W. McConneloug, Secretary, State Veterans Service Building Commission, 1745 Court House, St. Paul 2. Minn. Applicants should request a copy of the program, give full particulars of their individual or firm names and addresses, and state whether and in what states they are registered to practice architecture.

APPOINTMENTS

Dr. John D. Kraus, Harvard University research scientist and inventor of several wartime engineering devices, has been named associate professor of electrical engineering at Ohio State University, effective July 1. He will specialize in teaching and research in communications engineering.

Col. Harold Lee has been appointed governor of the Federal Home Loan Bank System. He has been associated with the FHLBA since 1934, has been its general counsel for the past seven years.

C. Stott Noble has been appointed Regional Housing Expediter for the Cleveland area, and a new regional office (Continued on page 142)



Barcol OVERd

A RELIABLE UPWARD-ACTING **DOOR with DISTINCTIVE Features**

The picture illustrates only one of many possible types of buildings in which the Barcol OVERdoor can be used successin this case, that of a lumber dealer who required a large-size door (18 feet wide by 13 feet high) for a trucking entrance. The Barcol OVERdoor is built to exacting standards of manufacture to insure long life and trouble-free operation, and offers a number of distinctive features such as:



Barcol OVERdoors Electric

Door Operators Switch Controls Radio Controls

ROLLER-CRANK CLOSING ACTION SELF-LATCHING BOLTS TWIN-TORSION TAILORED SPRINGS CONTINUOUS VERTICAL TRACK BRACKETS

Barcol OVERdoors are made in standard sizes for residence garages and in special large sizes to order for commercial, industrial, institutional, and similar buildings. Supplementary Barcol equipment includes Electric Door Operators for remote switch control of large doors and gates, and the Radio Control for opening and closing garage doors from a moving car by simply pushing a button. See your Barber-Colman representative for full details on any contemplated installation.

FACTORY-TRAINED SALES and SERVICE REPRESENTATIVES IN PRINCIPAL CITIES

ER-COLMAN

tanding
istry at
y of the
d medal
as prelirgil E.
pument,
tu, conNewton,
ted for
ping the
osetting
s spon-

ign and innesota g is now ission in

I on the in St. lion has e Legis-Jones, of Archiesota, is e compeneapolis, ork, and the jury. approved ee of the

th prizes, d \$1,000 l to the abmitted. be comrvise the

uld apply secretary, ing Comt. Paul 2. set a copy articulars ames and r and in

d Univereventor of devices, ofessor of hio State He will esearch in

appointed ome Loan associated as been its even years. appointed r for the ional office in page 142)

RECORD



Twenty-six years' service! Initial installation in 1918...interior "thermostats" replaced in 1944! That's the record of Webster Thermostatic Traps in the office building of the Chase Brass & Copper Co., Waterbury, Conn

Long Service from Webster Traps

The quarter-century plus record of Webster Traps cited above is not an isolated instance. In our files are many other records of ten... fifteen... twenty years and more... varying with service conditions, pressure, local water and quality of operating standards.

Webster Radiator Traps are built to give extra years of service—design, quality materials, precision manufacture and careful inspection are the "reasons why".

Traps at lower *first* cost do not mean a saving. Actual cost is determined by length of service... And Webster Traps are outstanding for years of service per dollar.

There's no waste of "live" steam because Webster Radiator Traps hold steam in the radiator till it has given up all its useful heat. They do not open too soon, allowing uncondensed steam to escape into the returns. Nor do they close too soon, holding up condensate. Webster Radiator Traps mean quick, continuous and complete discharge of air and condensation.

If your radiator traps need replacement, get the longest-lasting trap available. For full information on Webster Traps, consult the nearest Webster Representative. Or write us direct.

WARREN WEBSTER & CO., Camden, N. J. Pioneers of the Vacuum System of Steam Heating Representatives in principal cities:: Darling Bros., Ltd., Montreal



has been opened in Cleveland. Mr. Noble, who was in private real estate business for 16 years, and was formerly a regional manager for the Home Owners Loan Corp., has been assistant administrator of the Farm Security Administration since 1944.

James L. Pease of Cincinnati, Ohio. has been appointed director of the Prefabrication Production Branch of the NHA. One of the founders, and a past president of the Prefabricated

Home Manufacturers Institute, Mr. Pease is president of Pease Woodworking. Inc.

Ernest Pickering, head of the division of architecture in the School of Applied Arts, University of Cincinnati, since 1925, has been named dean of this unit, renamed the College of Applied

Rear Admiral Kirby Smith, USNR (Civil Engineering Corps), has been appointed General Deputy Expediter for the Veterans Emergency Housing Program. One of the Navy's top-ranking construction men during both World Wars, Admiral Smith was largely responsible for developing and supervising a \$4,500,000,000 building program for the Navy Department in the United States, Hawaii, the Canal zone, etc. He will be general deputy for Wilson Wyatt, in charge of all operations of the housing program, but will concentrate in the coming months on problems of supply and production.

Prof. James G. Van Derpool, head of the department of art at the University of Illinois since 1940 and associated with the departments of architecture and art at Illinois since 1932, has been appointed librarian of the Avery Library and a member of the faculties of the School of Architecture and School of Library Science at Columbia University.

effective next September 1.

ELECTIONS

Chester S. Allen has been elected president of Lockwood Greene Engineers, Inc., succeeding the late Albert L. Scott. He has been with the company since 1910. Another newly elected Lockwood officer is Howard E. Cousins, named a vice president.

Clarence W. Farrier has resigned as director of the Technical Division of the NHA to become assistant to the president of Gunnison Homes, Inc.

Dawson Winn, vice-president of Green Lumber Co., Laurel, Miss., has been elected president of Prefabricated Home Manufacturers' Institute. The other newly elected Institute officers are: vice-president, Austin Drewry, secretary of Gunnison Homes, Inc.; secretarytreasurer, John Pease, Pease Woodwork Co.

OFFICE NOTES

Offices Opened, Reopened

C. A. Balch and Wm. Glenn Balch. Architects, and L. L. Bryan announce the opening of their office for the general practice of architecture at 1725 Silver Lake Blvd., Los Angeles 26, Calif.

Stanley F. Chamberlain, Industrial Designer, has opened a completely equipped model-making shop at 317 E. 91st St., with offices at 654 Madison

Ave., New York City.

Robert Allan Class, A.I.A., has announced the establishment of professional offices for the general practice of architecture in the Architects Bldg., 17th St. at Sansom, Philadelphia 3, Pa.

Leonard B. Conley, Residential and Commercial Designer, has reopened his offices at 906 Neil P. Anderson Bldg., Fort Worth, Texas, following his release from the Army.

Daniel, Mann and Johnson, Architects of No. 15, Motta Bldg., Santa Maria, (Continued on page 144)



usAlRco


Evaporative Condensers

More Efficient Condensing of Refrigerants PLUS Big Water Savings . . .

The evaporative condenser is a "packaged" unit in that it incorporates all the desirable features of the conventional shell and tube condenser, water cooling tower and water pump in a single, compact piece of equipment.

Savings up to 95 % in water costs are possible with the use of evaporative condensers for refrigeration or air conditioning applications. They also eliminate waste water disposal problems, and pumping costs are much lower than those of a conventional cooling tower installation.

usAIRco Evaporative Condensers are designed for maximum economy and efficiency in operation. Complete design and engineering information may be had on usAIRco Evaporative Condensers by requesting a copy of special bulletin.



United States Air Conditioning Corporation

COMO AVENUE S. E. AT 33RD MINNEAPOLIS 14, MINNESOTA



y Housing op-ranking oth World largely resupervising rogram for the United ne, etc. He son Wyatt, the housing ate in the

ool, head of University associated architecture 2, has been ery Library Ities of the School of University,

een elected eene Engite Albert L. ne company vly elected E. Cousins,

resigned as Division of tant to the es, Inc.

ent of Green
., has been
cated Home
The other
officers are:
ry, secretary
e Woodwork

eopened

Glenn Balch, an announce or the general 1725 Silver o, Calif.

completely op at 317 E. 554 Madison

I.A., has anof professionpractice of itects Bldg., lelphia 3, Pa. sidential and as reopened derson Bldg., ng his release

on, Architects Santa Maria, d on page 144)

L RECORD



"THE complete interpretation of business news that I find in The Wall Street Journal has daily kept me informed of the important trends in the building material, industrial maintenance and construction, and paperboard product

industries. Now, more than ever, the need for up-to-theminute business news that affects such a vital industry as building in particular is a pressing problem. I consider The Wall Street Journal fills that need admirably."



has been opened in Cleveland. Mr. Noble, who was in private real estate business for 16 years, and was formerly a regional manager for the Home Owners Loan Corp., has been assistant administrator of the Farm Security Administration since 1944.

James L. Pease of Cincinnati, Ohio, has been appointed director of the Prefabrication Production Branch of the NHA. One of the founders, and a past president of the Prefabricated

Home Manufacturers Institute, Mr. Pease is president of Pease Woodworking, Inc.

Ernest Pickering, head of the division of architecture in the School of Applied Arts, University of Cincinnati, since 1925, has been named dean of this unit, renamed the College of Applied

Rear Admiral Kirby Smith, USNR (Civil Engineering Corps), has been appointed General Deputy Expediter

for the Veterans Emergency Housing Program. One of the Navy's top-ranking construction men during both World Wars, Admiral Smith was largely responsible for developing and supervising a \$4,500,000,000 building program for the Navy Department in the United States, Hawaii, the Canal zone, etc. He will be general deputy for Wilson Wyatt, in charge of all operations of the housing program, but will concentrate in the coming months on problems of supply and production.

Prof. James G. Van Derpool, head of the department of art at the University of Illinois since 1940 and associated with the departments of architecture and art at Illinois since 1932, has been appointed librarian of the Avery Library and a member of the faculties of the School of Architecture and School of Library Science at Columbia University.

effective next September 1.

ELECTIONS

Chester S. Allen has been elected president of Lockwood Greene Engineers, Inc., succeeding the late Albert L. Scott. He has been with the company since 1910. Another newly elected Lockwood officer is Howard E. Cousins, named a vice president.

Clarence W. Farrier has resigned as director of the Technical Division of the NHA to become assistant to the president of Gunnison Homes, Inc.

Dawson Winn, vice-president of Green Lumber Co., Laurel, Miss., has been elected president of Prefabricated Home Manufacturers' Institute. The other newly elected Institute officers are: vice-president, Austin Drewry, secretary of Gunnison Homes, Inc.; secretary-treasurer, John Pease, Pease Woodwork Co.

OFFICE NOTES

Offices Opened, Reopened

C. A. Balch and Wm. Glenn Balch. Architects, and L. L. Bryan announce the opening of their office for the general practice of architecture at 1725 Silver Lake Blvd., Los Angeles 26, Calif.

Stanley F. Chamberlain, Industrial Designer, has opened a completely equipped model-making shop at 317 E. 91st St., with offices at 654 Madison Ave., New York City.

Robert Allan Class, A.I.A., has announced the establishment of professional offices for the general practice of architecture in the Architects Bldg., 17th St. at Sansom, Philadelphia 3, Pa.

Leonard B. Conley, Residential and Commercial Designer, has reopened his offices at 906 Neil P. Anderson Bldg., Fort Worth, Texas, following his release from the Army.

Daniel, Mann and Johnson, Architects of No. 15, Motta Bldg., Santa Maria, (Continued on page 144)



usAlRco

Evaporative Condensers

More Efficient Condensing of Refrigerants PLUS Big Water Savings . . .

The evaporative condenser is a "packaged" unit in that it incorporates all the desirable features of the conventional shell and tube condenser, water cooling tower and water pump in a single, compact piece of equipment.

Savings up to 95 % in water costs are possible with the use of evaporative condensers for refrigeration or air conditioning applications. They also eliminate waste water disposal problems, and pumping costs are much lower than those of a conventional cool-

ing tower installation. usAIRco Evaporative Condensers are designed for maximum economy and efficiency in operation. Complete design and engineering information may be had on usAIRco Evaporative Condensers by requesting a copy of special

HEATING & UNIT & BLAST HEATERS AIR WASHERS

United States Air Conditioning Corporation

COMO AVENUE S. E. AT 33RD MINNEAPOLIS 14, MINNESOTA



or Housing op-ranking oth World largely reupervising ogram for he United he, etc. He son Wyatt, he housing ate in the of supply

ol, head of University associated rehitecture t, has been ery Library ties of the School of University,

een elected eene Engite Albert L. ee company dy elected E. Cousins,

resigned as Division of tant to the es, Inc.

ent of Green , has been cated Home The other officers are: ry, secretary; woodwork

eopened

Clenn Balch, an announce r the general 1725 Silver , Calif.

completely op at 317 E. 554 Madison

A., has anof professionpractice of itects Bldg., lelphia 3, Pasidential and as reopened derson Bldg., ng his release

on, Architects Santa Maria, d on page 144)

L RECORD



I. J. HARVEY, Jr., President, The Flintkote Company

"THE complete interpretation of business news that I find in The Wall Street Journal has daily kept me informed of the important trends in the building material, industrial maintenance and construction, and paperboard product

industries. Now, more than ever, the need for up-to-theminute business news that affects such a vital industry as building in particular is a pressing problem. I consider The Wall Street Journal fills that need admirably."



Calif., have opened an additional office at 672 S. Lafayet Park Pl., Los Angeles.

Frank Grad & Sons, Architects and Engineers, of 48 Commerce St., Newark 2, N. J., have opened a branch office at 1633 Connecticut Ave., N.W., Washington, D. C.

Roy A. Kazebier, A.I.A., has established his office for the general practice of architecture in Suite 15, 111 West B. St., Ontario, Celif.

Rebert W. Kennedy and Theodore

Jordan announce the opening of an office for the practice of architecture at 687 Boylston St., Boston, Mass.

E. J. Peterson, Architect, has opened offices in the Sherwood Bldg., Spokane 8, Wash., following four and a half years with the U.S. Army Engineers.

Owen F. Smith, Architect, has returned from the Navy and has opened an office at 2730 Anderson Dr., Raleigh, N. C.

Edward D. Stone has announced the

reopening of his New York architectural office at 50 East 64th St., New York 21, N. Y. Associated with him are Stanley C. Reese, Alexander Knowlton, J. Graham Stewart and Karl J. Holzinger, Jr.

Allan Wallsworth, Architect, has resumed the practice of architecture with offices at 2846 N. Prospect Ave., Milwaukee 11, Wis.

Jarrett C. White, A.I.A., has reopened his office at 1308 18th St., N.W., Washington, D. C., following three years as consultant to the Surgeon General, I.S. Army.

Harry Hayden Whiteley, Architect, has returned to his practice with offices at 2400 Fifth Ave., San Diego 1, Calif.

Paul P. Wiant, A.I.A., A.S.C.E., for many years prior to 1944 director of the Union Architectural Service, Foochow, China, is now architect and engineer for the Methodist Church in China, with offices at 169 Yuen Ming Yuen Road, Shanghai.

New Addresses

The following new addresses have been announced:

Victor D. Abel, Architect, Architects Bldg., 117 S. 17th St., Philadelphia 3, Pa.

Samuel Glaser, Architect, 105 Newbury St., Boston, Mass.

Holsman & Holsman and Klekamp, Architects, Dunham Bldg., 450 E. Ohio St., Chicago 11, Ill.

Johnson, Wallwork & Dukehart, Architects, 802 Dekum Bldg., 519 S.W. 3rd Ave., Portland 4, Ore.

Isadore Naftali, Architect, 312 High St., Newark, N. J.

National Committee on Housing, Inc., 1 Madison Ave., New York 10, N. Y. Pennell and Wiltberger, Consulting Engineers, 1524 Chestnut St., Philadelphia 2, Pa.

Firm Changes


Announcement has been made of the merger of the architectural offices of George Harwell Bond and Cooper & Cooper and the formation of the firm of Cooper, Bond & Cooper, Inc., Architects and Engineers, with temporary offices at 827-830 Forsyth Bldg., Atlanta, Ga.

William Wayne Caudill and John Miles Rowlett, both recently returned from service in the Navy, have established an architectural partnership under the firm name of Caudill and Rowlett. Architects, with offices at 1401½ Lavaca St., Austin, Texas.

L. C. Cavitt, Jr., and Clifford J. Lane have established the firm of Cavitt and Lane, Architects and Engineers. Address, 4801 Lemmon Ave., Dallas 9. Texas.

Theodore W. Dominick and William (Continued on page 146)





Two Problems in Plant Heating Solved by WING Revolving HEATERS

Two striking instances of the unique advantages of Wing Revolving Heaters are presented in the photographs above.

At the left is one of the shops of a large ship-building concern, where a high ceiling and a crowded shop area of 802 ft. x 156 ft. presented a heating problem that could not be overcome by ordinary heating systems. The solution was Wing Revolving Heaters, located 61 feet above the shop floor, projecting heated air down to the working level through slowly revolving outlets, circulating the heat thoroughly to every part of this huge shop in a constant, even temperature.

At the upper right is part of the assembly shop of one of the world's largest builders of cargo planes. This modern plant is heated by Wing Revolving Heaters. No other type of heater could so thoroughly and evenly heat a plant of this kind, where the massive planes form imposing obstacles to the projection of heated air from fixed discharge outlets. But with the slowly moving streams of warm air from the revolving discharge outlets of the Wing heaters, circulating around and under the huge plane bodies, wings, rudders, stabilizers, etc., the plant is kept at a uniform, comfortable remograture.

Operating officials in both plants find that the sensation of warm, live, invigorating comfort enjoyed by the workers is stimulating to production. And in summer, with the steam turned off and the fans on, a cooling effect is obtained that is likewise conducive to production.

Write for a copy of Bulletin HR-4



rchitectural ew York 21, are Stanley owlton, J. . Holzinger,

ect, has reecture with Ave., Mil-

as reopened I.W., Washree years as n General.

Architect, with offices go 1, Calif. S.C.E., for rector of the e, Foochow, engineer for China, with Yuen Road.

resses have

, Architects ladelphia 3,

, 105 New-

d Klekamp, 450 E. Ohio

Dukehart, g., 519 S.W.

t, 312 High

ousing, Inc., k 10, N. Y. Consulting St., Phila-

made of the al offices of l Cooper & of the firm of Inc., Architemporary Bldg., At-

l and John tly returned have estabership under and Rowlett, at 1401½

Clifford J. irm of Cavitt d Engineers. re., Dallas 9.

and William I on page 146)

RECORD



Contractor Casey was stumped...

BUT NOT FOR LONG


He consulted with the architect and engineer . . . together they called in Ceco . . . and the job went ahead on schedule

The job was a big one—the kind contractors like. It looked like smooth sailing to Casey until lack of materials suddenly stopped the job. But not Casey! With the architect, the engineer and Ceco, he made changes to use available Ceco products such as Concrete Reinforcing Bars, Meyer Steelforms, Welded Wire Fabric, Light Fabricated Trusses and Open Web Steel Joists, all of which gave greater advantages—in space and cost in manpower and installation. The gist of it all is that Casey completed his contract on time, within the original cost, and to the satisfaction of the architect and owner.

CECO ENGINEERING PLUS CONSTRUCTION KNOW-HOW...MAY HELP YOU WITH YOUR PROBLEMS

Ceco engineers do more than design fine construction products. All their wealth of technical engineering knowledge is constantly available to you, as well as their construction know how gained by years of experience on the job in the field. In 23 offices strategically located from coast to coast, they stand ready to help solve your problems without delay, with perfect technical skill. Ceco Construction Products, whatever they are, are engineered so as to make for ease of installation and correct construction practice. So call on Ceco for engineering and construction skill, for the finest in construction products.

ERE ARE THE PRODUCTS THAT HELPED SOLVE MR. CASEY'S PROBLEM



yer Steelforms mean less concrete is rered, making for economy in construction.

Welded Wire Fabric provides reinforcemente concrete slab over Meyer Steelform



Cece Reinforcing Bars provide positive bond to aid adhesion of concrete to the steel.



Open Web Steel Joists provide fire-resistive construction, concealing sanitary, lighting and heating systems.



Concrete Engineering Division,
Merchant Trade Division, Highway Products Division
Offices, Warehouses and Fabricating Plants in Principal Cities

Mail This Handy Coupon For Free CECO Catalogs

CECO STEEL PRODUCTS CORPORATION 5669 West 26th Street Chicago 50, Illinois

Please send me the catalogs checked below:

Handbook of Ceco Products

☐ Handbook of Ceco Prod
☐ Ceco Steel Joists

Name .

Address.

y Stafe

In construction products CECO ENGINEERING makes the big difference



"Looks like we're ALL for Cast Iron!"

Leading architects, engineers and contractors agree that they can recommend cast-iron boilers with confidence. These are the reasons:

They're a sound investment in long-term satisfaction . . . they resist corrosion and rust indefinitely . . . they are easily installed, maintained, replaced . . . they deliver high efficiency and resultant low operating cost.

Professionals also recognize H. B. Smith leadership in the cast-iron field . . . for every commercial, industrial, institutional and residential use, for all fuels and fuel-burning methods. Write today for your free catalogue.



THE RECORD REPORTS

(Continued from page 144)

H. Van Benschoten have formed a partnership under the firm name of Dominick and Van Benschoten, Architects, with offices at 1122 19th St., N.W., Washington 6, D. C.

Announcement has been made of the opening of the offices of Ford and Hobson, Architect and Engineer, Cor. Govt. and Broad Sts., Office No. 9, Mobile 18,

Grunsfeld, Yerkes & Koenig, Architects, have announced the addition to their partnership of Samuel Arthur Lichtmann, A.I.A., and the change of the firm name to Grunsfeld, Yerkes, Lichtmann & Koenig, Architects & Engineers. Address, 520 N. Michigan Ave., Chicago 11, Ill.

The Hingham Construction & Supply Co., Box 53, Hingham, Mass., has announced resumption of its activities following the return of its key men from the Armed Services.

McKim, Mead & White, 101 Park Ave., New York, have announced that Edward James Mathews is now affiliated with their organization as associate.

Kenneth H. Ripnen Co., Inc., Management Counsellors in Space Administration, announces the return of its president, Kenneth H. Ripnen, Major, A.U.S., who during the war was assigned to the Army Service Forces as Space Officer in the Office of the Army Headquarters Commandant, War Department. Mr. Ripnen, a member of the A.I.A., will also continue his private practice in commercial and industrial architecture.

George H. Schaffer has been named president of the newly formed Spence-Rigolo, Inc., an industrial and architectural firm with offices at 677 Fifth Ave., New York City. The firm is the outgrowth of the partnership of Edmond J. Spence, Industrial Designer and vice president of the new firm, and Arthur Rigolo, Architect and Industrial Designer, secretary-treasurer.

Sundberg & Ferar, Industrial Designers, have taken new and larger quarters in the Guardian Bldg., Detroit, Mich. The firm's two model shops in Detroit will continue operating in separate establishments.

P. M. Torraca, former associate professor of architectural engineering at the Virginia Polytechnic Institute, has been appointed a member of the Home Bureau of the General Electric Co., Bridgeport, Conn.

Frank Vitullo, formerly publications and exhibitions designer at the Museum of Modern Art, New York, has joined Bertell Inc., 40 E. 49th St., New York 17, design and development organization, as art director.

NEWMAN ORNAMENTAL METAL



Famous for Quality Since 1882

THE State Capitol of Louisiana (shown above) is a magnificent example of NEWMAN QUALITY AND NEWMAN SKILL... but from coast to coast are other shining and illustrious installations which portray this NEWMAN touch. Architects' dreams are crafted into handsome ornamental bronze, aluminum, nickel and stainless steel.

BANK FIXTURES • GATES • GRILLES RAILINGS • DOORS • ENTRANCES STOREFRONTS

> Hollow, cast or wrought work "equal to the finest"

HAND-CHASED TABLETS

Newman artistry reaches new peaks of perfection in interpreting the ideas and ideals of foremost designers who choose this as the medium of lasting expression... in "the metal of countless tomorrows."


WRITE FOR COMPLETE FILE DATA FREE

Estimates and construction information sent promptly, without obligation.



NEWMAN BROTHERS, Inc.

"64 Years Young" 708 W. 4TH Street CINCINNATI 3, OHIO



HOME OF WALT DISNEY PRODUCTIONS safely cooled with "FREON-12"

IN DESIGNING the Walt Disney Studios in Burbank, California, architects were vitally concerned with the need for safety in controlling temperature and humidity throughout the various buildings.

FAL

nt ex-

ILLES

TS

eaks of eas and choose expresantless

. Inc.

RECORD

In the building where animated pictures of the famous Disney characters are made, inflammable motion picture film is used. To reduce the fire hazard . . . it was good judgment and a logical choice to select air conditioning equipment designed to utilize non-flammable "Freon." "Freon" safe refrigerants are also non-toxic, non-explosive, odorless and stainless.

The air conditioning equipment, installed in 1940, consists of two banks each of six General Electric 8-cylinder V-type reciprocating compressors with a total of

600 h.p. Their operation is 100% automatic, governed by the temperature of a circulatory water loop which provides a positive control at all times of comfort-cooling and humidity.


Humidity Control Essential

Average temperature within the studio buildings is maintained between 72°F. and 75°F. In the Inking and Painting buildings, regulated humidity is essential to prevent paint from becoming tacky on the celluloids. Films must also be safely kept under controlled climatic conditions both before and after processing.

"Freon" safe refrigerants have become the first choice of prominent architects and engineers everywhere. They recognize the importance not only of the safety of these refrigerants, but also of their purity and almost complete absence of moisture . . . factors which contribute to the dependable operation and longer life of the equipment. Complete data for your files upon request.

Kinetic Chemicals, Inc., Tenth and Market Sts., Wilmington 98, Delaware.





Now you can plan with confidence, build with certainty . . . know your project will come within your budget . . . that your investment will not be short-circuited by premature style senility.



MODERN STORE DESIGN

is the last word on an important subject of which too little has been said, by Gene Burke and Edgar Kober, of Burke and Kober, America's outstanding authorities on every aspect of Mercantile Modernization. In 144 large pages, Burke and Kober have condensed the brilliant experience of 20 years... an entire library on a most vital subject in a single volume.

Profusely illustrated, filled with actual indexed, departmentalized cost records, charts, graphs, style detail, working drawings. Here is the short-cut to successful, economically sound STORE MODERNIZATION.



1000 copies only at special prepublication postage prepaid \$1000 price of ...

Reserve your copy now.
Use the coupon.

INSTITUTE OF PRODUCT RESEARCH
1209-H Pershing Square Building
Los Angeles 13, California
ENTER AT ONCE MY PRE-PUBLICATION ORDER FOR ____COPY(IES) OF MODERN STORE
DESIGN AT SPECIAL PREPAID PRICE OF \$10.

Check Enclosed ___ Send Invoice

Name	Title	
Firm		
City	State	

ARCHITECTURAL ENGINEERING

TECHNICAL NEWS AND RESEARCH

(Continued from page 126)

high-tensile, low-alloy steel. Dimensions, load and other design data tables are furnished for structural members made of this material. 16 pp., illus. Jones & Laughlin Steel Corp., Pittsburgh 30, Pa.*

VALVES

Walworth Today, Vol. 6, No. 5. Booklet describes manufacture of malleable iron unions and union fittings. The outstanding features of a new line of iron body gate valves are presented. Sectional drawings show details of their construction. 14 pp., illus. Walworth Co., 60 East 42nd St., New York 17, N. Y.

LITERATURE REQUESTED

The following individuals and organizations request manufacturers' literature:

Bank of the Manhattan Co., Att. Mr. W. G. Pedersen, 40 Wall St., New York. Building & Manufacturing, Publica-

tion, Ryan House, Eagle St., Brisbane, Australia.

Cavitt & Lane, Architects and Engineers, 4801 Lemmon Ave., Dallas 9, Tex.

Caudill & Rowlett, Architects, 1401½ Lavaca St., Austin, Tex.

C. C. Cheng, Architect, New China Syndicate, Ltd., Chung Cheng Rd., Shanghai, China,

Childers & Kohli, Engineers, Longanbach Block, Fremont, Ohio,

Daniel, Mann & Johnson, Architects, 672 South Lafayet Park Place, Los Angeles, Calif.

DelVisco-Reisinger Co., Engineers and Builders, 106 Glenridge Ave., Glen Ridge, N. J.

Frank Grad & Sons, Architects and Engineers, 48 Commerce St., Newark 2, N. J.

Roy A. Kazebier, Architect, 15 Euclid Bldg., 111 West B St., Ontario, Calif.

Aquiles Landoff, Architect, Casilla 119, Viana 35, Vina Del Mar, Chile.

Owen F. Smith, Architect, 2730 Anderson Drive, Raleigh, N. C.

Savo M. Stoshitch, Architect, 10328 Eastborne Ave., Los Angeles 24, Calif. Vann & Lyell, Architects, 2260 N.W.

North River Drive, Miami, Fla. Allan Wallsworth, Architect, 2846

Allan Wallsworth, Architect, 2846 North Prospect Ave., Milwaukee 11, Wis.

H. H. Whiteley, Architect, 2400 Fifth

Ave., San Diego 1, Calif.

Paul P. Wiant, Architect and Engineer, Methodist Church in China, 169 Yuen Ming Yuen Road, Shanghai, China.

ANCHOR FENCE STANDS UP Under Hard Use!

gro

Ne

cal

lin

cre

Ne

no

un

ple

the



First Chain Link Fence Still in Service After 39 Years

Testifying to the ruggedness of Anchor Fence is the protection this installation has given at the Ampere, N. J., plant of the Crocker-Wheeler Electric Manufacturing Company since 1907. This fence is held erect and in line by our exclusive deep-driven anchors. These anchors clamp to the posts . . . are driven deep into the sub-soil . . form a 3-point "tree root" anchorage. Yet, they permit easy relocation when necessary.

Three other exclusive features add to Anchor Fence's performance. Square Frame Gates . . . amazingly free from sagging and warping. U-Bar Line Posts . . . self-draining, rust-free and rigid. Square Terminal Posts . . . which improve strength, durability and appearance. Whether you're specifying fence for industrial or residential installations, these four big advantages are your extra assurance of satisfied clients.

Free Specification Manuals For Your A. I. A. File 14-K

Let us send you our Specification Manuals on Anchor Chain Link and Anchor-Weld Iron Fences. Contain installation photographs and sectional drawings . . . describe various heights, weights, structural features and applications . . include helpful sample specifications of many types of fencing jobs. Address: Anchor Post Products, Inc., 6600 Eastern Ave., Baltimore 24, Maryland.



Interest in The Nesbitt Package is running high. Architects and school executives are inquiring about the modern schoolroom ensemble which combines the healthful comfort of "Syncretized Air" with the convenience and utility of integrated storage facilities. The most frequent question asked is, "When can we have delivery?"

Nesbitts are making "The Package" the economical way for you . . . by standardized production-line methods. All component parts for Nesbitt Syncretizer Unit Ventilators, Nesbitt Convectors, and Nesbitt steel Classroom Shelving and Cabinets are now in stock. Upon receipt of your specifications we are ready to assemble and to make shipment.

If you have school building or modernizing plans under consideration, let us discuss with you the place in those plans for The Nesbitt Syncretizer or the complete Nesbitt Package.

Write to JOHN J. NESBITT, INC., State Road and Rhawn Street, Philadelphia 36, Pa. Sold also by American Blower Corporation.

you can get it.
NOW!



ice

uals on Id Iron ohs and various d appliecificaiddress: n Ave.,

nce

r Fence given at rockerompany in line These driven 3-point nic easy Anchor es . . . arping. ust-free which arance. dustrial big adatisfied

Wherever Cleanliness, Economy,

THIS ARCHITECT CHOOSES

WILLIAM I. HOHAUSER is well-known as one of America's leading architects. He has done such theater jobs as the Community Theater, Hamilton, N. J.; Beacon Theater, Beacon, N. Y.; the Lane, Symphony and Tribune Theaters in Manhattan; the Clinton Theater in Brooklyn; and the Avon Theater in Stamford, Conn.

He is now working on the renovation of the former Anderson Galleries at 59th Street and Park Avenue in New York into one of the country's finest movie houses.

Among other outstanding projects Mr. Hohauser has designed are Riveredge Apartments; 307 Fifth Avenue Building; Franklin Tower Hotel; and the new apartment projects for Fifth Avenue & 68th St., all in Manhattan. Also Kensington Gardens in Buffalo; Manchester Gardens in Manchester, Conn.; and Joseph P. Bradley Court in Newark.

He is one of the architects of such public housing projects as the Red Hook, Fort Greene and Wallabout Houses in Brooklyn.





PETROLEUM HEAT & POWER CO., Stamford, Connecticut

Convenience, Quiet Come First

PETRO OIL BURNING EQUIPMENT!

In a theater or in a home, apartment or commercial building, today's standards of better living call for a heating system that contributes to the occupants' comfort, convenience and health. Freedom from drudgery and costly maintenance must go hand in hand with fine, economical heating performance.

How do Petro Oil Burning Systems measure up to these exacting requirements? An evergrowing number of architects and engineers can give you the answer. For example, here is the way Mr. William I. Hohauser puts it:

"We believe the theater of the future will be distinguished by simple design and will be more functional than the pre-war theater. Special attention will be devoted to lighting, heating, airconditioning, visual conditions, and pleasant environment for the patrons. Motion picture theaters promise to lead the way in the upward trend, and community theaters will play a larger role in American life with their presentations integrating educational along with recreational facilities.

"In my opinion oil heating maintains its superiority for theaters, where cleanliness, convenience, economy and quiet surroundings are essen-

tial. Where Petro systems are in use, I know from experience that fuel costs are very favorable in comparison with coal, and labor costs have resulted in a saving of at least 15% and from there up.

"The wide range of Petro Oil Burning Systems can be considered a common denominator for any type of building. They are sturdy in construction and extremely efficient in operation."

In fact, architects who know all agree the best reason for installing Petro is that in the long run anything else costs considerably more.

INDUSTRIAL MODELS

No. 5 or No. 6 fuel oil, manual, semi-automatic or automatic operation, 8 sizes to 450 bhp. "Thermal Viscosity" preheating.

DOMESTIC MODELS

No. 3 or lighter oils, "conversion" and combination-unit types, 7 sizes. Patented "Tubular Atomization."

FULL DATA


on Petro Industrial Burners are in catalog files of Sweet's and Domestic Engineering. Details on Petro Domestic burners available in separate catalog. Copy of either sent gladly on request.

CUTS STEAM COSTS


Makers of Good Oil Burning Equipment Since 1903

ecticut

There are Two lines of Pittco Metal - each distinctively styled



PITTCO Since its introduction several years ago, the Pittco De Luxe line of store front metal has won a hearty endorsement from architects. Careful planning of the line as a whole, all at one time, resulted in unusual unity of design -a harmonious relationship between each Pittco De Luxe unit and all the other members in the line. And the extruded method of manufacture assures rugged strength, clean, sharp profiles, lasting color and perfect finish. This unrivalled combination of characteristics accounts for the continued popularity of Pittco De Luxe. It is first choice with architects whose clients demand sales-winning store fronts which reflect high quality.



PREMIER Recently, Pittco Premier was introduced to satisfy the need for a lightweight, moderately priced line of store front metal. The same careful planning and harmonious styling which have made Pittco De Luxe so popular are evident in the Premier line. Pittco Premier also was designed as a unit . . . each piece styled to complement and heighten the beauty of the other members with which it is used. Pittco Premier can be set easily and quickly from the outside, effecting a substantial savings in setting time. And the self-adjusting clip always maintains a firm grip on the glass, no matter what its thickness. These practical advantages plus the high degree of architectural beauty in the Premier line promise success comparable to that already attained by Pittco De Luxe.



PITTER LIBERT TORE FRONT METAL

PITTSBURGH PLATE GLASS COMPANY


"PITTS BURGH" stands for Quality Glass and Paint

eral years
the of store
ment from
line as a
sual unity
to between
the other
d method
th, clean,
tect finish.
acteristics
of Pittco
cts whose

onts which

was intro-

of store
and harco De Luxe
line. Pittco
and the
nit is used.
bickly from
savings in
lip always
no matter
dvantages
beauty in
parable to



For America's finest post war buildings

PERMATITE

ALUMINUM

WINDOWS



Selected for the new ADMINISTRATION BUILDING at CORNELL UNIVERSITY

Before the war PERMATITE windows, made in either aluminum or bronze, were the choice of many leading architects. They were selected for use in schools, hospitals, apartments, public and commercial buildings.

Today, the preference for these fine quality windows is even greater than ever before. Architects, contractors and owners alike are demanding them for their finest postwar jobs in every field.

Selected for their beauty, ease of operation, freedom from periodic painting and other maintenance expense, PERMATITE aluminum windows are being used in the new administration building at Cornell University, Ithaca, New York.

For complete information, full size details, etc., on PERMATITE windows and other General Bronze building products, consult Sweet's or write for catalogs.



GENERAL BRONZE CORPORATION

34-15 TENTH STREET


LONG ISLAND CITY 1, N. Y.

Architectural Metal Work · Windows · Revolving Doors

Enterprise Oil Burners

They wanted to make The Esquire "the dream theater of Chicago" . . . and among the equipment specified were two ENTERPRISE Oil Burners. After eight years of operation, these Burners are still giving "the maximum in efficiency with minimum maintenance", say the theater's managers. (Economy note: The Esquire's ENTERPRISE Burners burn Bunker C oil automatically.) ENTERPRISE Oil Burners are available in Manual, Semi-Automatic and Full-Automatic in combination with modulating fire control or special combinations for your specific requirements. Combustion Equipment Division. ENTERPRISE ENGINE & FOUNDRY COMPANY, San Francisco 10. Distributors in principal cities.

1886 60th 1946



HE ESQUIRE HOUR

ORD

THE TRUTH ABOUT

Until now, you've heard about Aquella from everybody but us. First...there was Kurt Steel's absorbing article ("Dry Cellars") in the December 15, 1945 issue of Forbes Magazine.

Second...there was the condensation of this same article which appeared under the caption "Water Stay Away from My Wall" in the January issue of the Reader's Digest.

Third...there was a flood of anonymous letters containing garbled references to a Federal Trade Commission complaint, as well as a copy of a letter dated December 29th, 1945, which purported to have come from the Director of the United States Bureau of Standards.

Why you've not heard from us until now...

In the first place, we were far too busy getting out production to meet the nationwide demand for Aquella. Thousands wanted to be Aquella distributors. Thousands wanted to be Aquella dealers and contractors. And many, many thousands more wanted to buy Aquella for homes, institutions, and factories. Aquella had captured the public's imagination overnight.

Furthermore, at first we thought that this anonymous attack was just the work of some small, misguided competitor. Then, when the vast extent of the campaign became apparent, we conducted an investigation into the source and motives behind the attack.

The complete details and documentary evidence are to be found in our brochure "The Truth About Aquella."

The Bureau of Standards never intended to discredit Aquella

On December 29, 1945, an unsigned letter came from the office of the United States Bureau of Standards written to Forbes Magazine and the Reader's Digest, protesting the publication of Mr. Steel's article.

After the Director of the Bureau was informed this letter was being reproduced and circulated by the hundreds of thousands for the purpose of disparaging Aquella, the Bureau refused to permit further public distribution of copies.

What the Bureau then did was to write other letters stating that the communication of December 29, 1945 was not intended to discredit Aquella.

Nevertheless, thousands of copies of that early letter still continued to be circulated through "mysterious sources."

The complete details and documentary evidence are to be found in our brochure "The Truth About Aquella."

AQUELLA...

The Controversy over "Waterproofing" before the Federal Trade Commission

For sometime back there has been a controversy between the Federal Trade Commission and the waterproofing-industry-at-large concerning the use of the word "waterproof" in advertising. What it boils down to is a definition of the word "waterproof" and not any misstatement of fact. Members of the Commission have their definition; those in the waterproofing industry have theirs. The maker of Aquella was only one of

many firms that were cited on the issue.

This issue was raised almost a year ago and a complete answer was promptly filed. No further action was taken.

In the meantime, however, there emanated from the same "mysterious sources," thousands of notices of the Commission's citation—with the dateline conspicuously omitted.

The complete details and documentary evidence are to be found in our brochure "The Truth About Aquella."

Now about AQUELLA itself!

From the time it proved itself on the French Maginot Line, Aquella has demonstrated its effectiveness against moisture and seepage in thousands of instances, in various types of masonry construction. There is no single instance where Aquella has ever failed when properly applied!

Further, we are continuing permeability tests under hydrostatic pressures which far exceed any that were ever used on Aquella by the Bureau of Standards.

Complete Documentary Evidence for you!

We have prepared a fully documented brochure which contains the complete story of Aquella.

If you are in the waterproofing industry...if you sell waterproofing...if you are counseling customers or clients on waterproofing...or if you are a buyer of waterproofing materials, you owe it to yourself to know the truth!

A copy of this brochure is yours for the asking. Simply write us on your letterhead.

PRIMA PRODUCTS, INC.

NATIONAL DISTRIBUTORS

Dept. E. 10 East 40th Street, New York 16, New York

JUNE 1946

157


this some the it, we

ermit

other ecemuella. early rough

99

CORD



The scientist must have what he needs — where and when he needs it. The utility of his laboratory is measured in terms of quick flexibility.

That is why the Firestone Laboratory has service lines for distilled water; hot water; chilled water; electricity, both AC and DC, in several different voltages including some three-phase AC; gas; vacuum; air at 20 lbs. and 100 lbs.; steam at 50 lbs. and 160 lbs.; and the necessary drains - all available at virtually any spot and with provision for adding a pipe or a wire wherever it may later be needed. Even the prefabricated partitions and the fluorescent lighting are movable! And - the whole structure is actually a building within a building; a day-lighted office building serves as the enclosure for the windowless, air-conditioned laboratory building.

Utility is one of the three major yardsticks by which the architect measures every building project and every building product. By Utility he means both usefulness—

*We have prepared a check list — "Pointers on writing architectural copy" — which enlarges on the three yardsticks of Appearance, Utility and Investment Value. Your copy will be mailed on request.


The ADD-A-PIPE, ADD-A-WIRE BUILDING

Firestone Research Laboratory Akron, Ohio

Foorhees, Walker, Foley & Smith Architects and Engineers

how the structure serves its purpose—and length of usefulness. (Appearance and Investment Value are his other yardsticks*.)

The Utility-minded readers of Architectural Record are the active



architects and engineers who prepare plans and specifications for over 80% of all investment building. They received the story of the Firestone Laboratory pointed up with 47 photographs, floor plans and detail drawings — plus a Time-Saver Standards section on service piping detail.

The Record selected this project for editorial presentation—and was selected by Voorhees, Walker, Foley & Smith to present it — because the Record's editors (architects and engineers themselves) have a way of knowing at all times just what their readers are doing, what information they need and how they want it. (Record editors are the only editors who have Dodge facilities** for finding out these things.)

Architectural Record is the intensely practical work book of the intensely practical architect-engineer who specifies building products. This is the market-place in which to keep your story told.

**Dodge reporters — 750 of them — maintain regular contact with 138,000 sources of authoritative building planning news — through some 1,845,000 personal calls and 1,383,000 telephone calls per year.

ARCHITECTURAL

RECORD

119 WEST 40TH STREET, NEW YORK 18

OTHER DODGE SERVICES

DODGE REPORTS AND DODGE STATISTICAL RESEARCH SERVICE
SWEET'S CATALOG FILES HOME OWNERS' CATALOGS
REAL ESTATE RECORD & BUILDERS' GUIDE



How Kimpreg* gives plywood the character of plastic



preover They tone pho-

raw-

ards

oject.

olev e the

y of their

tion t it.

itors

find-

inthe neer This keep

mainces of

and

ORD

IMPROVES BEAUTY-Now plywood gets a beauty treatment that's functional, too. Kimpreg*, fused to plywood, creates a beautiful plastic finish. Kimpreg can retain or cover natural grain, has fusedin color but may be painted like wood. It will not stain or fade and is easily washable.

INCREASES DURABILITY-Kimpreg plastic armor multiplies the service years of plywood. It defies weather, water, fungus, termites and rot. And it increases abrasion resistance. A bus floor of Kimpreg showed little sign of wear after 76,000 foot passages over it.



NEW KIMPREG OPPORTUNITY BOOK-

See what new and profitable possibilities Kimpreg offers in your business. Get the colorful, illustrated new Kimpreg book . . . full of information, specifications, and application ideas for plywood and Kimpreg. Mail the coupon for your free copy today.

the new plastic armor for physicod

Kimberly-Clark Corp., Neenah, Wis. Please send me the new free Kimpreg Book and names of manufacturers making plywood surfaced with Kimpreg.

PLASTIC SURFACING



		AROSO
Name		
Firm		
Type of Business		
Address		
City	Zone State	

Here's the Furnace for

THOSE G. I.




Holding down the cost of materials and equipment is important in the building of G. I. Homes, because of rigid government limitations on this type of construction. And in order to keep within the required cost range without sacrificing quality, those who are a part of the gigantic Veterans' Housing Program are looking to new materials and new equipment.

Now coming off production lines in ever-increasing quantities is the *new* Bryant steel gravity warm-air furnace. Here is a completely automatic furnace with a reasonable price which enables it to be installed in any G. I. Home with satisfaction and economy. It has many of the features incorporated in higher-priced Bryant equipment, and is the most quiet, compact and sturdy gasfired furnace ever offered in the popular-priced field.

And back of it is the famous Bryant name—the name which has signified quality gas heating equipment for more than thirty-five years. Ask the nearest Bryant representative to tell you the complete story on the new Bryant steel gravity warm-air furnace. You'll agree that it's the furnace for those G. I. Homes!

BRYANT HEATER COMPANY
17825 St. Clair Ave., Cleveland 10, Ohio
One of the Dresser Industries



NEW STEEL GRAVITY WARM-AIR FURNACE OFFERS THESE FEATURES:

- 1. Drum-tube Heat Exchanger—flue gas travel all upward, no condensation pockets, quiet operation.
- 2. Inner Radiation Shield—completely surrounds heating element to insure low casing temperature.
- 3. Axial Burner—cast iron with raised drilled ports; easily accessible, adjusted or removed.
- 4. Easy-Reach Controls—handily located for inspection and adjustment.
- 5. Compact Draft Hood—easily removed to provide access to heat exchanger tubes.
- 6. Attractive Casing—gray finished steel; compact, sturdy design.

DOUDT GAS HEATING

The most complete line of gas heating equipment in the nation!

Extra Copper Plus Molybdenum Makes Tonçan Iron



Each year, several billion dollars worth of iron and steel products are destroyed by rust. Your contribution to this staggering sum can be reduced by making sheet metal parts from Toncan Iron-the material that is rust-resistant throughout its entire cross-section.

Toncan Iron is made from highly refined openhearth iron. With this is alloyed twice as much copper as found in copper-bearing steel. Molybdenum is added to force the copper to produce its maximum protection against rust. That's why Toncan Iron has the highest rust-resistance of any ferrous material in its price class.

Another valuable quality of Toncan Iron is its high ductility. Because it's made from commercially pure iron and specially processed for working qualities, it is easy to fabricate by any method.

To give sheet metal products low cost rustresistance, make them from Toncan Iron. For complete details, write for Booklet 406, "A Few Facts About Toncan Iron for Architects and Engineers."

REPUBLIC STEEL CORPORATION GENERAL OFFICES • CLEVELAND 1, OHIO Export Department: Chrysler Building, New York 17, New York

See SWEET'S FILE

—or write us for detailed information on these Republic Steel Building Products:

Steel Building Products:

Pipe—Sheets—Roofing
Enduro Stainless Steel
Toncan Enameling Iron
Electrunite E. M.T.


Fretz-Moon Rigid Steel Conduit
Taylor Roofing Ternes
Berger Lockers, Bins, Shelving,
Kitchen Cabinets
con Steel Windows, Deors, Joista
and other building products

Republic



—for ducts, gutters, conductor pipes, roofing, siding, tunks, ventilators, skylights, hoods, and other sheet metal applications requiring rust-resistance and for corregated metal drainage products.

ORD



Freedom from Care

Early in the planning stage of a building comes an opportunity to free yourself and your client from uncertainty and time consuming details about vertical transportation.

By specifying elevators and escalators by Otis Elevator Company, this freedom from care exists before, during and after the construction period. This is because Otis provides:

- 1. PLANNING: Authoritative recommendations and layouts based on real experience. Personal analysis of your problem through our local office.
- 2. MANUFACTURING FACILITIES: All equipment (machines, motors, controls, and accessories) built by Otis for Otis . . . thus assuring minimum possibility of delays in shipment of any parts from other manufacturers. Best possible deliveries, depending on availability of raw materials.

- 3. GUARANTEE: Installation and inspection by trained Otis personnel using advanced methods. Unqualified guarantee of all equipment by the manufacturer.
- 4. CLIENT SATISFACTION: By specifying Otis Equipment you give your client his only opportunity to contract for Otis Maintenance, which relieves him of all care of equipment in the future.



Good Construction demands

THREE HINGES ON EVERY DOOR







Visible Mark of Good Construction

REMEMBER



Your prospective buyer can't see the insulation, brass piping or approved wiring you have built into a house. But there's one visible mark of good construction your prospect can see and appreciate: triple binging of doors.

You know that three hinges on a door help prevent warping – keep doors swinging free and true – and assure perfect fit of latch and lock. You also realize it may cost more to repair a single warped door than to put a third hinge on every door in the house.

Remember—"hinge-pennies" spent for a third hinge on a door are pennies that create a visible mark of good construction—pennies that create greater customer satisfaction... Triple hinge your doors. It's good business! The Stanley Works, New Britain,


STANLEY

THREE HINGES TO A DOOR

ds.

he

PUT G-E ON YOUR "SPECS"



when you look for COMPLETE conduit protection




Say G.E. when you specify rigid conduit, and make sure that there are no weak spots in the armor of your buildings' wiring systems. Give your clients the benefits of General Electric's long experience in making top quality conduit and fittings — General Electric's reputation for products that give lasting service.

If any part of the wiring system is exposed to the corrosive action of salts, acids, or alkalies, or other chemical liquids or fumes – specify asphalt-base baked enamel-coated

G-E Black conduit. For protection from atmospheric corrosion resulting from the effects of heat, cold, sunlight, moisture and weathering – specify hot-dipped, zinc-coated G-E White conduit.


Don't stop there! Specify G-E boxes and fittings for use with G-E conduit, and be assured of easy installation and added safety. Remember: Put G.E. in your "specs," and let your customers "see" the long-lasting service they will obtain.



Ask your local G-E office for information, or write to Section C663-44, General Electric Company, Appliance and Merchandise Department, Bridgeport, Conn.

GENERAL & ELECTRIC

THE FIRST FULLY AUTOMATIC CONTROL



Signed ESPECIALLY FOR PANEL HEATING WITH CONTINUOUS CIRCULATION

The relatively low temperatures required by Radiant Panels using forced hot water as the heating medium call for a control system capable of precise and continuous modulation. In the 90 Series Controller, Hoffman designers have achieved an engineering masterpiece—a fully automatic "mechanical brain" which directs the operation of the subordinate controls. It has proved its merit in thousands of forced hot water systems now in operation.


The Hoffman 90 Series Controller, activated by its Outdoor and Water Temperature Bulbs, smoothly raises or lowers the temperature of the continuously circulating water to meet changes in the need for heat. Thus the heat supply to the panels is always exactly equalized with the building heat loss. The diagrams below show the basic operating principles of this miracle Controller—for complete information, write for literature.



Radiant panels require the smooth temperature modulation provided by the Hoffman 90 Series Controller







HOFFMAN

Hoffman Specialty Co., Dept. AR-6, 1001 York St., Indianapolis. Famous for Hoffman Valves. Traps,Vacuum and Condensation Pumps, Forced Hot Water Heating Systems. Hot Water



tion

at-

ef-

and

ted

md

as-

and ing



Clean-Colorful-Durable

Terrazzo

Wherever EXTRA cleanliness is a must—and health must be protected use TERRAZZO. Schools. Hospitals, Food stores and factories, Filtration and Water plants—all profit with the added safety and spotless sanitary cleanliness that TERRAZZO offers.

TERRAZZO is easy to keep clean. Routine washing and mopping plus polishing at occasional intervals keeps TERRAZZO in excellent shape. It is highly stain-resistant and practically mar-proof under severest wear.


TERRAZZO offers these 5 advantages

- ECONOMY
- CLEANLINESS
- COMFORT
- · COLOR & DESIGN
- DEPENDABLE INSTALLATION

FREE A. I. A. KIT ANSWERS YOUR QUESTIONS ABOUT TERRAZZO

Get your fact-filled handy reference kit NOWit will show you why TERRAZZO is ideal for most any type of job.

MOSAIC ASSOCIATION, Inc.
1420 New York Ave., N. W., Dept. R., Wash. 5, D. C.



Save Installation and Maintenance Costs

Here's real protection against heavy floor traffic. Adjustable to floor level while concrete is being poured, the Boosey No. 809 eliminates many hours of installation and resetting due to errors in calculating. Heavy cover and sleeve protect countersunk brass plug and assures

straight uniform level floor. Available in 2", 3", 4" and 6" diameter sizes. Inquire today. Specify Boosey No. 809.



DIM	IEN	451	0	45	
OUTLET	A	В	D	E	- HEEVE AS
2"	64	2"	5į	ADJ	
3.	61	3.	51		10 900
4"	61	4"	51	-	CAT OFF
6"	81	6	51		AB/USTRE

Nº809

Manufacturers of complete Boosey line of Floor, Shower, Urinal and Roof Drains—Grease Interceptors, Backwater Valves, Vacuum Breakers and Fixed Air Gaps. Send for complete literature.

NORMAN BOOSEY

Monutocturing Co.

DIVISION OF

General Sales Offices: 420 North La Salle St. Chicago 10, Illinois

AMERICAN SKEIN and FOUNDRY COMPANY

FACTORY: RACINE, WISCONSIN

ESTABLISHED 1900



You don't have to be a detective to tell that a house in which floor and baseboards could separate like this wasn't built with steel joists.

Open baseboards, caused by shrinkage and settling of the floor joists, are unsightly and unsanitary. And when, as often happens, they're accompanied by plaster cracks and ill-fitting doors, there's a real headache for the owner.


You don't have to worry about these troubles in a house built with Bethlehem Open-Web Joists, because they never sag nor shrink. And if used in economical fire-safe construction, with concrete floor-slab and plaster ceiling, they are immune to termite attack and go a long way toward discouraging rats and mice-a major problem in city apartments, stores and other light-occupancy buildings.

Bethlehem Open-Web Joists are easy to install, arrive ready to erect without falsework. They'll be in good supply throughout the reconversion period, while some other materials may remain tight and of inferior quality.

Think about Bethlehem Open-Web Joists for light-occupancy commercial and institutional buildings, as well as for residential buildings. You may even discover that, at today's price levels in your locality they'll prove suitable for small homes, at little or no extra cost—and with advantages that will be readily apparent to the home owner. For full information, write to the nearest Bethlehem district office, or to Bethlehem Steel Company, Bethlehem Pa.

SEE OUR CATALOG IN SWEET'S FILE

BETHLEHEM OPEN-WEB



djustd, the llation

ssures Avail-


meter

oosey

PANY

CORD

H&H AUTOMATIC Specify the world's finest THEATRE CHAIRS DOOR SWITCHES




Automatically control the lights by opening and closing of doors as in closets, storage and refrigeration chambers, vaults etc. Numbers illustrated here are designed to switch on lights when door is opened; others available for lighting when door is closed. No. 6553 comes complete in an approved box with 23/32" and 1/2" knockouts and clamp for flexible metallic conduit. No. 2022 is mounted in a steel box, porcelain lined. No. 6550 is mounted in a porcelain base; fits all standard door switch boxes. Ratings: 6 Amps., 125 V.; 3 Amps., 250 V. Striker plates furnished with each switch.

> Write for specificationdata on the complete line.

HART & HEGEMAN DIVISION

ARROW-HART & HEGEMAN ELECTRIC COMPANY, HARTFORD G. CONN., U.S.A.



American Bodiform Theatre Chair with No. 12-123 End Stand

MERICAN Seating Company's new Bodiform Theatre A Chair introduces many improved features that are highly advantageous for architects engaged in building or remodeling theatres. New streamlined beauty of design, combined with new comfort and hazard-proof construction, provisions for easier, more economical housekeeping and smooth, silent operation, make them the finest theatre chairs ever developed. Bodiform Chairs are tested under conditions much more severe than those of actual use, in the world's largest and best-equipped seating laboratory.

CONSULT OUR SPECIALIZED SEATING ENGINEERS

Available at any time, without obligation, our specialized engineering service will provide whatever assistance you may need in developing your plans according to the latest achievements in clear-vision seating and chair-spacing economies. Write for full information.

A turn of the lever gives

NEEDLE SPRAY for
STIMULATION







SHOWER HEAD FACTS FOR ARCHITECTS

- No other shower head provides the many features of the Speakman Anystream.
- The Anystream is really three showers in one, the type of spray being adjustable instantly by the user, as shown in the sketches above.
- The Anystream is self-cleaning. In the flood position, the Anystream passes off pipe-scale, rust and sediment which clog ordinary shower heads.
- The Anystream delivers 48 individual jets of water all of which adjust simultaneously with a turn of the lever.
- The Anystream is easy to install and is designed to harmonize with all modern bathrooms.
- The Anystream is precision-made for long wear and low maintenance.
- And when the plungers are extended (in open position) after use, the shower head is immediately drained, eliminating that annoying after-drip.

See Sweet's Architectural File for a condensed Speakman catalog, or write for further information.



SPEAKMAN

SHOWERS AND FIXTURES

"The best in brass since 1869"

SPEAKMAN COMPANY, WILMINGTON 99, DELAWARE

tre

are

ing

of

oof

cal

em

rm ere

nd

RS

alst-

ing

nd on.

CORD

ELLISON BALANCED DOORS



· (SAFETY DOORS) ·

Because They Are Easy to Operate . . .

Because They Are Furnished with Highest

Quality Materials . . .

Because They Are Complete . . .

Three outstanding features of ELLISON BALANCED DOORS contribute to the solution of entrance door problems of architects and owners for their future building or alterations to entrances.

First, the ELLISON BALANCED DOOR is pivoted at the top and bottom so that when it is being opened the pull handle edge swings outward against the wind, and the opposite edge swings inward with the wind. The entire door, therefore, moves easily and quickly to one side of the door opening. Second, the easy opening and quick closing of the ELLISON BALANCED DOOR permits an uninterrupted flow of traffic. This door can be opened and will close in any wind and weather condition—with a minimum of effort. Because it is counter-balanced, it requires only a slight spring action in the closing device.

Third, the finest materials in the hands of expert ELLISON engineers have resulted in producing in ELLISON DOORS complete self-contained units, including frames, mullions, trim, saddles, and all necessary hardware.

Send for our new booklet giving illustrations and details for various types

ELLISON DOORS in the Methodist Hospital, Buckley Pavilion, Brooklyn, New York, Charles Butler and Addison Erdman, Architects Associated.

ELLISON BRONZE COMPANY, INC., Jamestown, New York



Your Copy is Ready

1946 EDITION Mo-Sai BROCHURE

With important descriptive details, specifications, application data, diagrams, plans. Profusely illustrated with color plates and photographs of typical modernization and new construction uses. Copy gladly mailed on request. Please address your nearest MO-SAI manufacturer.

MO-SAI ASSOCIATES

New Haven, Conn....The Dextone Company..... ...P. O. Box 606 Boston, Mass., Cambridge Cement Stone Company, Allston P.O. Box 41 Philadelphia, Pa......Formigli Arch'l Stone Company.....R. E. Trust Bldg. Richmond, Va......Economy Cast Stone Company......P. O. Box 1223 Greensboro, N. C......Arnold Stone Company, Inc......P. O. Box 477 Oshkosh, Wisc.......Badger Concrete Company.......191 Marion St. Salt Lake City, Utah....Otto Buehner & Company....640 Wilmington Ave. Rochester, New York.....Goodstone Mfg. Co., Inc......470 Hollenbeck St.

MO-SAI ASSOCIATES was founded in the year 1940 to standardize, improve and promote architectural slabs under the one name "MO-SAI"—Reg. U.S. Pat. Off.

MOST VERSATILE MATERIAL IN THE CONSTRUCTION INDUSTRY

"Whether it's a Cape Cod or a Skyscraper SPECIFY A MODERN SPENCER"



Today's drafting boards are loaded with plans for new projects. Into these plans go the "last word" in postwar design and construction. A deserving compliment to modern engineering is a precision-built Spencer heating unit.

You can rely on a Spencer to do the job efficiently and economically. Since 1890, there's been no more dependable name in heating. Teamed with this time-tested *know-how* is the great technical experience and resources of The Aviation Corporation.

Whatever you may require in heating, there's a Spencer steel boiler to do your job efficiently. Spencer offers not one but all types, as shown in the catalog of our complete line. More than likely it has details of units you will want to include in the specifications of new construction you are planning. Write for a copy now.

SPENCER HEATER

Division—The Aviation Corporation, Dept. A-4, Williamsport, Pa.

ward against d. The entire oor opening. I BALANCED

nd bottom so

contribute to

be opened num of effort. action in the

gineers have stained units, dware.

rarious types

du

IIDE

, aprated dernailed


D-SAI

ox 606 Box 41 It Bldg. x 1223 ox 477 ion St. in Ave. leck St.

1940 to al slabs at. Off.

A L RY

RECORD



ports are composed of 2 spans of 50-ft. Mesker Freespan Trusses topped by steel deck. Jack Nelson, contractor; Sam C. Malloy, architect, Louisville, Ky.

MESKER FREESPAN STEEL TRUSSES are ideally suited for factory buildings like the Somerset shirt factory. They are specially designed for maximum strength PLUS economy. Their ease of erection and adaptability to a wide variety of uses make them a favorite with architects and engineers the country over. From Freespans up to 59 feet and Bowstrings up to 100 feet you'll find a Mesker design to fit your need perfectly.

Complete catalogs and Design Tables on Mesker Freespan and Bowstring Trusses are ready. Write for your copies today.

EO. L. MESKER STEEL CORP.

416 N. W. First St., Evansville 8, Indiana

BOWSTRING STEEL ROOF TRUSSES . FREE SPAN STEEL FLOOR AND ROOF TRUSSES . STEEL WINDOWS . STEEL STAIRS . FIREPROOF DOORS . FIRE ESCAPES . ORNAMENTAL IRONWORK . SKYLIGHTS . ALL KINDS OF STRUCTURAL STEEL

THE FLOOR YOU'VE BEEN WAITING FOR —

Servicised Cork Rubber Tile!

ARCHITECTS & CONTRACTORS Can Now Specify this Beautiful Product

Servicised CORK RUBBER TILE is an unsurpassed floor covering wherever dignity and sheer elegance is requisite. It is designed in beautiful tones and patterns - of quiet, easy, foot tread and warmth for executive offices, homes, churches, schools, hospitals, colleges and libraries.

It is used in hotels, theatres, Railway and Airport Stations, unexcelled for beauty, wear and cleanliness; easily cleaned, resilient and noiseless.

FLOOR-LAY SEAL - (patent pending) a new, revolutionary product and method of laying rubber tile or linoleum; eliminates time-worn and laborious operations in installations. This new watertight and adhesive plastic, comes in large rolls, easy to handle. Send for information and literature.



SEE OUR LINE in Sweet's Files: also see announcements of other products

SERVICISED **PRODUCTS** 6051 West 65th Street, Chicago 38, III.

CORK-RUBBER TILE



	Mait	Inis	Coup	on I	oaay	
!	Send	informat	ion on Cori	k-Rubber	Tile	A.R.
NA	ME					
STR	TEET					
СІТ	Υ			STAT	TE	
TYP	E OF BUSI	WESS				
	SERVIC	SED	PRODI	UCTS	CORE	
60	51 West	65th	Street,	Chica	go 38.	121.

e the ction over. ectly. es on es are ana R AND • FIRE



50 38, Ill.

RECORD





Most people love the outdoors-its feeling of freedom and bigness and airiness. So, the trend to larger windows-to bring these benefits indoors-is natural.

But, of course, people like comfort, too. How to provide both was a problem, until Thermopane was

Thermopane is a transparent insulating unit composed of two or more panes of glass separated by sealed-in dehydrated air. It provides year-round insulation. The L·O·F Bondermetic Seal bonds the panes into a single unit to guard against dirt or moisture entering the air space. And the sealed-in air greatly reduces the possibility of condensation on the glass.

Manufacturers of both wood and metal windows make sash for Thermopane. For special sash, specify rabbeting wide enough to accommodate Thermopane's slightly greater thickness.

For more data on insulation values, sizes, thicknesses and types of glass than can be given here, write for a copy of our factual Thermopane book. Libbey Owens Ford Glass Company, 1766 Nicholas Bldg., Toledo 3, Ohio.



Architect George Fred Keck combined insolation with insulation in this house. The roof extension bars hot summer sun, lets in the warm slanting rays of winter sun.



LIBBEY · OWENS · FORD a Great Name in GLASS



CUTAWAY VIEW OF THERMOPANE

Your Floor Designs

FAITHFULLY REPRODUCED IN THIS PRACTICAL, LOW-COST MATERIAL

Give your imagination free rein! Choose from the wide range of deeply beautiful, marbleized Moultile colors, and arrange the individual squares into an original pattern that fits the particular project. Your drawing-board conception can be accurately reproduced in Moultile Asphalt Tile ... without resorting to costly special fabrication.

Yes, Moultile is as practical as it is beautiful. This material actually costs less, installed, than most resilient type floors. Yet it stands up to the hardest usage without visible signs of wear ... because colors and texture are uniform throughout its thickness. There's a comfortable, foot-easy resiliency to Moultile. It is quiet underfoot and non-slippery. Write today for free samples and catalog to: THOS. MOULD-ING FLOOR MFG. CO., 165 W. Wacker Drive, Dept. AR-6, Chicago 1, Ill.

THOS. MOULDING



With Moultile original designs can be economically worked out, even for small projects like this coffee shop in the Plankinton Arcade Bldg., Milwaukee, Wis. GRASSOLD & JOHNSON, Architects.



3-Way Protection for the buildings you design



...with "CZC" treated wood

You can give the buildings you design additional long life by including "CZC"-treated wood in your plans. Wood that has been pressure-impregnated with "CZC" resists decay, repels termites, and is resistant to fire.

'CZC"-treated wood is paintable, odorless, clean and safe to handle. It has all the advantages of untreated wood, plus these other life-extending features.

Wherever "CZC"-treated wood is used, maintenance costs are lower, safety is greater. Your clients will find that Du Pont Chromated Zinc Chloride pays for itself many times.

For additional information on this wood preservative that makes wood last longer, write E. I. du Pont de Nemours & Co. (Inc.), Grasselli Chemicals Department, Wilmington 98, Delaware,


DU PONT CZC

Chromated Zinc Chloride

MAKES WOOD RESIST DECAY . REPEL TERMITES . RETARD FIRE



BETTER THINGS FOR BETTER LIVING
...THROUGH CHEMISTRY



RECORD





I wanted SPEED!



gave me SPEED

OF INSTALLATION

The old law of supply and demand plus high wages and other costs make time a most important factor in any installation job. The Grand Rapids Invizible is a time and money saver because it is by far the easiest of all sash balances to install. If you, too, are interested in cutting off time at this end, make a date with the Grand Rapids Invizible. You'll be impressed with its durability, ease of adjustment and the fact that it is actually invisible — no exposed tubes — tapes and cables entirely eliminated. And, too, only 10 sizes meet 95% of all residential requirements.

SEND FOR SASH BALANCE CATALOG

which contains complete information on sash balance sizes, directions for installing, etc. All fully illustrated.



CRAND RAPIDS SASH PULLEYS

No. 103 face plate, cone bearing type and Nos. 175, 109, 110 sawtooth drive type sash pulleys cover 95% of all sash pulley requirements.



GRAND RAPIDS HARDWARE COMPANY
GRAND RAPIDS . . MICHIGAN



to ...

many colorful metal moulding ideas for adding gleaming beauty to kitchens, bathrooms, playrooms, stairs, and commercial interiors... Chromtrim Metal Mouldings follow the modern trend in architectural design.

★ Write for the new Chromtrim Catalogue No. 2 today, showing 80 dimensionally accurate profiles, designed in matching groups to serve every installation requirement. Sold only through a nation-wide distributor organization . . . see insert in Sweet's File (Architectural Edition).

R. D. WERNER CO., Inc.

Manufacturers of Metal and Plastic Products

195 FIFTH AVENUE . NEW YORK 16, N. Y.

Factories New York City - Greenville, Pa.



---Washable "TONTINE"* Shade Cloth Stands the Wear!

HERE'S WHY "TONTINE" SHADE CLOTH OFTEN GIVES UP TO 20 YEARS' SERVICE

Deep into the fibers of the fabric, the pyroxylin is driven. This chemical—a liquid form of cotton—is soaked up by the cotton fabric as a sponge soaks up water, then it hardens. Thus the two become, in effect, one material.

Pyroxylin is washable—it is impervious to water, rain, grime and dirt. When a shade made with "Tontine" becomes soiled, it can be scrubbed with soap and water, then rehung fresh and clean as ever. Service records show that "Tontine" can be scrubbed—vigorously—20 times or more without damage! And colors resist fading, stay bright for the life of the shade.

Resists crecking and pinholing. "Tontine's" pyroxylin impregnation gives it a protective finish that resists cracking and pinholing. And it gives maximum resistance to fraying and ripping. Constant improvement of all these qualities through the years makes today's "Tontine" one of the best values in its field.

Twenty years' service—that's the kind of long wear "Tontine" Shade Cloth has given many users! And this service story is important to you. It tells how you can please clients by specifying window shades that last longer, save costs. When you order window shades, just specify "Tontine." It's washable. Washing actually helps this pyroxylin-impregnated fabric to give you longer, better service! And to save you time and trouble, your "Tontine" dealer can arrange an economical washing and repairing service. Remember—for long wear, for economy—specify "Tontine"! E. I. du Pont de Nemours & Co. (Inc.), "Tontine" Sales, Newburgh, N. Y.

*"TONTINE" is Du Pont's registered trade mark for its pyroxylin-impregnated washable window shade cloth.







OPPORTUNITIES AVAILABLE

WAN FED: By large international construction company, experienced architect who can assume complete responsibility for the design of large-scale housing projects, both detached single houses and apartments. Some experience in the design of large industrial building also desirable. This is a top job for a good man. Write, giving educational background and professional experience. Location in the East. Box 132, Architectural Record, 119 West 40th St., New York 18.


WANTED: By large international construction company, experienced mechanical engineer who has a thorough knowledge of the design and layout of plumbing, heating, sewage, and sanitary work for large-scale housing projects; one with sufficient ingenuity to develop new types of plumbing and heating for low-cost individual homes especially desirable. Some experience in laying out of high and low pressure steam, water supply, power plants, etc., for industrial projects also desirable. This is a rare opportunity for a good man. Write, giving detailed educational and professional background. Location in the East. Box 134, Architectural Record, 119 W. 40th St., New York 18. WANTED: By large international construction company, experienced estimator who has had considerable experience in large-scale housing projects, both single detached units and apartments. Some experience in estimating large industrial projects also desirable. This is a very fine opportunity for the right man. Write, giving detailed background of experience and education. Location in the East. Box 136, Architectural Record, 119 W. 40th St., New York 18.

ARCHITECT: Registered, capable of preparing plans and specifications for public utility plants and office buildings. Permanent. State experience. Engineering Department, The United Light and Railways Service Co., Box 150, Davenport, Iowa.

ARCHITECTURAL DRAFTSMAN: Permanent, experienced in preparation of drawings for power plans and office buildings. State experience. Engineering Department, The United Light and Railways Service Co., Box 150, Davenport, Iowa.

ARCHITECTS WANTED: The Tennessee Valley Authority has several openings for architects in its Design Department at Knoxville, Tennessee, for work on a broad program of industrial, recreational, and power buildings. Excellent opportunity for architects desiring to become familiar with the architecture of TVA. Base entrance salaries range from \$3000 to \$4300 per annum, depending on training and experience, with provisions for automatic increases based on satisfactory performance. Interested candidates should write the Tennessee Valley Authority, Personnel Office, Knoxville, Tennessee.

YOUNG EQUIPMENT HELPS MAKE "WEATHER" TO ORDER!



__YOUNG

HEAT TRANSFER PRODUCTS

OIL COOLERS . GAS, GASOLINE, DIESEL ENGINE COOLING RADIATORS . HEAT EXCHANGERS

INTERCOOLERS • EVAPORATIVE COOLERS
GAS COOLERS • UNIT HEATERS
CONDITIONING UNITS • EVAPORATORS



ENGINE JACKET WATER COOLERS
CONVECTORS • CONDENSERS • AIR
HEATING COILS • COOLING COILS

AND A COMPLETE LINE OF AIRCRAFT HEAT TRANSFER EQUIPMENT

YOUNG RADIATOR CO., Dept. 516-F, RACINE, WIS., U.S.A.

Sales and Engineering Offices in all Principal Cities

automatic ould write nessee.

ECORD

ced archi-

arge-scale

ne experi-

rofessional

CORD. 119

layout of

projects; id heating

in laying

c., for in-

ocation in

ienced es-

projects,

estimating

ty for the education.

xperience. Co., Box

n preparaience. En-

Co., Box

as several

nessee, for buildings.

with the

\$4300 per

JUNE 1946

MATTING

information of interest to
ARCHITECTS and THEATREMEN

Floor Matting of All Kinds . . .

TO PROMOTE SAFETY FURTHER SANITATION PROTECT CARPETS

Now Available for Immediate Shipment

EZY-RUG RUBBER LINK MATTING. Traps all dirt at the door, keeps it out of sight and prevents tracking through the building, reducing cleaning costs and frequency of redecorating necessitated by dirt whirled into the air by the heating system. Modernizes and beautifies entrances and lobbies. Beveled edge. Reversible, its durability is doubled. Available with lettering and designs.

AMERITRED SOLID PLASTIC FRICTION MATTING for ramps, stairs, landings, entrances and in front of box offices. Good scrapeage. Lies flat. Comes in sections $29^{\prime\prime}$ x $62^{\prime\prime}$ x $9/64^{\prime\prime}$. Can be laid side by side for larger, or trimmed for smaller or odd-shaped areas.

AMERICAN COUNTER-TRED MATTING. A tough, durable rubber and cord matting. For use back of candy counters and around popcorn machines. Resilient, non-slip surface affords safety. Easily handled for cleaning. 5" thick, 24" wide, any length.

SAFETY STAIR TREADS AND RUNNERS • PERFORATED AND CROSS CORRUGATED MATTING • FLEXIBLE HARD WOOD LINK MATTING • SPONGE RUBBER MATTING • STEEL MATTING • COLORED RUBBER LINK MATTING • SWITCHBOARD MATTING

AMERICAN MAT CORPORATION

"America's Largest Matting Specialists"

1797 Adams Street, Toledo 2, Ohio







BURT
Free-Flow Fan
VENTILATORS

Now Give Even Longer Service

Burt Free-Flow Ventilators—both gravity and fan types—have firmly established themselves as outstanding performers. Now, addition of Burt's new "K-Frame" of angle iron welded into a one-piece, rigid structure, gives larger sizes even greater strength, durability and ease of erection. New data sheets in Sweet's or write direct for copies.

THE BURT MFG. CO.

ROOF VENTILATORS • OIL FILTERS
EXHAUST HEADS
48 East South St., Akron 11, Ohio

SEND FOR CATALOGS Burt Engineers are glad to help on plans

Where other materials often fail ...

PC FOAMGLAS INSULATION

helps control temperature, humidity and condensation-

permanently

One of the commonest complaints lodged against many insulating materials is this: that they lose insulating efficiency with the passage of time.


When you recommend PC Foamglas insulation to your clients, you need never worry about that hazard. For PC Foamglas has proved in all sorts of plants that it insulates effectively and economically—permanently.

PC Foamglas is composed of millions of tiny air cells, sealed in glass. It is impervious to moisture, vapor, the fumes of most acids. It will not burn. It repels vermin. It will not swell, or shrink, or rot, or check. It thus is totally unaffected by the elements which cause many insu-

lating materials to deteriorate with age.

PC Foamglas insulation begins, the moment it is installed, to help control temperatures, humidities, and condensation in your clients' plants. And it goes right on doing so, year after year, with the same degree of efficiency. Foamglas is the insulation that never grows old.

You will want complete information on this modern insulating material. Just check the booklets offered in the convenient coupon below. Send in the coupon. Your free copies of our helpful handbooks will be forwarded immediately, without obligation. Pittsburgh Corning Corporation, Room 138, 632 Duquesne Way, Pittsburgh 22, Pa.





THIS WON'T HAPPEN HERE

Your clients don't have to figure on repairs or replacement when they insulate their roofs with PC Foamflas. Even a break in the roofing felt that exposes the insulation to rain or melting snow will not cause PC Foamflas to flake, crack, rot, check, warp, swell or shrink. In addition, it forms such a firm, even base for roofing felt that such breaks rarely, if ever, occur.



IN THE THROW ROOM of this hosiery mill, temperature, humidity and condensation must be kept under rigid control. PC Foamglas has proved helpful in solving this and other similar insulating problems.

· Also makers of PC Glass Blocks ·

PC FOAMGLAS Waterproof INSULATION

Pittsburgh Corning Corporation Room 188, 632 Duquesne Way Pittsburgh 22, Pa.

Please send me, without obligation, your free booklets on the use of PC Foamglas insulation for:

Roofs..... Walls.... Floors.....

Name....

Address

City_____State____

tion hthis

trol, ipers

ally,

n ex-

lose

d the

com-

with

ntrol.

REGU-

-231

York.

200

URE

ITROL

ce and em-

ddi-

iron

ives

ility in

LOGS

ECORD

ities. 49



How much fuel, energy and equipment could you save by saving conditioned air?

Converting 1000 CFM of stale, odorous air to fresh air with Dorex activated carbon Air Recovery Equipment, instead of bringing in and conditioning outdoor air, saves:

100,000 BTU of installed heating capacity

3 tons of installed refrigeration

1800 KW hours of current per cooling season

1500 gallons of fuel oil or

9 tons of coal per heating season

incidental water consumption and maintenance

Per 1000 CFM of heated or cooled air saved

The above savings are figured for average temperate zones. Some installations have shown greater savings, some less. But in every case, Dorex Air Recovery has converted contaminated air to fresh air at a cost much below that required to replace it with an equal volume of outdoor air.

We will be glad to give you the details on actual savings in typical installations or estimate the savings on any existing or planned system. For full information call the nearest District Representative or write Dept. L-11.

W. B. CONNOR ENGINEERING CORP.

AIR DIFFUSION

AIR PURIFICATION

AIR RECOVERY

112 East 32nd Street



New York 16, N. Y.

CARBO-WELD DRAWING PENCILS

22 DEGREES (**)

GENERAL PENCIL COMPANY

67-73 FLEET STREET, JERSEY CITY 6, N. J.

IN CLEVELAND

IT'S THE





HOME OF THE FAMOUS

VOGUE ROOM

1000 ROOMS WITH BATH RADIO IN EVERY ROOM FIVE FINE RESTAURANTS CENTRAL DOWNTOWN LOCATION Left, 24-bour growth of B typhosus.

Right, Bacillus Typhosus.





But You CAN'T MAGNIFY the DANGER from WATER-BORNE GERMS

By installing an approved Vacuum Breaker, such as the DELANY No. 50 you prevent back-syphonage from entering into the water supply line, and STOP COMPLETELY one common source of possible contamination with probably transmission of water-borne diseases such as typhoid, dysentery, possibly polio.

The No. 50 DELANY VACUUM BREAKER meets the requirements of U. S. Bureau of Standards, and is FULLY APPROVED by most States and Municipalities.

The DELANY No. 50 VACUUM BREAKER is self policing -will function for years-will prevent back-syphonage under vacuum even though maliciously or mischievously sabotagedhas only one moving part-practically invisible when installed.



Magnified cutaway view shows No. 50 installed in a DELANY FLUSHBOY VALVE - it can be in-stalled on ANY make of

STOP

THIS


Send for Valuable Facts

EXCLUSIVE FEATURES OF THE DELANY NO. 50 VACUUM BREAKER



SIMPLEST ASSEMBLY ONLY ONE MOVING PART

PRACTICALLY INVISIBLE WHEN INSTALLED



Drawings show cross section of the No. 50 in operation. The unit, upon application of flow, expands the rubber sleeve, seals off the air vents and permits the proper flushing of the fixture.

Under the weakest vacuum, the rubber sleeve of the No. 50 collapses inwardly, seals and breaks the vacuum. This instantly prevents the slightest back-syphonage.






ECORD

Theatre and Motion Picture LIGHTING

Send Today for Valuable Information

Ask for Theatrical Lighting Catalog



How Theatres Should Be Lighted

WE INVITE YOU to make use of our theatre lighting "know-how." Consult us freely. Consult us early. We'll gladly suggest a Lighting Layout for you — based on a generation of theatre lighting experience.

CENTURY Lighting Equipment is ENGINEERED Lighting Equipment

CENTURY LIGHTING, INC. 419 W. 55th Street, New York 19, N. Y.

A MARK OF QUALITY



in home cellar construction

If you want the convenience and safety of an accessible cellar . . . If you want a leak-proof, burglat-proof, termite-proof and permanently

trouble-free cellar door which will always be a source of satisfaction to you . . . buy



BILCO

COPPER STEEL

BULKHEAD DOORS A Sound and Sensible Investment

ASK YOUR DEALER or write

164 Hallock Ave., New Haven, Conn.
SIDEWALK AND DULKHEAD DOORS . STEEL ROOF SCUTTLES



AUTOMATIC SAFETY CATCK FABRON—THE Decorative Structural Wall Finish




FABRON is a permanent fabric and plastic material which in one operation completes the structure and lends decorative interest to the wall.

FABRON is devised for interior walls and ceilings of buildings of all types where permanency, ease of upkeep and economy are essential requisites.

FREDERIC BLANK & COMPANY, INC.

Established 1913

230 PARK AVENUE, NEW YORK 17, N.Y.



where the 3-point Formula pays off

Wherever the familiar "X" symbol indicates a valve, in any piping plan, it pays to apply this proved 3-point formula for trouble-free, time-defying valve performance.

- A. Use the right type valve for the service.
- B. Place valves correctly in the line.
- C. Choose Jenkins Valves for lifetime economy!

Specify Jenkins Valves... over 600 patterns, described in the Jenkins Catalog, for every service. Jenkins Bros., 80 White St., New York 13, N. Y.



JENKINS VALVES

For Domestic, Commercial, Institutional, and Industrial Service . . . In Bronze, Iron, Cast Steel, and Corrosion-resisting alloys 125 to 600 lbs. pressure.

inish

fabric ch in s the rative

walls types and

NC.

off ve, in at for-

my! cribed Bros.,

ES adustrial arrosion-

_

CORD



Apartment Buildings of Architectural Concrete

for fast, economical construction of housing facilities

CONSTRUCTION of well-designed, and soundly built apartment buildings, offers an economical way to provide adequate housing without danger of creating future slum areas.

Architectural concrete meets every essential requirement, including firesafety, attractive appearance and economy, for apartment buildings, hotels, schools or hospitals.

This construction is economical because concrete com-

bines both architectural and structural functions in one firesafe material.


The rugged strength and durability of concrete buildings keep maintenance cost at a minimum, giving many years of service at consistently low annual cost.

Experienced members of our technical staff are available to assist architects and engineers in obtaining maximum structural advantages of concrete for apartment buildings or any project involving the use of concrete.

PORTLAND CEMENT ASSOCIATION

Dep't. 6-8, 33 West Grand Avenue, Chicago 10, Illinois

A national organization to improve and extend the uses of concrete . . . through scientific research and engineering field work



A "find" for the ARCHITECT! This comprehensive Color Guide (pages 9" x 15") displays 150 beautiful colors ranging from pastels to deep shades. Formulas are given on the reverse of each color sheet to show how the shade can be quickly made. Price, \$5.00 . . . delivered anywhere in the U. S. A. Write for your copy.

MONROE, LEDERER & TAUSSIG, INC. 606 N. AMERICAN STREET PHILA. 23, PA.



FLAT OIL PAINT

THE TRULY WASHABLE FLAT PAINT



This Efficient Roof Ventilator FITS IN ARCHITECTURALLY

The Burt Monovent Continuous Ridge Ventilator blends with roof lines—will look well on your clients' buildings. Its efficiency is high—as evidenced by its selection for installations like the huge Atomic Bomb project—its cost is low. See Sweet's or write direct for complete data sheets on Burt Monovent—now!



SEND FOR CATALOGS Burt Engineers are glad to help on plans

Hours are saved with **OZALID**

Prints made in seconds

Consider the convenience of an Ozalid machine beside your drawing board.


When you want a print, you take a sheet of Ozalid sensitized material, place your drawing on it, and feed both into the machine.

Your print is ready in seconds. For there are only two automatic steps—Exposure and Dry-Development.

What's more, it is a positive copy—not a negative—of the original. It's easier to read, completely dry, and ready for immediate use.

Offers Versatility Unlimited

In identical fashion, you turn out all 10 types of Ozalid prints —prints that have black, blue, red, or sepia lines...prints that are on paper, cloth, foil, or film.



Assume that you want additional tracings of the above floor plan so that you can add the plumbing layout to one copy; the air-conditioning layout to the next, and so on.

With Ozalid, you need never redraw the "Master" original. Just make Ozalid Intermediate prints of it; add individual details in pencil or pen. Then use the "Intermediate" to produce the desired number and type of positive OZALID PRINTS.

Write for Free Booklet No. 108. Contains 10 Types Ozalid Prints. Tells Complete Story.

OZALID

Division of General Aniline & Film Corporation Johnson City, New York Ozalid in Canada—Hughes Owens Co., Ltd., Mostreal

THESE
PATENTED

Malta

FEATURES





Mullcenter Clamp

Jamb Clamp

Give Customers The Utmost In WINDOW FRAME VALUE

JAMB CLAMP—prevents jamb from pulling away from sill end, prevents leakage, and reinforces the frame. All important joints rot-proofed.



MULL CENTER CLAMP—assures permanent water-tight sill—Mull Center Joint.


OVERHEAD PULLEYS—permit cutting frame any length down to pockets—allow any type weather stripping—give frame neater appearance.

To build good will specify Malta Frames—customers are quick to recognize their extra value.

Write for Malta Catalog

THE MALTA MFG. CO., MALTA, OHIO Top Quality Frames Malta Frames Cost Less Per Year Of Service State 1905

REVERE FLASHING IS USED THROUGHOUT



Just completed, Case Study House #11 was designed by J. R. Davison, Architect, as one of the continuing series of studies sponsored by Arts & Architecture in behalf of good design and good construction.

The merit specification basis on which materials for all these houses are selected has led to the extensive use of Revere building products in the program. In Case Study House #11, which imposes especially important requirements on the flashing, Revere Leadtex (lead coated copper)* was specified and used throughout.

Revere Sheet, Strip, and Parallel Edge Strip Copper offer enduring service for roofing, flashing, gutters, conductor pipes, skylights, termite proofing, and decorative applications.

On this subject architects will find Revere's 96-page booklet, "Copper and Common Sense," extremely useful and practical. Revere urges you to refer to it in all matters of sheet copper construction. If you do not have it, write on your letterhead for a free copy while there are still a few available. For any further help you may wish, call on the Revere Technical Advisory Service, Architectural. Revere building products include Copper Water Tube, Red-Brass Pipe; Herculoy and Sheet Copper for hot water heating and storage tanks; Extruded Shapes and Panel Sheets; as well as sheet materials for structural and decorative purposes. They are sold by Revere Distributors in all parts of the country.

Due to the acute shortage of lead, the use of lead coated copper is now officially restricted to applications "where corrosion makes the use of any other material impractical."

COPPER AND BRASS INCORPORATED

Founded by Paul Revere in 1801 230 Park Avenue, New York 17, New York Mills: Baltimore, Md.; Chicago, Ill.; Detroit, Mich.; New Bedford, Mass.; Rome, N. Y. Sales Offices in Principal Cities, Distributors Everywhere.

Listen to Exploring the Unknown on the Mutual Network every Sunday evening, 9 to 9:30 p. m., EDST.

ill end, joints

onds. auto-Drysitive commme-

d the сору; ut to never ginal. diate il den use duce pe of No. zalid ry.

-assures

IluM-Ili

-permit down to weather

neater

y Malta quick to

gola

CORD

TODAY'S STAIN



TODAY'S DESIGN



CABOT'S SHINGLE'STAINS complete the beauty of good building design. From clear, brilliant hues to New England grays and browns, Cabot has the right stain for any building, traditional or modern. Cabot's Stains give lasting protection because they contain from 60% to 90% creosote - the best wood preservative known.

CABOT'S SHINGLE STAINS - cost less than paint - are easy to apply - don't peel or blister even on green lumber.

FREE BOOKLET "Stained Houses" contains illustrations and complete information on Cabot's Creosote and Cabot's Heavy Bodied Stains. For your copy and color card, write Samuel Cabot, Inc., 1282 Oliver Oliver Bldg., Boston 9, Mass.

CABOT'S Creosote Shingle Stains

For Shingles and Clapboards



this heater moves in bag and baggage-no building to do on the job

When these heaters are built, the combustion chamberrefractory material and all-is built right into them so that each heat producing unit is shipped from the factory complete. When gas or oil is the fuel to be used it is only necessary to connect to the fuel supply and to a power line, and the heating plant is ready to function. For the

complete story on Dravo Direct Fired Heaters ask for Bulletin 509-A. Address DRAVO CORPORATION, 300 Penn Avenue, Pittsburgh, 22, Pa.





A BASIC IMPROVEMENT IN WINDOW DESIGN

NEW SELF-FITTING SILENTITE

NEW WEATHER-TIGHTNESS-"Floating" chemically treated wood sliding bars seated on resilient bronze weatherstrips-effective weather-stripping at top, bottom and meeting rail. The new Silentite is 20% more weather-tight even than the original Silentite!

EASIER OPERATION-Easy to operate when new, the Seli-Fitting Silentite continues to work smoothly with use. No sticking-no binding-famous Silentite spring suspension without weights, cords or pulleys.

NEW LOCKING SAFETY-Window locks when partly opennew patented "Silentite" lock placed at side where it will be concealed by draperies.


SIMPLE INSTALLATION-New economy in installation-sash is put in with minimum effort, yet once installed, is firmly in place.

PLUS streamlined beauty-new Curtis combination screen and storm sash unit-and many other features. For full information, write us.

CURTIS COMPANIES SERVICE BUREAU

CLINTON, IOWA





What Does "FIREPROOF" Mean?

The architect, the builder and the building inspector all said this building was fireproof. And they were right! The building didn't burn ... it collapsed under the intense heat from the combustible contents.

Modern fireproof construction alone can't prevent this hazard in a busy plant filled with equipment and materials. It takes automatic sprinkler are protection, too . . . positive, ever-vigilant Grinnell Systems

that stop fire at its source.
Grinnell Systems are your best guardians . . . built by the world's leader in fire protection ... prefabricated to Grinnellengineered layouts . . . proved dependable by 8000 fires killed in the past ten years!

Experienced engineers from nearby Grinnell office will be glad to work with you or, write Grinnell Company, Inc., Executive Offices, Providence, Rhode Island.

Automatic Sprinkler Fire Protection

MENT

TING

eated therand tight

Selt-No nsion

will sash

r full

ITE


rce.
re your to by the otection rinnell-proved es killed

will be you or, y, Inc., yidence,

idence,

ECORD

For Capacity Control PRE-ROTATION VANES



The YORK Allis-Chalmers Turbo REFRIGERATION Compressor

Capacity control to extremely low limits—approximately 10% of load—is achieved by the incorporation of Pre-Rotation Vanes in the construction of the York Allis-Chalmers Turbo Compressor. Such control is accomplished by changing the direction of the rotation of the suction gas entering the first stage wheel. Each change produces the same results as would be obtained from a separate machine of smaller size.

York Corporation, York, Pennsylvania.

Other Outstanding Features

- Low center of gravity of compressor—permitted by trough type cooler—cuts vibration, provides accessible operation.
- Stainless steel impeller blades resist erosion and corrosion assuring perfect wheel balance. Blade rivet heads are eliminated to provide unobstructed gas flow.
- Balance piston to equalize wheel thrust makes necessary only a positioning thrust bearing, and results in less bearing friction losses.
- 4. Simplified refrigerant shaft seal.
- 5. Permanently silver-sealed condenser joints.

YORK REFRIGERATION AND AIR CONDITION

HEADQUARTERS FOR MECHANICAL COOLING SINCE 1885



COMPLETE WORKING DRAWINGS

of

Fixed Hospital Furniture

designed for

U. S. Public Health Service

Layouts as shown in this issue of Architectural Record may be obtained by writing

E. H. SHELDON & COMPANY

MUSKEGON, MICHIGAN

A Superlative Product
plus
Superlative Service . . .
A Combination Hard to Beat

"F & M" Pipe Hangers, Supports and Accessories are strong and withstand terrific vibration and strain on pipes. They are safe and easy to apply and economical in cost.

Ask your jobber. If he handles the "F & M" line he has your best interest at heart. He knows the "F & M" line produces the best satisfaction with the greatest economy.

Ask your Jobber and write for catalog

FEE & MASON MANUFACTURING CO., INC.

81 Beekman St., New York 7, N. Y.

Sales Offices in Principal Cities

If It's "F & M" It's Tops


IN PIPE HANGERS



SUPPORTS







46

day.

0.

SAN

CORD

Acclaimed by

THEATREMEN EVERYWHERE

Jhe Most Desirable

MARQUEE DISPLAY

EQUIPMENT

WAGNER'S Sensational New WINDOW-TYPE MARQUEE FRAME

with which are used the popular Wagner Translucent Colored Plastic Changeable Letters and Wagner Photographic Transparencies in all sizes.

Wagner Frames permit billing space of any height or length. Installed separately and before the glass. The most effective yet also most economically maintained frame made.

WAGNER LOBBY DISPLAY UNITS AND WAGNER MOUNTING STRIP for use with colored plastic letters

Every Architect Should Have a Copy of the Wagner Catalog

which contains all necessary mechanical data and information on installing. Write for yours today.

Wagner Sign Service, Inc. 240 S. Hoyne Avenue CHICAGO 12, ILLINOIS







U. S. MAIL CHUTES & BOXES

in Bronze, Nickel Bronze, Aluminum, or Enameled Steel, maintain the Cutler Tradition of Fine Workmanship.

Catalog in Sweets

Guller Hail Chute Go Rochester 7, N.Y.





HORN FOLDING BLEACHERS and PARTITIONS

Hundreds of High Schools, Colleges and Armories have installed Horn Folding Bleachers and Electrically Operated Folding Partitions for greater flexibility of gym layout. Our experienced engineers are at your service, Mr. Architect.

> See Sweet's Catalog for Horn Details and Specifications

> > Dept. 111

HORN MANUFACTURING COMPANY

IS INADEQUATE WIRING



on out-of-date electrical system can be the single vulnerable point in a plant's output potential... the lone weak spot that prevents management from realizing the profit possibilities on orders easily obtainable.

tail... the lone weak spot that prevents management from realizing the profit possibilities on orders easily obtainable.

Only Adequate Wiring can meet the challenge of suddenly increased work loads. And wiring is adequate only when it meets future needs, insures electrical systems that meet present and future lighting and power demands at the lowest cost per kilowatt consumed.

kilowatt consumed.

In making sure of full electrical efficiency, add an Okonite engineer's experience to your

own. He represents a company that has specialized in insulated wires and cables since 1878. He can show you how to use them best. The Okonite Company, Passaic, New Jersey.

IN EXISTING BUILDINGS
Adequate Wiring reduces voltage drop when copper-skimping conductor sizes are replaced, permits high voltage cables, and unit sub-stations at load centers, corrects power factor through synchronous motors and capacitors.

IN NEW BUILDINGS, it makes unnecessary the expenditures and work disruptions of future renovations.

OKONITE

insulated wires and cables for adequate wiring at its best

4586

ery use and for every kind of

paper surface.



ARKETEX Uramatic Beauty

For artistic expression and unceasing flexibility of design. you'll find Arketex Ceramic Glazed Structural Tile perfect! The unlimited adaptability and eye appeal affords innumerable opportunities for variety. This tile retains an orderly appearance years after construction ... a pleasing beauty and freshness forever! In more than a dozen colors, the lustrous surface of the tile acts as a complement to modern lighting systems and to building materials such as glass and metal. A permanent wall and finish all in one, fire and sound proof, no periodic

painting or refinishing is necessary. With Arketex, the first cost is the only cost! Only soap and water washing is required to maintain its lustre. The finish is impervious to the action of steam, water, acids or alkalies . . . won't crack, craze, scar or peel . . . a perfect balance between beauty and durability. Today, as for over twenty years, Arketex Ceramic Corporation is producing the finest ceramic glazed structural tile available. In new construction or remodeling . . . build better . . . specify Arketex! First with the finest in ceramic glazed structural tile!

A PEACETIME PROMISE



Arketex' continuous achievement in the structural tile field assures you the finest in workmanship. Arketex . . . the standard of textured tile.



ARKETEX CERAMIC CORPORATION · BRAZIL, INDIANA

JUNE 1946

193

BUILDINGS ices volt--skimping s, and unit nters, cor-ough synapacitors.

1878. He use them company,

ING

nakes un-tures and ture reno-

for

ECORD

NOW on all **Jamison Track Port Doors**

AJUSTOFLEX TRACK PORT OPERATOR and COMPENSATOR



The ultimate in flexibility - positively co-ordinated operation of entrance door and track port without strain on the operating mechanism.



BRANCHES IN PRINCIPAL CITIES



Drinking Water is necessary in Theatres too!

HAWS Model No. 7F

Wherever people assemble there is a demand for cool, refreshing drinking water. Meet this demand with HAWS sanitary Drinking Water Fountains and Electric Ice Water Coolers. HAWS fountain designs harmonize with modern interiors and are available in color.

Plan with HAWS . . . write for catalog today!

HAWS DRINKING FAUCET CO.

1808 Harmon Street

Berkeley 3, California


Sales Representatives and Distributors in All Principal Cities







The RIGHT pencil for the RIGHT job KOH-I-NOOR PENCIL COMPANY, INC., BLOOMSBURY, NEW JERSEY



For those looking for the Iruly Distinctive!

Among the wide variety of unusually attractive "special designs," offered in Hendrick Grilles, are many developed to meet the individual ideas or requirements of architects. These, together with other exclusive Hendrick patterns, are now available without premium. Write for complete information.

Perforated Metals HENDRICK
Perforated Metal Screens HENDRICK

Architectural Grilles
Mitco Open Steel Flooring, Manufacturing Company
"Shur-Site" Treads and 38 DUNDAFF STREET, CARBONDALE, PA.
Amorgrids. Sales Offices in Principal Cities

Announcing... Authoritative up-to-the-minute Handbook

Hospital Plannii

by Charles Butler, F.A.I.A., and Addison Erdman, A.I.A.

A Case-Study Analysis of **Modern Hospitals**

With tremendous energy and insight Charles Butler and Addison Erdman, distinguished architects and hospital consultants, have made a nation-wide survey of the current adaptation of hospital architecture to changing practices in hospitalization.

The fruits of their study are set forth in "Hospital Planning" — a completely new treatise of present-day practices, based on a painstaking study of hundreds of institutions from which have been selected fifty-one modern hospitals, representing the creative efforts of more than thirty architectural firms, for illustration and discussion. "Hospital Planning" presents a textual summation of the outstanding problems in hospital architecture and shows how these problems have been met in actual practice. Generous use of illustrations, including perspectives, floor plans, elevations and photographs, make solutions abundantly clear and afford sound, applicable principles for innumerable problems to come.

For Hospital Administrators . . . Superintendents ... Doctors ... Architects

This 232-page, fully-illustrated volume, carefully organized for both reading and reference, is designed for architects and hospital groups alike. It will help trustees, administrators and doctors to visualize their problems in terms of their community needs . . . show how others are meeting similar problems . . . provide them with a basic understanding of hospital architecture so that they may intelligently discuss their problems with the architect.

It will help architects and engineers to learn of the great advances made in hospital architecture . . . to acquire a working knowledge of medical problems and hospital procedure ... to avoid the many pitfalls which beset the hospital planner.

Special Pre-Publication Price . . . \$12

You can save \$3 by sending your order today. The regular price of "Hospital Planning" will be \$15. But orders received in advance of the publication date of July 15, 1946, will be accepted at the special, pre-publication price of only \$12.

So use the convenient coupon below to take advantage of this opportunity to save \$3. The book will be sent, prepaid, promptly upon publication.

A FEW of the architectural firms whose works were selected for discussion and illustration include...

Coolidge, Shepley, Bulfinch and Abbott Samuel Hannaford & Sons Schmidt, Garden and Erickson

Jamieson and Spearl Charles B. Meyers James Gamble Rogers Mayers, Murray and Phillip Eggers and Higgins Crow, Lewis and Wick

---- Mail this coupon today -----ARCHITECTURAL RECORD BOOK DEPARTMENT 119 West 40th Street, New York 18, New York Enter my advance order forcopies of the new, 1946 edition of "Hospital Planning" by Charles Butler and Addison Erdman, at the pre-publication price of \$12 per copy. (Regular price \$15.) I enclose payment of \$...... Address.... City......Zone....State



"Hospital Planning" presents the plans of fifty-one selected modern hospitals . . . represents the creative efforts of 30 architects. Includes 32 photographs . . . 11 site plans . . . 187 floor plans . . . 38 special unit plans of rooms, wards and departments. ments . . . numerous construction details.

THE AUTHORS-Perhaps no other two authors are so well qualified by background and experience to write a volume of such broad scope and magnitude as those selected for this authoritative and technically difficult work.



Charles Butler has been closely associated with hospital planning throughout his broad professional career. As architect or consultant, his works include St. Luke's International Medical Center, Tokyo; War Demonstration Hospital at Rockefeller Institute; Goldwater Memorial Hospital.



Addison Erdman, holder of the A.I.A.'s Langley Fellowship for two successive years, is a consultant on hospitals for a number of architectural firms. His works include the Mobile Hospital Unit for the British Army in Egypt, the Private Patient Pavilion, Methodist Hospital of Brooklyn. Recently appointed as one of the five architects consultants for the Veterans Administration.

Sultants for the vectoris Administration.

HOSPITALS selected for illustration include — Cornell-New York Medical Center, New York; Goldwater Memorial Hospital, Welfare Island, New York; Methodist Hospital, Brooklyn; General Hospital, Cincinnati; Saint Vincent's Hospital, New York; Community Hospital, Cincinnati; Saint Mary's Hospital, Rochester, Minnesota; American Memorial Hospital, Reims, France; Mallinckroot Institute of Radiology, Saint Louis; Royal Victoria Hospital, Montreal; Rochester Municipal Hospital, Rochester, New York; Potts Memorial Hospital, Livingston, New York; Fort Sill Hospital, Fort Sill, Oklahoma. Saint Luke's Hospital, Spokane, Washington; Massachusetts General Hospital, Boston and many more.

JUNE 1946

195

in to nts ner for

lly

ERSEY

CORD

WURLTZER ORGATRON

Series 20 two-manual



... is specifically intended for church use

The superb church organ tone of the Wurlitzer Orgatron is a perfect accompaniment to religious services. Its modest space requirements leave a maximum of room for other architectural embellishments and its cost leaves funds to provide them. It furnishes traditional organ music with modern practicality. The Rudolph Wurlitzer* Company, Orgatron Division, Dept. AR 6, North Tonawanda, N. Y.

*The Name That Means Music to Millions.

ORCO housing SAFETY TREADS



Non-slip even when wet or oily, ORCO Housing Safety Treads are standardized to maintain quality at moderate cost. Alundum abrasive aggregate in balance of tread surface assure maximum protection underfoot.

alundum obrasive aggregate obrasive grain

Designed especially for housing projects, these long-lasting safety treads combine non-slip features with sound-absorbing qualities. Alundum abrasive grain and aggregate are imbedded in a base of semi-resilient rubber. Installation is easily accomplished by competent soft flooring contractors. Write for complete data sheets.



THE OHIO RUBBER COMPANY
SAFETY TREAD AND FLOORING DIVISION
100 BEN HUR AVE.
WILLOUGHBY . OHIO

THE MOST ECONOMICAL ELEVATOR SERVICE For 2, 3 or 4 Stories

Oildraulic Elevators will help you "keep within the budget" by making substantial savings in over-all building costs. Because the elevator car is pushed up from below—not pulled up from above—costly penthouses are eliminated, heavy load-bearing supporting columns in shaftway walls are unnecessary. And no need for a special machine room with an Oildraulic Elevator...the compact electric hydraulic power unit can be located in any

convenient space. These modern, efficient elevators—for freight or passenger service—are the result of Rotary's experience in building over 40,000 hydraulic lifting units in the past twenty years. Leading industrials and institutions find Oildraulic the most satisfactory 2, 3, or 4-story elevator

WRITE FOR AIA FILE CATALOG RE-301

Contains complete information and Architect's Preliminary Layout Data—a real aid in formulating plans. For free copy, write, Rotary Lift Company, 1105 Kentucky, Memphis (2), Tenn.

OILDRAULIC ELEVATORS

Lockwood

IDENTIFIES QUALITY IN BUILDERS' HARDWARE

LOCKWOOD identifies its Builders' Hardware with this famous Trade Mark. You will find it on cylinder locks and keys, on mortise locks, on door closers . . . a symbol of enduring quality since 1882.

To the Architect the name LOCKWOOD also signifies a line of Builders' Hardware embracing all requirements, characterized by steady advancement in feature and design . . . and a company that never hesitates to give full and prompt co-operation.

We aim to keep it that way.


R-1

LOCKWOOD HARDWARE MFG. COMPANY

Division of Independent Lock Company

Fitchburg

Massachusetts






liminary ee copy, 2), Tenn.



RECORD





THIS Castle CATALOG specify...



WILMOT CASTLE CO. 1258 University Ave.
ROCHESTER 7, N. Y.
Please send me the co

Please send me the complete Castle Catalog . . . no obligation.

 ${
m T}_{
m HE}$ Castle catalog gives you full details of

construction and performance of all Castle equipment, as well as other technical infor-

mation to help you select the most scientific-

Get your free copy, today! Fill out and

mail the attached coupon to: Wilmot Castle

Co., 1258 University Ave., Rochester 7, N. Y.

ally correct unit for the required service.

Name
Address
City State

LIGHTS AND STERILIZERS

INDEX TO ADVERTISEMENTS

Catalogs of concerns marked (s) are filed in Sweet's File (1946)

s Adam, Frank Electric Co	47
s Adams & Westlake Company	46
Aerofin Corporation	20
s Airtemp Division	41
Alan Wood Steel Company	14
s Aluminum Company of America	63
s American Brass Company	27
American Lead Pencil Company	23
American Lumber & Treating Co	18
American Mat Corporation	180
American Rediator & Standard Sanitary Cor-	
	40
peration	48
American Seating Company	168
s American Skein & Foundry Company	166
s American Telephone & Telegraph Co	40
s Anaconda Copper Mining Co	27
s Anchor Post Fence Co	148
Anthracite Institute	57
Arketex Ceramic Corporation	193
s Armstrong Cork Company	67
s Arrew Hart & Hegeman Electric Co	168
8 Aviation Corporation	171
s Barbar Calman Co	140
s Barber-Colman Company	
s Bethlehem Steel Company42	1-167
s Bilco Manufacturing Company	184
s Blank Frederic & Co., Inc	184
Blodgett, G. S., Co., Inc	134
s Blue Ridge Sales Division	8
Books	195
s Boosey Norman Mfg. Co	166
Brasco Manufacturing Company	60
s Bryant Heater Company	160
Burnham Boiler Corporation	199
Burnham Boiler Corporation	
s Burt Mfg. Co	0-186 4
s Burt Mfg. Co18)-186
s Burt Mfg. Co	0-186 4 188
Byers, A. M., Co	0-186 4 188
s Burl Mig. Co	188 Cover
Burt Mfg. Co	188 Covar 64
s Burl Mfg. Co	0-186 4 188 Cover 64 145 127
Burt Mfg. Co	188 Cover 64 145 127
s Burl Mfg. Co	0-186 4 188 Cover 64 145 127 184
Burt Mfg. Co	188 Covar 64 145 127 184 22
s Burt Mfg. Co	0-186 4 188 Cover 64 145 127 184
Burt Mfg. Co	188 Covar 64 145 127 184 22
s Burt Mfg. Co	0-186 4 188 Cover 64 145 127 184 22 41
s Burt Mfg. Co	0-186 4 188 Cover 64 145 127 184 22 41 178 54
s Burt Mfg. Co	188 4 188 64 145 127 184 22 41 178 54
s Burt Mfg. Co	188 188 188 188 64 145 127 184 22 41 178 54 183 56
s Burt Mfg. Co	188 188 Cover 64 143 127 184 22 41 178 54 183 56
s Burt Mfg. Co	188 188 188 188 64 145 127 184 22 41 178 54 183 56
s Burt Mfg. Co	188 188 CCover 64 145 127 184 22 41 178 54 183 56 188
Burt Mfg. Co	1886 44 1888 64 143 127 184 22 41 178 54 183 56 188 190
Burt Mfg. Co	188 190 121 53
s Burt Mfg. Co	1886 64 145 127 184 22 41 178 54 183 56 188 190
s Burt Mfg. Co	188 188 64 143 127 184 22 41 178 54 183 56 188 190
s Burt Mfg. Co	0-186 4 188 Cover 64 143 127 184 22 41 178 54 183 56 188 190 128 53 65 188
s Burt Mfg. Co	0-186 4 188 Cover 64 143 127 184 22 41 178 54 183 56 188 190 128 53 65 188
s Burt Mfg. Co	188 Covered 4 145 127 184 22 41 178 54 182 183 56 188 190 121 184 185 190 144 187 187 187 187 187 187 187 187 187 187
s Burt Mfg. Co	188 Covered 44 145 127 184 22 41 178 54 183 56 188 190 121 53 65 14-177 31
s Burt Mfg. Co	1888 Cover 64 145 127 184 22 41 178 54 182 183 566 188 190 121 131 170 170 170 170 170 170 170 170 170 17
s Burt Mfg. Co	188 Covered 44 145 127 184 22 41 178 54 183 56 188 190 121 53 65 14-177 31
s Burt Mfg. Co	1888 Cover 64 145 127 184 22 41 178 54 182 183 566 188 190 121 131 170 170 170 170 170 170 170 170 170 17
s Burt Mfg. Co	188 188 190 128 188 190 128 188 190 128 189 180 180 180 180 180 180 180 180 180 180
s Burt Mfg. Co	188 188 190 128 188 190 128 188 190 128 189 180 180 180 180 180 180 180 180 180 180
s Burt Mfg. Co	1888 Cover 64 143 127 184 182 183 566 188 190 124 177 31 170 155 199 199 199
s Burt Mfg. Co	188 188 190 128 188 190 128 188 190 128 189 180 180 180 180 180 180 180 180 180 180

	General Aniline & Film Corp	186	s Owens-Illinois Glass Company	66
s	General Bronze Corporation	154	Ozalid Products Division	186
8	General Electric Air Conditioning	62		
	General Electric Wiring	164	s Petroleum Heat & Power Company150	-151
	General Pencil Company	182	s Pittsburgh Corning Corporation	181
	Goodrich, B. F., Chemical Company	33	s Pittsburgh Plate Glass Company30-31-	-152
	Grand Rapids Hardware Company	176	s Pittsburgh Reflector Company	69
	Grasselli Chemicals Dept	174	s Portland Coment Association	185
	Great Lakes Steel Corporation	17	s Powers Regulator Company	180
	Grinnell Company, Inc	188	s Prima Products Inc	-157
•	Ottober Company, Inc		Protected Steel Products	37
8	Hart & Hegeman Division	168		
8	Haws Drinking Faucet Co	194	s Radio Corporation of America	61
9	Hendrick Manufacturing Co	194	s Republic Steel Corporation24-25	-161
9	Herring-Hall-Marvin Safe Co	50	s Revere Copper & Bruss, Inc	187
	Hoffman Specialty Co	165	s Ric-Wil Company	32
	Horn, A. C., Company, Inc	52	s Robertson, H. H., Co4	4-45
	Hern Manufacturing Co	190	s Roddis Lumber & Veneer Co	133
	Hotel Hollenden	182	s Rotary Lift Company	196
	Huntington Laboratories Inc.	12	s Ruberoid Co	49
		-		
-	Imperial Brass Mfg. Co	6	s Samson Cordage Works	197
8	Indiana Limestone Institute	153	s Sanymetal Products Company, Inc	137
	Institute of Product Research	148	s Scott Paper Company	68
			s Segporcel Porcelain Metals, Inc	178
1	Jamison Cold Storage Door Co	194	s Servicised Products Corp	172
	Jenkins Bros	184	s Sheldon, E. H. & Company	192
1	Johns-Manville3	14-35	s Sisalkraft Co	182
	Kimberly-Clark Corp	159	s Siegn Valve Company	
-	Kinetic Chemicals Inc	147		19
		194	Smith, Alexander & Sons Carpet Company	146
	Koh-I-Noor Pencil Company, Inc		s Smith, H. B., Co., Inc	15
1	Koppers Company	4-14	s Snead & Company	
	Libbey-Owens-Ford Glass Company	1-173	s Speakman Company	169
	Lockwood Hardware Mfg. Co	196	s Spencer Heater Division	171
	Lone Star Cement Corporation	1	s Stanley Works	163
	Louisville Cement Co., Inc.	21	s Stewart Iron Works	136
		-	s Stran-Steel Division	17
	Macomber, Inc	138	s Struthers Wells Corp	55
-	Mahon, R. C., Company	51	s Swadish Crucible Steel Co	192
	Malta Mfg. Co	186		21
	McQuay, Inc	13	s Tar & Chemical Division	25
	s Medusa Portland Cement Co	11	s Titusville Iron Werks Ce	5.5
	Mosker Bros	59	s Trane Company	132
	Mosker, Geo. L., Steel Corp	172	s Truscon Steel Company	24-25
	Milcor Steel Company	130	11 11 12 12 1 1 1 1 1 1	2.44
	Miller Company2nd	Cover	s United States Air Conditioning Corp	
	Minneapolis-Honeywell Regulator Co	70	s United States Steel Corporation Subsidiaries	21
	Monroe, Lederer & Taussig, Inc	185	s Universal Atlas Coment Company	2
	s Mo-Sai Associates	170	- Wada Manufactualna Ca	17
	Moulding, Thos. Floor Mfg. Co	174	s Wade Manufacturing Co	
			Wagner Sign Service Inc	
	s National Association of Ornamental Metal		Wall Street Journal	143
	Manufacturers	2-3	Washington Concrete Co	180
	National Chemical & Mfg. Co	135	s Webster, Warren & Co	14
*	s National Gypsum Company	58	s Werner, R. D. Co., Inc	17
	National Lead Company	39	s Wickwire Spencer Steel Co	17
	s National Terrazzo & Mosaic Association, Inc	166	Wilmot Castle Co	19
	Nesbitt, John J., Inc	149	s Wing, L. J., Mfg. Co	14
	s Newman Brothers, Inc	146	s Wood Conversion Company	13
			s Wood Preserving Division	-
	Ohio Chemical & Mfg. Co		Wurlitzer, Rudolph Company	19
	s Ohio Rubber Co	195		
	Okenite Company	190	s York Corporation	18
	s Otis Elevator Company	162	s Young Radiater Company	17

NEW YORK—H. Judd Payne, General Manager; Robert F. Marshall, Business Manager; Tom Tredwell, Advertising Mgr., Benton B. Orwig, Creative Service Manager, 119 West 40th Street; BOSTON—Howard C. Perrine, 855 Park Square Bildg., CHICAGO—C. B. Riemersma, Jack Casey, 700 Merchandise Mart; CLEVELAND—IOn. C. Jackson, 321 Hanna Bildg., LOS ANGELES—Robert P. Wettstein, Architects Bildg., 832 West 5th St., PHILADELPHIA—Tom Tredwell, 1321 Arch St.

marked (s) File (1946) 66 186 ..150-151 161 69 185 180 .156-157 37 24-25-161 187 32 ...44-45 ... 133 49 197 137 68 178 172 192 182 4th Cover 19 146 15 169 171 163 136 17 55 192 29 55 13224-25 142 s... 28 28 178 191 143 180 141 176 175 197 ... 144 ... 139 9 ... 196 189 ... 179



CORD



The trend is definitely to radiant heating. And BASE-RAY* provides radiant heating in its simplest, most practical form. With BASE-RAY, which is only 7" high and 13/4" thick, the heating units become part of the trim . . . with obvious design advantages, Smartness, beauty, comfort and heating efficiency are achieved in one stroke.

These room-long, ankle height units deliver heating-uniformity previously unattainable . . . a floor-to-ceiling differential of only 3° even in sub-zero weather. That means real cold-weather comfort. It will pay you to get all the facts.

A FEW ADVANTAGES: No structural changes are necessary for BASE-RAY installations in new homes or alteration jobs, BASE-RAY castiron units are easy to install-your Heating Contractor can do a good job. May be used with any type hot-water system as well as 2-pipe steam and vapor jobs. Specifications are extremely simple. National advertising is building enthusiastic consumer acceptance. The convenient coupon will bring complete data by return mail.

*Reg. U.S. Pat. Office



CONCEALED VALVES

This neat metal enclosure shaped like the heating unit itself, is at-tached to each end of BASE-RAY, thus completely concealing all



MOLDINGS

To provide an even more realistic baseboard appearance and to com-pensate for irregularities sometimes found in walls and floors, regular wood moldings are added at top and bottom of "Standard" BASE-RAY and at top only of "Hy-Power" units.



Write today for this FREE Booklet, which gives rat-ings and installation data on BASE-RAY Radiant

Burnham Boiler Co Irvington, New Yo													
Please send me (Guide on BASE-RA	opy of Y Radian	"Ro	atings iseboo	ard	nd s'	li	18	to	ili	la	12	io	il
Name											٠		
Address													

Burnham Boiler Corporation



IRVINGTON, N. Y., Dept. AR66 **Export Department** 50 CHURCH ST., NEW YORK 7, N. Y.



AN exclusive SUNTILE VALUE you can depend on

NEW MODULAR SIZES FOR CERAMIC MOSAIC


Now, for the first time, Architects can detail ceramic mosaic areas on their plans, simply and easily.

Ceramic Mosaic Suntile, in new modular sizes, conforms with Modular Planning Project No. 62 of The American Standards Association, sponsored by The American Institute of Architects. Unit dimensions include width of joint. 12 pieces of 1" x 1", or 6 pieces of 2" x 2" Modular Ceramic Mosaic Suntile lay out to 12" including joints.

Joint calculations are eliminated, layout


work is simplified, and drafting time is reduced. This same advantage affords even a greater saving of the tile-setter's installation time.

Modular Ceramic Mosaic Suntile can be integrated with other modular dimensioned materials and equipment, reducing the waste and labor inherent in "cut-to-fit" methods. Swimming pool markers and lanes, and decorative features in other types of construction can be correctly placed without cutting or shifting tile.



2" NOMINAL DIMENSION





The Royal never needs adjustment



Because there's nothing to adjust

The ROYAL is the only Flush Valve which has no adjustment or regulation. Its simplicity of engineering design, plus precision manufacture, insure accurate and lasting performance.

More than 4 million ROYAL Flush Valves are in daily service—including thousands of the first ROYALS installed over 36 years ago.

The ROYAL is "standard equipment" with discriminating builders and owners throughout the country. In fact, entire school systems, hotel chains, hospitals, industrial institutions, etc., use ROYALS exclusively.

For the best in Flush Valves specify Sloanremember, there are more Sloan Flush Valves sold than all other makes combined.

SLOAN VALVE COMPANY
4300 WEST LAKE STREET, CHICAGO 24, ILLINOIS

